

QUALITY

CHAIN CORP

CAT-2023
EFFECTIVE MARCH 2022



EASYSOX
THE ALTERNATIVE TRACTION DEVICE

VOLT

VIKING

KING COBRA

TRYGG

NORDIC
tire chains
engineered in Canada

QUALTRAX



FOLLOW US ON
SOCIAL MEDIA, FIND US
@QUALITYCHAINCORP







TABLE OF CONTENTS

PASSENGER **5-16**

LIGHT TRUCK / SUV **16-34**

COMMERCIAL TRUCK **35-58**

LOADER / GRADER **59-70**

TRACTOR **71-81**

GARDEN TRACTOR / SNOW BLOWER **82-83**

FORKLIFT **84-85**

SKID STEER **86-89**

ATV / UTV **90-91**

FORESTRY **92-99**

ACCESSORIES **100-115**

MISC. INFORMATION **116-119**



WARNING: READ BEFORE USE!



-  Vehicle operators unwilling to accept the possible risks with the use of any traction device installed on their vehicle such as, but not limited to, accident, vehicle damage, tire damage or wheel damage, should not use any traction device on their vehicle.
-  Traction devices may cause cosmetic scuffing on tire when installed. This condition is unavoidable on certain tread types and tire designs.
-  Wheels are also at risk of cosmetic scuffing with the use of traction devices. Wheels using low profile tires such as 35, 40, 45 and 50 series tires are at higher risk due to the short height of the tire sidewall.
-  Traction devices must hang down over the sidewall of the tire in order to stay on the tire while being used.
-  Vehicle components (ABS sensors, brake lines, etc.) can be damaged if the traction device strikes the components. Pre-fit traction device before use and check clearance.
-  Traction devices can break during the course of their service life.
(If traction device breaks, remove immediately).
-  Traveling at speeds faster than 30 MPH increases the chance of component failure.
-  Using traction devices with component failure is extremely unsafe and may cause loss of control or damage to the vehicle. **(If traction device breaks, remove immediately.)**
-  Traction devices with broken components should immediately be repaired or replaced.
-  The use of traction devices are at the risk of the vehicle operator.
-  Always wear eye protection when installing rubber bungees, tighteners or straps.

Under no circumstances will compensation for damage be considered by QCC where the damage is found to have resulted from the misuse of any traction device.

WARRANTIES

SPEEDS OVER 30 MPH, IMPROPER FIT OR IMPROPER INSTALLATION VOIDS THESE WARRANTIES

1. **DISCLAIMER OF WARRANTIES:** The products listed in this catalog are warranted free from defects in workmanship and material for thirty (30) days from the date of delivery. No other express warranty is given and no affirmation of seller, by words or action, shall constitute a warranty.
2. The above warranty is made only to the dealer, retailer or other direct customer of Quality Chain Corp. (hereby referred to as QCC). QCC makes no warranty to the end user and prohibits the transfer of the warranty given above to its direct customer or to any subsequent purchaser, including but not limited to end user.
3. **REMEDIES:** The buyer's sole remedy for breach of any warranty is limited exclusively to obtaining, at the discretion of the seller, either credit, repair or replacement of any product sold hereunder by QCC. Product shall be returned to seller's plant, transportation prepaid within thirty (30) days after the delivery to a user and within ten (10) days of discovery of alleged defect. QCC inspection shall identify the presence of any defects. Buyer shall not be entitled to recover any incidental or consequential damages. No material shall be returned without written consent of the seller.

RETURN MERCHANDISE: No merchandise will be accepted without prior written authorization. All return merchandise must be shipped freight prepaid. Collect shipments will be refused. A 20% restock/handling charge will be deducted from the credit amount.

PASSENGER





PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.

	EASYSOX <i>ES</i>	VOLT CABLE <i>QV300</i>	HIGH VOLT CABLE <i>QV500</i>	LOW VOLT CABLE <i>QV100</i>	COBRA CABLE <i>1000</i>	DIAMOND BACK <i>1500Q</i>	TYPE "PL" LINK CHAIN <i>1100</i>
TIRE SIZE	Page 16	Page 12	Page 12	Page 13	Page 13	Page 15	Page 14
185/70-13	ES72	QV319	QV539	QV119	1026	1525Q	1126
155/80-13	ES81	QV315	-	-	1014	1515Q	1114
175/80-13	ES77	QV319	QV539	QV119	1022	1525Q	1122
185/60-14	ES81	QV319	-	QV119	1018	1520Q	1118
195/60-14	ES72	QV319	QV539	QV119	1026	1525Q	1126
175/65-14	ES81	QV315	-	QV119	1018	1520Q	1118
185/65-14	ES72	QV319	QV539	QV119	1026	1525Q	1126
175/70-14	ES72	QV319	QV539	QV119	1026	1525Q	1126
185/70-14	ES77	QV323	QV539	QV123	1026	1530Q	1126
195/70-14	ES78	QV327	QV547	QV127	1030	1535Q	1130
205/70-14	ES73	QV329	QV547	QV129	1034	1540Q	1134
215/70-14	ES79	QV335	QV547	QV135	1034	1545Q	1134
195/75-14	ES79	QV323	QV539	QV129	1030	1535Q	1130
205/75-14	ES79	QV331	QV555	QV131	1034	1540Q	1134
215/75-14	ES75	QV335	QV555	QV135	1034	1545Q	1138
285/40-15	-	-	QV555	-	1038	-	1138
195/45-15	ES71	QV315	-	-	1026	1520Q	1126
195/50-15	ES81	QV319	QV539	QV119	1026	1525Q	1126
205/50-15	ES76	QV323	QV539	QV123	1026	1525Q	1126
225/50-15	ES77	QV327	QV539	QV127	1030	1535Q	1130
235/50-15	-	QV327	QV547	QV127	1034	-	1138
245/50-15	ES78	QV331	QV555	QV131	1038	-	1138
265/50-15	ES79	QV339	QV555	QV139	1042	1553Q	1142
275/50-15	-	QV339	QV555	QV139	1042	1555Q	1142
295/50-15	ES80	QV339	QV563	QV139	1046	-	1146
175/55-15	ES81	QV315	-	-	1018	1520Q	1118
185/55-15	ES81	QV319	QV539	QV119	1022	1525Q	1122
195/55-15	ES72	QV323	QV539	QV123	1022	1525Q	1122
205/55-15	ES77	QV327	QV539	QV127	1034	1535Q	1134
225/55-15	ES78	QV327	QV547	QV133	1034	1540Q	1134
155/60-15	ES71	QV311	-	-	1014	-	1114
165/60-15	ES81	QV315	-	-	1018	1520Q	1118
175/60-15	ES72	QV319	QV539	QV119	1018	1525Q	1118
185/60-15	ES72	QV323	QV539	QV123	1026	1525Q	1126
195/60-15	ES77	QV327	QV539	QV127	1030	1530Q	1130
205/60-15	ES78	QV331	QV547	QV131	1030	1535Q	1130
215/60-15	ES73	QV331	QV547	QV133	1034	1540Q	1138
225/60-15	ES79	QV331	QV547	QV133	1034	1547Q	1134
235/60-15	ES79	QV335	QV555	QV135	1038	1550Q	1138
245/60-15	ES74	QV339	QV555	QV139	1042	1553Q	1142
255/60-15	ES75	QV343	QV563	QV143	1042	1555Q	1142
265/60-15	-	-	QV563	-	1042	1555Q	1142
275/60-15	ES83	QV729	QV563	-	1046	1555Q	1146
145/65-15	ES71	QV315	-	-	1014	-	1114
165/65-15	ES72	QV319	QV539	QV119	1022	1525Q	1122
175/65-15	ES77	QV319	QV539	QV119	1022	1525Q	1122
185/65-15	ES77	QV323	QV539	QV123	1030	1530Q	1130
195/65-15	ES73	QV329	QV547	QV129	1030	1535Q	1130



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



PASSENGER

	EASYSOX <i>ES</i>	VOLT CABLE <i>QV300</i>	HIGH VOLT CABLE <i>QV500</i>	LOW VOLT CABLE <i>QV100</i>	COBRA CABLE <i>1000</i>	DIAMOND BACK <i>1500Q</i>	TYPE "PL" LINK CHAIN <i>1100</i>
TIRE SIZE	Page 16	Page 12	Page 12	Page 13	Page 13	Page 15	Page 14
205/65-15	<i>ES79</i>	<i>QV329</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1540Q</i>	<i>1134</i>
215/65-15	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
225/65-15	<i>ES74</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1038</i>	-	<i>1138</i>
235/65-15	<i>ES75</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
255/65-15	<i>ES83</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
175/70-15	<i>ES78</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1022</i>	<i>1530Q</i>	<i>1122</i>
185/70-15	<i>ES73</i>	<i>QV323</i>	<i>QV547</i>	<i>QV123</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
185/70-15.5	<i>ES79</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1030</i>	-	<i>1130</i>
195/70-15	<i>ES79</i>	<i>QV329</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1540Q</i>	<i>1134</i>
205/70-15	<i>ES74</i>	<i>QV335</i>	<i>QV555</i>	<i>QV133</i>	<i>1034</i>	<i>1545Q</i>	<i>1134</i>
215/70-15	<i>ES74</i>	<i>QV335</i>	<i>QV555</i>	<i>QV131</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
225/70-15	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV137</i>	<i>1038</i>	<i>1553Q</i>	<i>1138</i>
235/70-15	<i>ES83</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
255/70-15	<i>ES83</i>	<i>QV735</i>	<i>QV571</i>	-	<i>1046</i>	<i>2319LW</i>	<i>1146</i>
185/75-15	-	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1026</i>	<i>1535Q</i>	<i>1130</i>
195/75-15	<i>ES74</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1030</i>	<i>1540Q</i>	<i>1130</i>
205/75-15	<i>ES75</i>	<i>QV335</i>	<i>QV555</i>	<i>QV133</i>	<i>1034</i>	<i>1547Q</i>	<i>1138</i>
215/75-15	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
225/75-15	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV139</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
235/75-15	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	-	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
155/80-15	<i>ES78</i>	<i>QV319</i>	<i>QV539</i>	<i>QV119</i>	<i>1022</i>	-	<i>1122</i>
165/80-15	<i>ES73</i>	<i>QV323</i>	<i>QV547</i>	<i>QV123</i>	<i>1022</i>	<i>1530Q</i>	<i>1122</i>
175/80-15	<i>ES79</i>	<i>QV329</i>	<i>QV547</i>	<i>QV129</i>	-	-	-
195/80-15	<i>ES75</i>	<i>QV335</i>	<i>QV563</i>	<i>QV135</i>	<i>1034</i>	<i>1545Q</i>	<i>1134</i>
215/80-15	<i>ES82</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1038</i>	-	<i>1142</i>
205/40-16	<i>ES81</i>	<i>QV323</i>	<i>QV539</i>	-	<i>1026</i>	<i>1525Q</i>	<i>1126</i>
215/40-16	<i>ES81</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1030</i>	<i>1525Q</i>	<i>1130</i>
195/45-16	<i>ES81</i>	<i>QV319</i>	<i>QV539</i>	<i>QV119</i>	<i>1026</i>	<i>1525Q</i>	<i>1126</i>
205/45-16	<i>ES76</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1030</i>	<i>1525Q</i>	<i>1130</i>
215/45-16	<i>ES76</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
225/45-16	<i>ES77</i>	-	<i>QV539</i>	<i>QV133</i>	<i>1034</i>	<i>1540Q</i>	<i>1134</i>
245/45-16	<i>ES78</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
255/45-16	<i>ES73</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	-	<i>1138</i>
185/50-16	<i>ES72</i>	<i>QV319</i>	<i>QV539</i>	<i>QV119</i>	<i>1026</i>	<i>1525Q</i>	<i>1126</i>
195/50-16	<i>ES76</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1030</i>	<i>1530Q</i>	<i>1130</i>
205/50-16	<i>ES77</i>	<i>QV327</i>	<i>QV539</i>	<i>QV127</i>	<i>1034</i>	<i>1535Q</i>	<i>1134</i>
215/50-16	<i>ES77</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	-	<i>1134</i>
225/50-16	<i>ES78</i>	<i>QV335</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1547Q</i>	<i>1134</i>
235/50-16	<i>ES73</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
245/50-16	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1038</i>	<i>1555Q</i>	<i>1138</i>
255/50-16	<i>ES79</i>	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
265/50-16	-	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	<i>1042</i>	-	<i>1142</i>
175/55-16	<i>ES76</i>	<i>QV319</i>	<i>QV539</i>	<i>QV119</i>	<i>1026</i>	<i>1525Q</i>	<i>1126</i>
185/55-16	<i>ES77</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
195/55-16	<i>ES77</i>	<i>QV327</i>	<i>QV539</i>	<i>QV129</i>	<i>1030</i>	<i>1540Q</i>	<i>1130</i>
205/55-16	<i>ES78</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1540Q</i>	<i>1134</i>
215/55-16	<i>ES73</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1545Q</i>	<i>1134</i>
225/55-16	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.

	EASYSOX <i>ES</i>	VOLT CABLE <i>QV300</i>	HIGH VOLT CABLE <i>QV500</i>	LOW VOLT CABLE <i>QV100</i>	COBRA CABLE <i>1000</i>	DIAMOND BACK <i>1500Q</i>	TYPE "PL" LINK CHAIN <i>1100</i>
TIRE SIZE	Page 16	Page 12	Page 12	Page 13	Page 13	Page 15	Page 14
235/55-16	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1038</i>	-	<i>1138</i>
245/55-16	<i>ES74</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
255/55-16	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
175/60-16	<i>ES77</i>	<i>QV323</i>	<i>QV547</i>	<i>QV123</i>	<i>1026</i>	<i>1525Q</i>	<i>1122</i>
185/60-16	<i>ES78</i>	<i>QV327</i>	<i>QV547</i>	<i>QV127</i>	<i>1030</i>	<i>1530Q</i>	<i>1122</i>
195/60-16	<i>ES73</i>	<i>QV329</i>	<i>QV547</i>	<i>QV129</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
205/60-16	<i>ES79</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1542Q</i>	<i>1138</i>
215/60-16	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
225/60-16	<i>ES74</i>	<i>QV339</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
235/60-16	<i>ES75</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
245/60-16	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
255/60-16	<i>ES83</i>	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	-	-	-
195/65-16	<i>ES79</i>	<i>QV329</i>	<i>QV547</i>	<i>QV129</i>	<i>1034</i>	<i>1542Q</i>	<i>1134</i>
205/65-16	<i>ES74</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
215/65-16	<i>ES74</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
225/65-16	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV143</i>	<i>1038</i>	<i>1553Q</i>	<i>1138</i>
235/65-16	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
205/70-16	<i>ES75</i>	<i>QV335</i>	<i>QV555</i>	<i>QV133</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
215/70-16	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
225/70-16	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	<i>QV143</i>	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
185/75-16	<i>ES74</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1030</i>	<i>1542Q</i>	<i>1130</i>
195/75-16	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
205/75-16	-	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
215/75-16	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	<i>QV143</i>	<i>1042</i>	-	<i>1142</i>
225/75-16	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	-	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
175/80-16	<i>ES75</i>	<i>QV331</i>	<i>QV555</i>	<i>QV131</i>	<i>1030</i>	-	<i>1134</i>
195/80-16	-	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1038</i>	-	<i>1142</i>
205/80-16	-	<i>QV343</i>	<i>QV571</i>	<i>QV143</i>	<i>1042</i>	-	<i>1142</i>
215/80-16	-	<i>QV343</i>	<i>QV575</i>	-	-	-	-
205/40-17	<i>ES76</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1026</i>	<i>1530Q</i>	<i>1126</i>
215/40-17	<i>ES77</i>	<i>QV327</i>	<i>QV539</i>	<i>QV127</i>	<i>1034</i>	<i>1535Q</i>	<i>1134</i>
225/40-17	<i>ES77</i>	-	<i>QV539</i>	<i>QV133</i>	-	-	-
235/40-17	<i>ES77</i>	<i>QV335</i>	<i>QV547</i>	<i>QV133</i>	<i>1034</i>	<i>1540Q</i>	<i>1134</i>
245/40-17	<i>ES78</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
255/40-17	<i>ES73</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
265/40-17	-	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
275/40-17	<i>ES79</i>	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
285/40-17	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1046</i>	-	<i>1146</i>
195/45-17	<i>ES77</i>	<i>QV323</i>	<i>QV539</i>	<i>QV129</i>	<i>1030</i>	-	<i>1130</i>
205/45-17	<i>ES77</i>	<i>QV327</i>	<i>QV539</i>	<i>QV127</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
215/45-17	<i>ES78</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1030</i>	<i>1540Q</i>	<i>1130</i>
225/45-17	<i>ES78</i>	<i>QV335</i>	<i>QV547</i>	<i>QV133</i>	<i>1034</i>	<i>1545Q</i>	<i>1134</i>
235/45-17	<i>ES73</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
245/45-17	<i>ES79</i>	<i>QV343</i>	<i>QV555</i>	<i>QV137</i>	<i>1042</i>	<i>1547Q</i>	<i>1138</i>
255/45-17	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
205/50-17	<i>ES73</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1545Q</i>	<i>1134</i>
215/50-17	<i>ES79</i>	<i>QV331</i>	<i>QV547</i>	<i>QV133</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
225/50-17	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



PASSENGER

	EASYSOX <i>ES</i>	VOLT CABLE <i>QV300</i>	HIGH VOLT CABLE <i>QV500</i>	LOW VOLT CABLE <i>QV100</i>	COBRA CABLE <i>1000</i>	DIAMOND BACK <i>1500Q</i>	TYPE "PL" LINK CHAIN <i>1100</i>
TIRE SIZE	Page 16	Page 12	Page 12	Page 13	Page 13	Page 15	Page 14
235/50-17	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
245/50-17	<i>ES74</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
255/50-17	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
175/55-17	<i>ES77</i>	<i>QV323</i>	<i>QV539</i>	<i>QV123</i>	<i>1022</i>	<i>1530Q</i>	<i>1122</i>
205/55-17	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV131</i>	<i>1034</i>	-	<i>1134</i>
215/55-17	<i>ES74</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
225/55-17	<i>ES74</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
235/55-17	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
245/55-17	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
255/55-17	<i>ES83</i>	<i>QV729</i>	<i>QV563</i>	<i>QV143</i>	<i>1673</i>	<i>2317LW</i>	<i>2219QC</i>
275/55-17	-	<i>QV741</i>	<i>QV575</i>	-	<i>1673</i>	<i>2319LW</i>	<i>3210QC</i>
215/60-17	<i>ES75</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
225/60-17	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
235/60-17	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1146</i>
215/65-17	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
225/65-17	<i>ES80</i>	<i>QV343</i>	<i>QV571</i>	<i>QV143</i>	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
235/65-17	<i>ES82</i>	<i>QV729</i>	<i>QV571</i>	-	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
245/65-17	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	-	<i>1046</i>	<i>2319LW</i>	<i>1146</i>
215/70-17	<i>ES82</i>	<i>QV729</i>	<i>QV571</i>	-	<i>1042</i>	-	<i>1142</i>
225/70-17	-	<i>QV729</i>	<i>QV575</i>	-	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
215/35-18	<i>ES77</i>	<i>QV327</i>	<i>QV539</i>	<i>QV127</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
225/35-18	<i>ES77</i>	<i>QV329</i>	<i>QV547</i>	<i>QV133</i>	<i>1034</i>	<i>1542Q</i>	<i>1134</i>
235/35-18	<i>ES77</i>	<i>QV331</i>	<i>QV547</i>	<i>QV133</i>	<i>1038</i>	<i>1542Q</i>	<i>1138</i>
245/35-18	<i>ES78</i>	<i>QV331</i>	<i>QV555</i>	<i>QV131</i>	<i>1038</i>	<i>1545Q</i>	<i>1138</i>
255/35-18	<i>ES73</i>	<i>QV335</i>	<i>QV555</i>	<i>QV135</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
265/35-18	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
275/35-18	<i>ES79</i>	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	<i>1046</i>	<i>1550Q</i>	<i>1146</i>
285/35-18	<i>ES80</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1046</i>	-	<i>1146</i>
295/35-18	<i>ES80</i>	<i>QV729</i>	<i>QV555</i>	-	-	-	-
205/40-18	<i>ES77</i>	<i>QV327</i>	<i>QV539</i>	<i>QV127</i>	<i>1030</i>	<i>1535Q</i>	<i>1130</i>
215/40-18	<i>ES78</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1034</i>	<i>1547Q</i>	<i>1134</i>
225/40-18	<i>ES73</i>	<i>QV335</i>	<i>QV547</i>	<i>QV133</i>	<i>1034</i>	<i>1547Q</i>	<i>1134</i>
235/40-18	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV137</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
245/40-18	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
255/40-18	<i>ES79</i>	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
265/40-18	<i>ES74</i>	<i>QV343</i>	<i>QV555</i>	<i>QV143</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
275/40-18	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
285/40-18	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	-	-	-
215/45-18	<i>ES79</i>	<i>QV331</i>	<i>QV547</i>	<i>QV131</i>	<i>1038</i>	<i>1547Q</i>	<i>1138</i>
225/45-18	<i>ES79</i>	<i>QV335</i>	<i>QV555</i>	<i>QV139</i>	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
235/45-18	<i>ES74</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
245/45-18	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
255/45-18	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
275/45-18	<i>ES80</i>	<i>QV735</i>	<i>QV563</i>	-	<i>1046</i>	<i>2319LW</i>	<i>1146</i>
215/50-18	<i>ES75</i>	<i>QV339</i>	<i>QV563</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
225/50-18	<i>ES75</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1553Q</i>	<i>1142</i>
235/50-18	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1046</i>	<i>1553Q</i>	<i>1146</i>
245/50-18	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1146</i>



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.

	EASYSOX <i>ES</i>	VOLT CABLE <i>QV300</i>	HIGH VOLT CABLE <i>QV500</i>	LOW VOLT CABLE <i>QV100</i>	COBRA CABLE <i>1000</i>	DIAMOND BACK <i>1500Q</i>	TYPE "PL" LINK CHAIN <i>1100</i>
TIRE SIZE	Page 16	Page 12	Page 12	Page 13	Page 13	Page 15	Page 14
255/50-18	ES83	QV343	QV563	QV143	1042	-	-
205/55-18	ES75	QV339	QV563	QV139	1038	-	1138
215/55-18	ES75	QV339	QV571	QV139	1042	1553Q	1142
225/55-18	ES80	QV339	QV563	QV143	1042	1553Q	1142
235/55-18	ES80	QV729	QV563	-	1046	-	1146
255/55-18	ES82	QV735	QV575	-	1046	2319LW	1146
215/60-18	ES80	QV339	QV571	QV139	1042	1555Q	1142
225/60-18	ES82	QV729	QV571	-	1046	1555Q	1146
235/60-18	ES82	QV729	QV571	-	1046	2317LW	1146
225/65-18	-	QV735	QV575	-	1046	2319LW	1146
235/65-18	-	QV735	QV575	-	1046	2319LW	1146
245/30-19	ES78	QV331	QV555	QV131	1038	1545Q	1138
265/30-19	-	QV339	QV555	QV139	1042	1550Q	1142
275/30-19	ES79	QV343	QV571	QV143	1042	1553Q	1142
285/30-19	ES80	QV729	QV571	QV143	1673	2319LW	-
295/30-19	ES80	QV735	QV563	-	1673	2317LW	-
215/35-19	-	QV331	QV547	-	1034	1542Q	1134
225/35-19	ES79	QV323	QV539	QV123	1038	1545Q	1138
235/35-19	ES79	QV323	QV539	QV137	1038	1547Q	1138
245/35-19	ES75	QV339	QV555	QV139	1042	1550Q	1142
255/35-19	ES79	QV343	QV555	QV143	1042	1550Q	1142
265/35-19	ES80	QV339	QV563	QV143	1046	1555Q	1146
275/35-19	ES80	QV343	QV555	QV143	1046	1555Q	1146
285/35-19	ES80	QV343	QV563	QV143	1046	-	1146
295/35-19	ES80	-	QV563	QV143	-	-	-
225/40-19	ES79	QV339	QV555	QV139	1038	1545Q	1138
235/40-19	ES80	QV339	QV555	QV139	1042	1553Q	1142
245/40-19	ES75	QV339	QV555	QV139	1042	1553Q	1142
255/40-19	ES75	QV343	QV563	QV143	1042	1555Q	1142
275/40-19	ES80	QV729	QV563	-	1046	2319LW	1146
285/40-19	ES83	QV343	QV571	QV143	-	-	-
225/45-19	ES74	QV339	QV563	QV139	1042	1550Q	1142
235/45-19	ES74	QV343	QV563	QV143	1042	1555Q	1142
245/45-19	ES80	QV343	QV563	QV143	1046	1555Q	1146
255/45-19	ES83	QV729	QV563	QV143	1046	2319LW	1146
225/50-19	ES80	QV339	QV563	QV143	1042	1553Q	1142
235/50-19	ES83	QV729	QV571	QV143	1046	1555Q	1146
235/55-19	ES82	QV729	QV575	-	1046	1555Q	1146
275/55-19	ES84	QV747	QV579	-	1679	2327LW	2228QC
175/60-19	ES80	QV335	-	-	1034	-	1134
155/70-19	ES80	-	-	-	-	-	-
225/30-20	ES73	QV335	QV555	-	1038	1545Q	1138
235/30-20	ES79	QV339	QV555	-	1038	1547Q	1138
245/30-20	ES79	QV339	QV555	QV139	1042	1550Q	1142
255/30-20	ES79	QV343	QV563	-	1042	1553Q	1142
265/30-20	ES80	-	-	-	-	-	-
275/30-20	ES80	QV729	QV571	-	1046	1555Q	1146
285/30-20	ES80	QV729	QV563	QV143	-	-	-

PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.




NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



PASSENGER

	EASYSOX <i>ES</i>	VOLT CABLE <i>QV300</i>	HIGH VOLT CABLE <i>QV500</i>	LOW VOLT CABLE <i>QV100</i>	COBRA CABLE <i>1000</i>	DIAMOND BACK <i>1500Q</i>	TYPE "PL" LINK CHAIN <i>1100</i>
TIRE SIZE	Page 16	Page 12	Page 12	Page 13	Page 13	Page 15	Page 14
295/30-20	<i>ES80</i>	<i>QV729</i>	<i>QV563</i>	-	<i>1673</i>	<i>2319LW</i>	-
225/35-20	<i>ES79</i>	<i>QV343</i>	<i>QV563</i>	-	<i>1038</i>	<i>1550Q</i>	<i>1138</i>
235/35-20	<i>ES80</i>	<i>QV339</i>	<i>QV555</i>	-	<i>1042</i>	<i>1550Q</i>	<i>1142</i>
245/35-20	<i>ES75</i>	<i>QV339</i>	<i>QV555</i>	<i>QV139</i>	<i>1042</i>	<i>1550Q</i>	<i>1146</i>
255/35-20	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
265/35-20	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
275/35-20	<i>ES80</i>	<i>QV729</i>	<i>QV563</i>	-	<i>1046</i>	<i>2319LW</i>	<i>1146</i>
285/35-20	<i>ES83</i>	<i>QV735</i>	<i>QV563</i>	-	-	-	-
315/35-20	<i>ES84</i>	<i>QV751</i>	<i>QV579</i>	-	-	<i>2321LW</i>	-
245/40-20	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
255/40-20	<i>ES83</i>	<i>QV729</i>	<i>QV563</i>	-	<i>1661</i>	-	-
235/45-20	-	<i>QV343</i>	<i>QV571</i>	<i>QV143</i>	<i>1665</i>	<i>1555Q</i>	<i>1146</i>
195/50-20	<i>ES80</i>	-	-	-	-	-	-
235/50-20	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	-	<i>1042</i>	<i>1555Q</i>	<i>1142</i>
175/55-20	<i>ES80</i>	<i>QV335</i>	-	-	<i>1034</i>	-	<i>1134</i>
275/30-21	-	-	<i>QV563</i>	-	-	-	-
245/35-21	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>QV143</i>	<i>1046</i>	-	<i>1146</i>
255/35-21	<i>ES83</i>	-	-	-	-	-	-
265/35-21	<i>ES83</i>	-	-	-	-	-	-
265/40-21	<i>ES83</i>	<i>QV741</i>	<i>QV579</i>	-	-	-	-
275/45-21	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	-	-	-	-
235/30-22	<i>ES80</i>	<i>QV729</i>	<i>QV571</i>	-	<i>1046</i>	<i>1555Q</i>	<i>1146</i>
245/30-22	<i>ES80</i>	<i>QV729</i>	<i>QV571</i>	<i>QV143</i>	<i>1046</i>	-	<i>1146</i>



**VOLT****PREMIUM PASSENGER**

Volt cable chains give better traction than ladder-style chains and longer wear using cross cables made of alloy rollers. The diagonal cross cable design provides a smooth ride and easy installation.

RUBBER ADJUSTERS INCLUDED

⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	BUNGEE
QV311	9	QV1332	QV1172
QV315	10	QV1334	
QV319	10	QV1336	
QV323	10	QV1338	
QV327	10		
QV329	11		
QV331	11	QV1340	
QV335	11	QV1342	
QV339	11		
QV343	11	QV1344	QV1174



STANDARD PACKAGING

Packed 1 Pair Per Bag
4 Pair Per Master Carton

HIGH VOLT**PREMIUM EMERGENCY VEHICLES
(POLICE, FIRE & AMBULANCE)**

High Volt cable chains were engineered to meet the high-performance needs of emergency vehicles. Long lasting alloy rollers and high strength aircraft cable provide maximum traction and durability. Easy installation with no rubber adjusters needed.

⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
QV539	11	QV9380
QV547	12	QV9384
QV555	12	QV9388
QV563	12	
QV571	12	QV9390
QV575	13	QV9394
QV579	13	
QV583	13	QV9398



STANDARD PACKAGING

Packed 1 Pair Per Box
4 Pair Per Master Carton

LOW VOLT

With clearances on passenger vehicles getting smaller, the Low Volt design provides a safe alternative to SAE Class "S" chains with a minimal clearance profile on the inside of the tire. Following along with the Volt product line, the Low Volt offers easy installation, alloy rollers for longer life, and the ability to fit a wider range of tires than many of the comparable link tire chain products.

RUBBER ADJUSTERS INCLUDED

⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	BUNGEE
QV119	8	QV1172
QV123	9	
QV127	9	
QV129	9	
QV131	9	
QV133	9	
QV135	10	
QV137	10	QV1174
QV139	10	
QV143	10	



STANDARD PACKAGING
Packed 1 Pair Per Bag
4 Pair Per Master Carton

COBRA™ CABLE CHAIN

Tough carbon steel rollers provide traction and long wear. The low profile steel rollers allow increased tire-to-road contact, resulting in better stability as well as considerable reduction in noise and vibration.

⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
1014	5	10.4"	56.8"
1018	5		61.8"
1022	6		66.8"
1026	5	11.6"	61.8"
1030	6		66.8"
1034	6		71.8"
1038	7	12.8"	71.8"
1042	8		76.0"
1046	9		76.0"

For Traction That
Bites!



STANDARD PACKAGING
Packed 1 Pair Per Bag
4 Pair Per Master Carton

**RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY**
PART # 0212
SEE PAGE 107 FOR DETAILS





"PL" LINK CHAINS

Passenger Limited type chains are an all link construction made of tough carbon steel. These chains are designed for use on cars with minimal clearance, using original equipment size tires with highway tread.

Packed 1 Pair Per Bag



STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
1114	9	5414	1134	12	5420
1118	10		1138	13	
1122	11		1142	13	
1126	10	5419	1146	14	5422
1130	11				

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0212
SEE PAGE 107 FOR DETAILS





PASSENGER

DIAMOND BACK PASSENGER

Diamond Back is a premium European design tire chain. Square link construction with a diamond pattern for excellent traction, a smooth ride, and long wear.

⚠ DO NOT USE ON TRAILERS



STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
1505Q	9	1572
1510Q	9	1574
1515Q	9	1576
1520Q	9	
1525Q	10	1578
1530Q	10	1582
1535Q	10	1584
1540Q	11	1588
1542Q	11	
1545Q	11	
1547Q	13	1592
1550Q	13	1594
1553Q	13	1596
1555Q	13	



INSIDE FASTENER



STANDARD PACKAGING
Packed 1 Pair Per Bag
4 Pair Per Master Carton

PARTS AND PIECES

STOCK NUMBER	APPLICATION	STANDARD PACKAGE	WEIGHT PER PKG (LBS)
F-3	1500Q & 2300LW / 2500Q Quick Hook	10	0.5
L-3	1500Q & 2300LW / 2500Q Lock System		1.0
R-1	1500Q Rubber End		2.5
R-2	2500Q & 2300LW Rubber End		2.5
PK-1	1500Q & 2300LW Repair Kit		0.5
PK-2	2500Q Repair Kit		1.0
S-1	1500Q & 2300LW / 2500Q Short Hook		0.6



F-3



L-3



R-1 & R-2



PK-1 & PK-2



S-1

Quick and Easy to Install

EASYSOX



PASSENGER / LIGHT TRUCK & SUV



THE TRUE ALTERNATIVE TO TRADITIONAL TRACTION

- LIGHT WEIGHT:** EASIER TO HANDLE AND STORE!
- LESS BULKY:** CAN BE APPLIED TO VEHICLES WITH EXTREMELY LOW CLEARANCE!
- LOWER RISK:** OF VEHICLE DAMAGE, NO METAL OR PLASTIC COMPONENTS THAT CAN STRIKE VEHICLE OR SCUFF WHEELS!

- ⚠ CHECK YOUR VEHICLE OWNER'S MANUAL BEFORE USING EASYSOX TO CONFIRM CLEARANCE FOR TRACTION DEVICES. FOLLOW ALL VEHICLE GUIDELINES.
- ⚠ EASYSOX ARE ONLY INTENDED FOR USE ON SNOW OR ICE COVERED SURFACES; NOT ON WET OR DRY PAVEMENT. REMOVE EASYSOX WHEN THE ROAD SURFACE IS CLEAR.
- ⚠ REFER TO THE FITMENT CHART TO CONFIRM THE EASYSOX IS THE CORRECT SIZE FOR THE TIRE YOU ARE APPLYING IT TO. PRIOR TO USE, PRE-FIT EASYSOX TO VEHICLE TIRE TO VERIFY CORRECT FITMENT.

EASY AS...



QUALITY
CHAIN CORP

For more info please visit our website:
WWW.EASYSOX.COM



EASYSOX are an environmentally friendly traction alternative. No steelmaking or zinc plating involved in the manufacturing process.

DISCLAIMER:

EASYSOX ARE GUARANTEED FOR WORKMANSHIP AND MATERIAL ONLY. THE CONSUMER ACCEPTS ALL LIABILITY IN USE OF THIS PRODUCT. ALL SALES ARE FINAL.

LIGHT TRUCK / SUV



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD / ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDER <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
7.50-16	-	QV741	QV579	1669	2519Q	2319LW	2221QC	2821QC	2121SLC	S315	2437HH
7-17.5	-	QV343	QV571	-	-	-	2211QC	2811QC	-	-	-
8-19.5	-	QV747	QV579	1663	2514Q	2314LW	2221QC	2821QC	2121SLC	-	2439HH
225/60-14	ES78	QV327	QV547	-	2519Q	2319LW	2209QC	2809QC	2109SLC	-	-
195/75-14	ES79	QV323	QV539	1030	1535Q	-	2209QC	2809QC	2109SLC	-	-
215/75-14	ES75	QV335	QV555	1661	1545Q	-	2216QC	2816QC	2116SLC	-	-
275/60-15	ES83	QV729	QV563	1661	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2437HH
225/70-15	ES75	QV343	QV563	1661	2515Q	2315LW	2216QC	2816QC	2116SLC	-	2433HH
235/70-15	ES83	QV729	QV563	1661	2517Q	2317LW	2216QC	2816QC	2116SLC	-	2435HH
245/70-15	-	QV729	QV563	1661	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2437HH
255/70-15	ES83	QV735	QV575	1669	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2435HH
265/70-15	ES83	QV735	QV575	1665	2519Q	2319LW	2221QC	2821QC	2121SLC	-	2437HH
285/70-15	-	QV747	QV579	1661	2529Q	2329LW	2219QC	2819QC	2119SLC	-	-
295/70-15	-	QV751	QV579	-	-	-	-	-	-	-	-
215/75-15	ES80	QV339	QV563	1661	2515Q	2315LW	2216QC	2816QC	2116SLC	-	2433HH
225/75-15	ES80	QV343	QV563	1661	2515Q	2315LW	2216QC	2816QC	2116SLC	-	2435HH
235/75-15	ES82	QV729	QV571	1661	2517Q	2317LW	2219QC	2819QC	2119SLC	-	2435HH
245/75-15	ES83	QV729	QV575	1669	2521Q	2321LW	2229QC	2829QC	2129SLC	-	2437HH
255/75-15	ES83	QV735	QV575	1669	2527Q	2327LW	2228QC	2828QC	2128SLC	-	2439HH
265/75-15	ES83	QV741	QV575	1669	2519Q	2319LW	3210QC	3810QC	3110SLC	S315	2437HH
275/75-15	ES84	QV747	QV575	1675	2521Q	2321LW	2228QC	2828QC	2128SLC	-	3428HH
285/75-15	-	QV747	QV579	-	-	-	-	-	-	-	-
225/50-16	ES78	QV335	QV547	1034	1547Q	-	2209QC	2809QC	2109SLC	-	-
215/55-16	ES73	QV331	QV547	-	2515Q	2315LW	-	-	-	-	-
235/60-16	ES75	QV339	QV563	1042	1550Q	2315LW	1142	-	-	-	-
255/60-16	ES83	QV729	QV555	1665	2517Q	2317LW	2229QC	2829QC	2129SLC	-	-
265/60-16	-	QV729	QV571	-	-	-	3210QC	3810QC	3110SLC	-	3410HH
275/60-16	ES83	QV741	QV575	1669	2519Q	2319LW	3210QC	3810QC	3110SLC	-	2439HH
285/60-16	-	QV735	QV579	1673	-	-	2228QC	2828QC	2128SLC	-	2439HH
235/65-16	ES80	QV729	QV563	1665	2517Q	2317LW	2216QC	2816QC	2116SLC	-	-
245/65-16	-	QV729	QV563	1661	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2435HH
255/65-16	ES82	QV735	QV575	1669	2519Q	2319LW	2229QC	2829QC	2129SLC	S315	2435HH
265/65-16	ES83	QV735	QV575	1661	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2437HH
275/65-16	ES83	QV741	QV579	1673	2521Q	2321LW	2228QC	2828QC	2128SLC	-	-
285/65-16	ES84	QV747	QV579	-	-	-	-	-	-	-	-
215/70-16	ES80	QV343	QV563	1661	2515Q	2315LW	2216QC	2816QC	2116SLC	-	2435HH
225/70-16	ES82	QV343	QV571	1661	2517Q	2317LW	2219QC	2819QC	2119SLC	-	2435HH
235/70-16	ES82	QV729	QV571	1665	2519Q	2319LW	2229QC	2829QC	2129SLC	S315	2435HH
245/70-16	ES83	QV735	QV575	1669	2519Q	2319LW	2229QC	2829QC	2129SLC	S315	2435HH
255/70-16	ES83	QV735	QV575	1669	2519Q	2319LW	2221QC	2821QC	2121SLC	-	2437HH
265/70-16	ES83	QV741	QV579	1669	2529Q	2329LW	3210QC	3810QC	3110SLC	S320	3410HH
275/70-16	ES84	QV747	QV579	1675	2521Q	2321LW	2228QC	2828QC	2128SLC	S320	3428HH
285/70-16	ES84	QV751	QV579	1675	-	-	3229QC	3829QC	3129SLC	S320	3429HH
305/70-16	ES85	QV757	QV583	1678	2536Q	2335LW	3228QC	3828QC	3128SLC	S295	2440HH
315/70-16	ES188	QV751	QV841	-	-	-	3231QC	3831QC	3131SLC	S296	3431HH
205/75-16	ES80	QV343	QV563	1661	1550Q	-	2216QC	2816QC	2116SLC	-	2433HH
215/75-16	ES82	QV729	QV571	1669	2515Q	2315LW	2216QC	2816QC	2116SLC	-	-

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDD <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
225/75-16	<i>ES82</i>	<i>QV729</i>	<i>QV571</i>	<i>1665</i>	2517Q	<i>2317LW</i>	2219QC	2819QC	2119SLC	S315	2435HH
235/75-16	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1665</i>	2519Q	<i>2319LW</i>	2219QC	2819QC	2119SLC	S315	2435HH
245/75-16	<i>ES83</i>	<i>QV741</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	2221QC	2821QC	2121SLC	S315	2437HH
255/75-16	-	<i>QV747</i>	<i>QV575</i>	-	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S315	2439HH
265/75-16	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1675</i>	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S320	2439HH
275/75-16	<i>ES85</i>	<i>QV747</i>	<i>QV579</i>	-	-	-	3228QC	3828QC	3128SLC	-	2439HH
285/75-16	<i>ES85</i>	<i>QV751</i>	<i>QV583</i>	<i>1678</i>	2533Q	<i>2328LW</i>	3228QC	3828QC	3128SLC	S295	2440HH
295/75-16	<i>ES85</i>	<i>QV757</i>	-	<i>1678</i>	2521Q	<i>2321LW</i>	3229QC	3829QC	3129SLC	S296	2440HH
315/75-16	<i>ES195</i>	<i>QV761</i>	QV853	-	2536Q	<i>2337LW</i>	3231QC	3831QC	3131SLC	S296	2441HH
205/80-16	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	<i>1661</i>	-	-	2229QC	2829QC	2129SLC	-	-
215/80-16	-	<i>QV729</i>	<i>QV575</i>	-	-	-	2219QC	2819QC	2119SLC	-	2435HH
235/80-16	<i>ES83</i>	<i>QV741</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	2219QC	2819QC	2119SLC	S320	-
265/80-16	-	<i>QV747</i>	<i>QV583</i>	-	-	-	-	-	-	-	-
215/85-16	<i>ES83</i>	<i>QV729</i>	<i>QV575</i>	<i>1665</i>	2519Q	<i>2319LW</i>	2219QC	2819QC	2119SLC	S315	2435HH
225/85-16	-	<i>QV735</i>	<i>QV575</i>	<i>1669</i>	2517Q	<i>2317LW</i>	2221QC	2821QC	2121SLC	S315	2437HH
235/85-16	<i>ES84</i>	<i>QV741</i>	<i>QV579</i>	<i>1669</i>	2521Q	<i>2321LW</i>	2221QC	2821QC	2121SLC	S320	2437HH
245/85-16	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	-	-	3228QC	3828QC	3128SLC	S322	2439HH
255/85-16	<i>ES85</i>	<i>QV751</i>	<i>QV583</i>	<i>1675</i>	2514Q	<i>2314LW</i>	3228QC	3828QC	3128SLC	S322	2439HH
265/85-16	<i>ES85</i>	-	<i>QV583</i>	<i>1675</i>	2519Q	<i>2319LW</i>	3228QC	3828QC	3128SLC	S322	2439HH
275/85-16	<i>ES195</i>	-	-	<i>1675</i>	-	-	3228QC	3828QC	3128SLC	S295	3428HH
245/45-17	<i>ES79</i>	<i>QV343</i>	<i>QV555</i>	<i>1042</i>	<i>1547Q</i>	-	<i>1138</i>	-	-	-	-
235/50-17	<i>ES79</i>	<i>QV339</i>	<i>QV555</i>	<i>1042</i>	<i>1550Q</i>	-	<i>1142</i>	-	-	-	-
275/50-17	-	<i>QV735</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	3210QC	3810QC	3110SLC	-	3410HH
235/55-17	<i>ES75</i>	<i>QV343</i>	<i>QV563</i>	<i>1661</i>	<i>1553Q</i>	<i>2315LW</i>	<i>1142</i>	-	-	-	-
255/55-17	<i>ES83</i>	<i>QV729</i>	<i>QV563</i>	<i>1673</i>	2517Q	<i>2317LW</i>	2219QC	2819QC	2119SLC	S315	-
265/55-17	-	<i>QV735</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	3210QC	3810QC	3110SLC	S315	3410HH
275/55-17	-	<i>QV741</i>	<i>QV575</i>	<i>1673</i>	2519Q	<i>2319LW</i>	3210QC	3810QC	3110SLC	S320	3410HH
235/60-17	<i>ES80</i>	<i>QV343</i>	<i>QV563</i>	<i>1665</i>	<i>1555Q</i>	<i>2317LW</i>	<i>1142</i>	-	-	S315	-
245/60-17	<i>ES83</i>	<i>QV729</i>	<i>QV563</i>	<i>1665</i>	2517Q	<i>2317LW</i>	2229QC	2829QC	2129SLC	S315	-
255/60-17	<i>ES83</i>	<i>QV735</i>	<i>QV571</i>	<i>1673</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	S315	2435HH
265/60-17	-	<i>QV735</i>	<i>QV575</i>	<i>1673</i>	2519Q	<i>2319LW</i>	3210QC	3810QC	3110SLC	S320	3410HH
275/60-17	<i>ES83</i>	<i>QV741</i>	<i>QV579</i>	<i>1675</i>	2529Q	<i>2329LW</i>	2228QC	2828QC	2128SLC	S320	3427HH
285/60-17	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1675</i>	2527Q	<i>2327LW</i>	3228QC	3828QC	3128SLC	S295	2439HH
305/60-17	-	-	-	-	-	-	3235QC	3835QC	3135SLC	S296	3435HH
225/65-17	<i>ES82</i>	<i>QV343</i>	<i>QV571</i>	<i>1665</i>	2517Q	<i>2317LW</i>	2216QC	2816QC	2116SLC	-	-
235/65-17	<i>ES82</i>	<i>QV729</i>	<i>QV571</i>	<i>1665</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	S315	2435HH
245/65-17	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	S315	2439HH
255/65-17	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1663</i>	2519Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S320	2439HH
265/65-17	<i>ES83</i>	<i>QV741</i>	<i>QV579</i>	<i>1663</i>	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S320	2439HH
275/65-17	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2514Q	<i>2314LW</i>	2228QC	2828QC	2128SLC	S320	2439HH
285/65-17	<i>ES84</i>	<i>QV747</i>	<i>QV583</i>	<i>1678</i>	2514Q	<i>2314LW</i>	3227QC	3827QC	3127SLC	-	3427HH
305/65-17	-	<i>QV751</i>	<i>QV583</i>	<i>1680</i>	2536Q	<i>2335LW</i>	3229QC	3829QC	3129SLC	S295	3429HH
225/70-17	<i>ES82</i>	<i>QV729</i>	<i>QV575</i>	<i>1665</i>	2517Q	<i>2317LW</i>	2219QC	2819QC	2119SLC	-	-
235/70-17	<i>ES83</i>	<i>QV735</i>	<i>QV579</i>	<i>1665</i>	2519Q	<i>2319LW</i>	2219QC	2819QC	2119SLC	S315	2439HH
245/70-17	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1673</i>	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S315	3410HH
255/70-17	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S320	2439HH
265/70-17	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1675</i>	2521Q	<i>2314LW</i>	3228QC	3828QC	3128SLC	S320	2439HH



LIGHT TRUCK/SUV

MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408





PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.

Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDUED <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
275/70-17	ES85	QV751	QV583	1675	2533Q	2328LW	3228QC	3828QC	3128SLC	S322	2439HH
285/70-17	ES85	QV753	QV583	1678	2533Q	2328LW	3228QC	3828QC	3128SLC	S295	3428HH
295/70-17	ES188	QV761	QV583	1678	2536Q	2337LW	3229QC	3829QC	3129SLC	S295	3429HH
305/70-17	ES85	QV761	QV853	1678	2536Q	-	3229QC	3829QC	3129SLC	S296	3429HH
315/70-17	ES195	QV761	QV853	1681	2536Q	-	3231QC	3831QC	3131SLC	S372	3431HH
225/75-17	ES83	QV729	QV575	1669	2519Q	2319LW	2219QC	2819QC	2119SLC	S315	-
235/75-17	ES83	QV735	QV579	1675	2521Q	2321LW	3210QC	3810QC	3110SLC	S320	3410HH
245/75-17	ES84	QV741	QV579	1675	2521Q	2321LW	2228QC	2828QC	2128SLC	S320	2439HH
255/75-17	ES84	QV751	QV579	1663	2527Q	2327LW	2228QC	2828QC	2128SLC	S320	2439HH
265/75-17	-	QV751	QV583	1678	2521Q	2321LW	3228QC	3828QC	3128SLC	S322	-
285/75-17	ES188	QV757	QV583	1680	2536Q	-	3229QC	3829QC	3129SLC	S295	3429HH
235/80-17	ES84	QV747	QV579	1669	2519Q	2319LW	2221QC	2821QC	2121SLC	S320	2437HH
255/80-17	ES85	QV835	QV583	1675	2514Q	2314LW	2237QC	2837QC	2137SLC	-	2437HH
275/80-17	ES195	-	-	1680	-	-	3231QC	3831QC	3131SLC	S295	3431HH
245/85-17	-	-	-	1675	-	-	2228QC	2828QC	2128SLC	S322	-
215/70-17.5	ES82	QV729	QV575	1673	2515Q	2315LW	2219QC	2819QC	2119SLC	S315	2435HH
225/70-17.5	-	-	-	1663	2517Q	2317LW	2214QC	2814QC	2114SLC	S315	2439HH
235/70-17.5	ES83	QV735	QV579	-	-	-	2221QC	2821QC	2121SLC	-	-
245/70-17.5	ES83	QV741	QV579	1675	2521Q	2321LW	3228QC	3828QC	3128SLC	S320	-
275/70-17.5	-	-	-	-	2519Q	2319LW	3228QC	3828QC	3128SLC	S295	2440HH
205/75-17.5	-	QV729	QV575	1661	2529Q	2329LW	-	-	-	-	-
215/75-17.5	ES83	QV729	QV575	1673	2519Q	2319LW	2229QC	2829QC	2129SLC	S315	2437HH
225/75-17.5	ES83	QV735	QV575	1665	2521Q	2321LW	-	-	-	-	-
235/75-17.5	ES84	QV741	QV579	1665	2514Q	2314LW	3228QC	3828QC	3128SLC	S320	2439HH
245/75-17.5	ES84	QV741	QV579	-	-	-	3228QC	3828QC	3128SLC	-	2439HH
265/45-18	-	QV729	QV571	-	-	-	-	-	-	-	-
275/45-18	-	QV735	QV563	1673	2519Q	2319LW	2229QC	2829QC	2129SLC	-	-
285/45-18	-	QV735	QV563	-	-	-	-	-	-	-	-
295/45-18	ES83	QV735	QV575	1673	2529Q	2329LW	3210QC	3810QC	3110SLC	-	2439HH
285/50-18	ES83	QV735	QV575	1675	2529Q	2329LW	2228QC	2828QC	2128SLC	-	2439HH
225/55-18	ES80	QV729	QV563	1661	2517Q	2317LW	2229QC	2829QC	2129SLC	-	2435HH
235/55-18	ES80	QV729	QV563	1673	2517Q	2317LW	2229QC	2829QC	2129SLC	-	-
245/55-18	ES83	QV735	QV571	1673	2519Q	2319LW	2229QC	2829QC	2129SLC	-	-
255/55-18	ES82	QV735	QV575	1673	2519Q	2319LW	2229QC	2829QC	2129SLC	S320	2435HH
265/55-18	-	QV735	QV575	1673	2519Q	2319LW	3210QC	3810QC	3110SLC	-	3410HH
275/55-18	ES83	QV741	QV579	1675	2521Q	2321LW	3210QC	3810QC	3110SLC	S322	3410HH
285/55-18	-	QV747	-	1679	2527Q	2327LW	3210QC	3810QC	3110SLC	S295	3410HH
225/60-18	ES82	QV729	QV571	1661	1555Q	-	2229QC	2829QC	2129SLC	-	2435HH
235/60-18	ES82	QV729	QV571	1669	2517Q	2317LW	2229QC	2829QC	2129SLC	S320	2439HH
245/60-18	ES83	QV735	QV575	1673	2519Q	2319LW	2229QC	2829QC	2129SLC	S320	2439HH
255/60-18	ES83	QV741	QV579	1675	2521Q	2321LW	3210QC	3810QC	3110SLC	S320	3410HH
265/60-18	ES83	QV741	QV579	1675	2521Q	2321LW	3228QC	3828QC	3128SLC	S320	-
275/60-18	ES84	QV747	QV579	1675	2527Q	2327LW	3228QC	3828QC	3128SLC	S320	2439HH
285/60-18	ES84	QV751	QV579	1675	2527Q	2327LW	3228QC	3828QC	3128SLC	S295	2439HH
295/60-18	-	QV751	QV579	-	-	-	3227QC	3827QC	3127SLC	-	3427HH
305/60-18	ES85	QV753	QV841	1681	2536Q	-	3231QC	3831QC	3131SLC	S296	3431HH
325/60-18	ES85	QV753	QV853	-	2536Q	-	3231QC	3831QC	3131SLC	S296	3431HH

LIGHT TRUCK / SUV



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
 EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDUED <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
225/65-18	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1673</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	-	-
235/65-18	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1673</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	S320	2439HH
255/65-18	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1675</i>	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	S320	2439HH
265/65-18	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2527Q	<i>2327LW</i>	3228QC	3828QC	3128SLC	S320	2439HH
275/65-18	<i>ES85</i>	<i>QV751</i>	<i>QV583</i>	<i>1675</i>	2533Q	<i>2328LW</i>	3228QC	3828QC	3128SLC	S320	2439HH
285/65-18	<i>ES85</i>	<i>QV751</i>	<i>QV583</i>	<i>1678</i>	2533Q	<i>2328LW</i>	3228QC	3828QC	3128SLC	S295	3429HH
295/65-18	<i>ES188</i>	QV841	-	<i>1680</i>	2536Q	-	3229QC	3829QC	3129SLC	-	3429HH
305/65-18	<i>ES188</i>	-	-	<i>1681</i>	2536Q	-	3231QC	3831QC	3131SLC	S296	3431HH
325/65-18	<i>ES199</i>	<i>QV761</i>	QV853	<i>1681</i>	-	-	3231QC	3831QC	3131SLC	S298	3431HH
355/65-18	-	QV881	-	-	-	-	3254QC	3854QC	3154SLC	-	-
225/70-18	<i>ES83</i>	<i>QV735</i>	<i>QV579</i>	<i>1663</i>	-	-	2221QC	2821QC	2121SLC	S320	2435HH
235/70-18	-	<i>QV741</i>	<i>QV579</i>	-	-	-	2221QC	2821QC	2121SLC	-	2437HH
245/70-18	-	<i>QV747</i>	<i>QV579</i>	-	-	-	2228QC	2828QC	2128SLC	-	-
255/70-18	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2527Q	<i>2327LW</i>	2228QC	2828QC	2128SLC	S320	2439HH
265/70-18	<i>ES85</i>	<i>QV751</i>	<i>QV583</i>	<i>1678</i>	2533Q	<i>2328LW</i>	2228QC	2828QC	2128SLC	S322	2439HH
275/70-18	<i>ES85</i>	<i>QV753</i>	<i>QV583</i>	<i>1680</i>	2536Q	-	3228QC	3828QC	3128SLC	S322	3428HH
285/70-18	<i>ES85</i>	<i>QV757</i>	<i>QV583</i>	<i>1681</i>	2536Q	-	3231QC	3831QC	3131SLC	S295	3431HH
295/70-18	<i>ES195</i>	QV835	<i>QV583</i>	<i>1681</i>	2536Q	-	3231QC	3831QC	3131SLC	S296	3431HH
305/70-18	<i>ES195</i>	QV859	-	-	2539Q	-	3231QC	3831QC	3131SLC	S296	3431HH
245/75-18	<i>ES84</i>	<i>QV751</i>	<i>QV583</i>	-	-	-	2228QC	2828QC	2128SLC	-	-
265/75-18	<i>ES85</i>	QV837	<i>QV583</i>	<i>1679</i>	-	-	3229QC	3829QC	3129SLC	S322	3429HH
285/75-18	<i>ES195</i>	<i>QV761</i>	-	<i>1681</i>	2536Q	<i>2337LW</i>	3231QC	3831QC	3131SLC	S296	3431HH
235/80-18	-	-	-	<i>1675</i>	2521Q	<i>2321LW</i>	2228QC	2828QC	2128SLC	S322	2439HH
275/45-19	<i>ES83</i>	<i>QV741</i>	<i>QV575</i>	<i>1673</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	S320	-
285/45-19	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1663</i>	2529Q	<i>2329LW</i>	3210QC	3810QC	3110SLC	S322	3410HH
225/50-19	<i>ES80</i>	<i>QV339</i>	<i>QV563</i>	<i>1042</i>	<i>1553Q</i>	-	<i>1142</i>	-	-	-	-
235/50-19	<i>ES83</i>	<i>QV729</i>	<i>QV571</i>	<i>1673</i>	-	<i>2319LW</i>	-	-	-	-	-
245/50-19	<i>ES83</i>	<i>QV729</i>	<i>QV571</i>	<i>1673</i>	2519Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	-	2435HH
255/50-19	<i>ES82</i>	<i>QV735</i>	<i>QV575</i>	<i>1669</i>	2529Q	<i>2329LW</i>	2229QC	2829QC	2129SLC	-	2435HH
265/50-19	<i>ES83</i>	<i>QV741</i>	<i>QV575</i>	<i>1675</i>	2529Q	<i>2329LW</i>	3210QC	3810QC	3110SLC	-	2437HH
275/50-19	<i>ES83</i>	<i>QV735</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
225/55-19	<i>ES82</i>	<i>QV729</i>	<i>QV571</i>	<i>1673</i>	2517Q	<i>2319LW</i>	2229QC	2829QC	2129SLC	-	-
235/55-19	<i>ES82</i>	<i>QV729</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	2219QC	2819QC	2119SLC	-	2437HH
245/55-19	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	<i>1669</i>	2519Q	<i>2319LW</i>	3210QC	3810QC	3110SLC	-	3410HH
255/55-19	<i>ES83</i>	<i>QV735</i>	<i>QV579</i>	<i>1663</i>	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	-	3410HH
265/55-19	<i>ES83</i>	<i>QV741</i>	-	-	2521Q	<i>2321LW</i>	3210QC	3810QC	3110SLC	-	3410HH
275/55-19	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1679</i>	2527Q	<i>2327LW</i>	2228QC	2828QC	2128SLC	-	-
285/55-19	-	<i>QV747</i>	<i>QV579</i>	-	-	-	2228QC	2828QC	2128SLC	-	-
255/60-19	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2521Q	<i>2321LW</i>	2228QC	2828QC	2128SLC	-	2437HH
285/60-19	<i>ES85</i>	-	<i>QV583</i>	-	-	-	3229QC	3829QC	3129SLC	-	3429HH
235/65-19	<i>ES83</i>	<i>QV741</i>	-	-	-	-	2228QC	2828QC	2128SLC	-	2439HH
255/65-19	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2527Q	<i>2327LW</i>	2228QC	2828QC	2128SLC	-	2439HH
275/65-19	<i>ES85</i>	-	-	-	-	-	3228QC	3828QC	3128SLC	-	-
225/70-19.5	<i>ES85</i>	<i>QV747</i>	<i>QV579</i>	<i>1663</i>	2521Q	<i>2321LW</i>	2214QC	2814QC	2114SLC	S320	2437HH
235/70-19.5	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
245/70-19.5	<i>ES188</i>	<i>QV751</i>	<i>QV583</i>	<i>1675</i>	2514Q	<i>2314LW</i>	3228QC	3828QC	3128SLC	S322	2439HH
265/70-19.5	<i>ES188</i>	<i>QV757</i>	<i>QV583</i>	<i>1680</i>	2529Q	<i>2329LW</i>	2237QC	2837QC	2137SLC	S322	2440HH



LIGHT TRUCK/SUV

MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408





Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDED <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
275/70-19.5	ES195	QV837	QV583	-	-	-	-	-	-	-	-
285/70-19.5	ES195	QV853	-	2315	2527Q	2327LW	2246QC	2846QC	2146SLC	-	-
305/70-19.5	ES199	QV869	-	-	2514Q	2314LW	2239QC	2839QC	2139SLC	-	-
215/75-19.5	-	QV747	QV579	-	-	-	-	-	-	-	-
225/75-19.5	ES85	QV747	QV579	1663	2521Q	2321LW	2214QC	2814QC	2114SLC	S320	2437HH
305/30-20	-	-	-	-	-	-	3257QC	3857QC	3157SLC	-	-
285/35-20	-	QV735	QV563	-	-	-	-	-	-	-	-
315/35-20	-	QV751	QV579	-	2521Q	2321LW	-	-	-	-	-
235/40-20	ES75	-	-	-	-	-	-	-	-	-	-
255/40-20	ES83	QV729	QV563	-	2521Q	2321LW	-	-	-	-	-
265/40-20	ES83	QV729	QV571	-	-	-	-	-	-	-	-
275/40-20	ES83	QV735	QV575	1663	2521Q	2321LW	3210QC	3810QC	3110SLC	-	3410HH
285/40-20	ES83	QV741	QV579	-	-	-	-	-	-	-	-
295/40-20	ES83	QV735	QV579	1675	2521Q	2321LW	2228QC	2828QC	2128SLC	-	2439HH
305/40-20	ES84	-	-	-	-	-	-	-	-	-	-
235/45-20	ES80	QV343	QV571	1665	-	2319LW	-	-	-	-	-
245/45-20	ES82	QV729	QV575	1669	2519Q	2319LW	2229QC	2829QC	2129SLC	S295	-
255/45-20	ES82	QV729	QV575	1669	2519Q	2319LW	2229QC	2829QC	2129SLC	-	-
265/45-20	ES83	QV735	QV575	1673	2519Q	2319LW	3210QC	3810QC	3110SLC	-	2437HH
275/45-20	ES83	QV741	QV579	1669	2521Q	2321LW	2229QC	2829QC	2129SLC	S298	2439HH
285/45-20	ES83	QV741	QV579	-	-	-	-	-	-	-	-
295/45-20	ES84	QV747	QV579	1679	2527Q	2327LW	2228QC	2828QC	2128SLC	-	2439HH
305/45-20	ES85	QV741	QV579	1679	2514Q	2314LW	3229QC	3829QC	3129SLC	-	3429HH
235/50-20	ES82	QV343	QV571	1042	1555Q	-	1142	-	-	-	-
245/50-20	ES83	QV735	QV575	1669	2521Q	2321LW	3210QC	3810QC	3110SLC	-	3410HH
255/50-20	ES83	QV735	QV579	1675	2521Q	2321LW	3210QC	3810QC	3110SLC	-	3410HH
265/50-20	ES83	QV747	QV579	1675	2527Q	2327LW	3210QC	3810QC	3110SLC	-	3410HH
275/50-20	ES84	QV747	QV579	1679	2527Q	-	2228QC	2828QC	2128SLC	S320	-
285/50-20	ES84	QV751	QV579	1679	2533Q	2328LW	3228QC	3828QC	3128SLC	S295	3428HH
295/50-20	-	QV751	QV579	1680	-	-	3228QC	3828QC	3128SLC	-	3428HH
305/50-20	ES85	QV761	QV583	1681	2536Q	2328LW	3228QC	3828QC	3128SLC	S295	2440HH
325/50-20	-	QV751	QV841	-	-	-	3231QC	3831QC	3131SLC	-	3431HH
235/55-20	ES83	QV735	QV575	1669	2519Q	2319LW	3210QC	3810QC	3110SLC	-	2437HH
255/55-20	ES84	QV747	QV579	1675	2521Q	2321LW	2228QC	2828QC	2128SLC	-	2439HH
275/55-20	ES85	QV751	QV583	1679	2533Q	2328LW	3228QC	3828QC	3128SLC	S295	3428HH
285/55-20	ES85	QV757	QV583	1681	2536Q	-	3228QC	3828QC	3128SLC	-	3428HH
295/55-20	ES85	QV837	QV583	-	-	-	-	-	-	-	-
305/55-20	ES188	QV853	-	1681	2536Q	-	3231QC	3831QC	3131SLC	S298	3431HH
245/60-20	ES84	QV741	QV579	-	-	-	2228QC	2828QC	2128SLC	-	-
255/60-20	-	-	-	1679	-	-	2228QC	2828QC	2128SLC	-	-
265/60-20	ES84	QV751	QV579	1678	2533Q	-	3228QC	3828QC	3128SLC	S295	3428HH
275/60-20	ES188	QV751	QV583	1679	2533Q	-	2228QC	2828QC	2128SLC	S295	2440HH
285/60-20	ES188	QV757	-	1679	2536Q	-	3229QC	3829QC	3129SLC	S296	-
295/60-20	ES188	QV761	QV853	1681	-	-	3229QC	3829QC	3129SLC	-	3429HH
315/60-20	ES195	QV859	-	-	-	-	3231QC	3831QC	3131SLC	-	3431HH
325/60-20	ES199	QV865	-	-	2539Q	-	3235QC	3835QC	3135SLC	S298	3435HH
355/60-20	-	QV869	-	-	-	-	3251QC	3851QC	3151SLC	-	-



LIGHT TRUCK / SUV



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDER <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
265/65-20	<i>ES85</i>	<i>QV757</i>	<i>QV583</i>	-	-	-	3227QC	3827QC	3127SLC	-	3427HH
275/65-20	<i>ES195</i>	<i>QV757</i>	-	1681	2536Q	-	3231QC	3831QC	3131SLC	S296	3431HH
285/65-20	<i>ES199</i>	<i>QV757</i>	QV859	1681	2536Q	-	3231QC	3831QC	3131SLC	-	3431HH
295/65-20	<i>ES195</i>	<i>QV761</i>	QV853	-	-	-	3231QC	3831QC	3131SLC	-	3431HH
225/75-20	-	<i>QV747</i>	<i>QV579</i>	-	-	-	2228QC	2828QC	2128SLC	-	-
285/30-21	-	<i>QV735</i>	<i>QV563</i>	-	-	-	-	-	-	-	-
315/30-21	<i>ES85</i>	-	-	-	-	-	-	-	-	-	-
275/35-21	<i>ES83</i>	-	-	-	-	-	-	-	-	-	-
295/35-21	<i>ES83</i>	<i>QV735</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
315/35-21	<i>ES85</i>	-	-	-	-	-	-	-	-	-	-
255/40-21	<i>ES82</i>	<i>QV735</i>	<i>QV575</i>	-	-	-	2229QC	2829QC	2129SLC	-	2435HH
265/40-21	<i>ES83</i>	<i>QV741</i>	<i>QV579</i>	1673	2521Q	2321LW	3210QC	3810QC	3110SLC	-	3410HH
275/40-21	<i>ES83</i>	<i>QV741</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
285/40-21	<i>ES83</i>	-	-	-	-	-	-	-	-	-	-
295/40-21	<i>ES83</i>	<i>QV747</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
315/40-21	<i>ES85</i>	-	-	-	-	-	-	-	-	-	-
265/45-21	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	1675	2521Q	2321LW	3210QC	3810QC	3110SLC	-	3410HH
275/45-21	<i>ES84</i>	<i>QV751</i>	<i>QV583</i>	-	2527Q	-	2228QC	2828QC	2128SLC	-	3410HH
285/45-21	<i>ES84</i>	<i>QV751</i>	<i>QV583</i>	-	-	-	-	-	-	-	-
255/50-21	<i>ES84</i>	<i>QV747</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
275/50-21	<i>ES84</i>	<i>QV751</i>	<i>QV583</i>	-	-	-	3229QC	3829QC	3129SLC	-	3429HH
295/30-22	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	1675	-	-	2228QC	2828QC	2128SLC	-	-
255/35-22	<i>ES82</i>	<i>QV741</i>	<i>QV571</i>	1673	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2435HH
265/35-22	<i>ES83</i>	<i>QV741</i>	<i>QV575</i>	1673	2521Q	2321LW	2229QC	2829QC	2129SLC	-	-
285/35-22	<i>ES83</i>	<i>QV747</i>	<i>QV579</i>	1675	2527Q	2327LW	2228QC	2828QC	2128SLC	-	-
295/35-22	-	<i>QV747</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
305/35-22	-	<i>QV747</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
315/35-22	<i>ES188</i>	-	-	-	-	-	-	-	-	-	-
245/40-22	<i>ES83</i>	<i>QV735</i>	<i>QV575</i>	-	-	-	-	-	-	-	-
265/40-22	<i>ES83</i>	<i>QV741</i>	<i>QV579</i>	1663	2521Q	2321LW	3210QC	3810QC	3110SLC	-	3410HH
275/40-22	<i>ES83</i>	<i>QV747</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
285/40-22	-	<i>QV741</i>	<i>QV579</i>	1675	2527Q	2327LW	2228QC	2828QC	2128SLC	-	-
295/40-22	<i>ES84</i>	-	-	-	-	-	-	-	-	-	-
305/40-22	<i>ES84</i>	<i>QV751</i>	<i>QV583</i>	1679	-	2328LW	2228QC	2828QC	2128SLC	-	3428HH
325/40-22	<i>ES85</i>	-	-	1681	-	2328LW	3228QC	3828QC	3128SLC	-	-
265/45-22	-	<i>QV735</i>	<i>QV575</i>	1675	2527Q	2327LW	2228QC	2828QC	2128SLC	-	-
275/45-22	-	<i>QV747</i>	<i>QV579</i>	1679	2514Q	2314LW	-	-	-	-	-
285/45-22	<i>ES85</i>	<i>QV751</i>	<i>QV583</i>	1679	2533Q	2328LW	2228QC	2828QC	2128SLC	-	-
295/45-22	<i>ES85</i>	-	<i>QV583</i>	-	-	-	-	-	-	-	-
305/45-22	<i>ES85</i>	<i>QV757</i>	<i>QV583</i>	1678	2536Q	2335LW	2228QC	2828QC	2128SLC	-	2440HH
275/50-22	<i>ES85</i>	QV835	<i>QV583</i>	-	-	-	-	-	-	-	-
285/50-22	<i>ES188</i>	<i>QV757</i>	<i>QV583</i>	1680	2536Q	-	3228QC	3828QC	3128SLC	-	3428HH
305/50-22	-	QV859	-	-	-	-	3231QC	3831QC	3131SLC	-	3431HH
325/50-22	<i>ES199</i>	-	-	2315	2539Q	-	3235QC	3835QC	3135SLC	-	3435HH
285/55-22	-	-	-	-	-	-	3231QC	3831QC	3131SLC	-	3431HH
295/30-23	-	<i>QV741</i>	<i>QV579</i>	-	-	-	-	-	-	-	-
285/40-23	<i>ES85</i>	-	-	-	-	-	-	-	-	-	-



LIGHT TRUCK/SUV

MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408





Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDER <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
305/40-23	-	QV751	-	-	-	-	-	-	-	-	-
245/30-24	ES83	QV747	-	-	-	-	-	-	-	-	-
255/30-24	ES83	QV747	QV579	1675	-	-	-	-	-	-	-
275/30-24	ES83	QV751	QV583	1679	-	-	-	-	-	-	-
295/30-24	-	-	QV583	1680	2514Q	2314LW	-	-	-	-	-
285/35-24	-	QV741	QV579	-	-	-	-	-	-	-	-
295/35-24	ES85	QV751	QV583	1681	-	-	-	-	-	-	-
305/35-24	ES85	QV757	QV583	1681	2536Q	-	3231QC	3831QC	3131SLC	-	3431HH
315/35-24	-	-	QV583	-	-	-	-	-	-	-	-
285/40-24	-	QV757	QV583	1680	2536Q	-	3229QC	3829QC	3129SLC	-	3429HH
295/40-24	ES188	QV761	QV583	1681	2536Q	2337LW	3231QC	3831QC	3131SLC	-	3431HH
305/30-26	ES188	-	-	1681	-	-	-	-	-	-	-
27x8.50-14	ES75	QV335	QV563	1661	1545Q	-	2216QC	2816QC	2116SLC	-	-
27x9.50-14	ES75	-	-	1665	-	-	2216QC	2816QC	2116SLC	-	-
29x9.50-14	ES82	QV729	QV571	1665	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2435HH
29x9.50-15	ES82	QV729	QV571	1661	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2435HH
29x10.50-15	ES82	QV729	QV571	1661	2519Q	2319LW	3210QC	3810QC	3110SLC	S315	3410HH
30x9.50-15	ES83	QV735	QV575	1669	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2435HH
31x9.50-15	-	QV741	QV579	1673	2519Q	2319LW	3227QC	3827QC	3127SLC	S315	2437HH
31x10.50-15	ES84	QV741	QV575	1669	2529Q	2329LW	3210QC	3810QC	3110SLC	S315	3410HH
31x11.50-15	-	QV747	QV579	1669	2529Q	2329LW	3227QC	3827QC	3127SLC	S320	3427HH
31x12.50-15	-	-	-	1675	2514Q	2314LW	3229QC	3829QC	3129SLC	S295	3429HH
32x9.50-15	-	QV741	QV579	1669	2519Q	2319LW	3227QC	3827QC	3127SLC	S315	3427HH
32x11.50-15	ES84	QV747	QV583	1675	2514Q	2314LW	3229QC	3829QC	3129SLC	S320	3429HH
33x9.50-15	-	QV751	QV583	1675	2514Q	2314LW	3210QC	3810QC	3110SLC	S320	3410HH
33x10.50-15	-	QV747	QV583	1675	2514Q	2314LW	3229QC	3829QC	3129SLC	S320	3429HH
33x12.50-15	ES188	QV757	-	1678	2536Q	2335LW	3229QC	3829QC	3129SLC	S295	3429HH
33x13.50-15	ES188	-	-	-	-	-	3229QC	3829QC	3129SLC	S298	3429HH
35x10.50-15	ES195	-	-	1679	2514Q	2314LW	3229QC	3829QC	3129SLC	S295	3427HH
35x12.50-15	ES195	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S296	3431HH
35x13.50-15	ES199	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S298	3431HH
35x14.50-15	ES199	-	-	-	-	2337LW	3235QC	3835QC	3135SLC	S298	3435HH
37x12.50-15	ES199	QV859	-	-	2539Q	-	3235QC	3835QC	3135SLC	S298	3435HH
37x14.50-15	-	QV869	-	-	-	-	3251QC	3851QC	3151SLC	-	-
38x12.50-15	-	-	-	-	-	-	3259QC	3859QC	3159SLC	-	-
29x9.50-16	ES82	QV729	QV571	1661	2519Q	2319LW	2229QC	2829QC	2129SLC	-	2437HH
33x13.50-16	ES188	-	-	-	2533Q	-	3229QC	3829QC	3129SLC	S298	3429HH
35x12.50-16	ES195	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S296	3431HH
35x13.50-16	ES199	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S298	3431HH
33x12.50-17	ES188	QV757	-	1678	2536Q	2335LW	3229QC	3829QC	3129SLC	S295	3429HH
35x11.50-17	ES195	QV761	-	-	-	-	3231QC	3831QC	3131SLC	S296	3431HH
35x12.50-17	ES195	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S296	3431HH
37x12.50-17	ES199	QV859	-	-	2539Q	-	3235QC	3835QC	3135SLC	S298	3435HH
37x13.50-17	ES199	QV869	-	2316	-	-	3235QC	3835QC	3135SLC	S298	3435HH
40x13.50-17	-	QV881	-	-	-	-	3254QC	3854QC	3154SLC	-	-
42x14.50-17	-	-	-	3355	-	-	3255QC	3855QC	3155SLC	-	3455HH
33x12.50-18	ES188	QV757	-	1678	2536Q	2335LW	3229QC	3829QC	3129SLC	S295	3429HH



NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.




* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT LT CABLE <i>QV700</i>	HIGH VOLT CABLE <i>QV500</i>	COBRA JR CABLE <i>1600</i>	DIAMOND BACK <i>2500Q</i>	LT. WT. DIAMOND <i>2300LW</i>	HIGHWAY SINGLE <i>2200QC</i> <i>3200QC</i>	V-BAR SINGLE <i>2800QC</i> <i>3800QC</i>	SQ. LINK SINGLE <i>2100SLC</i> <i>3100SLC</i>	NORDIC STUDDED <i>S200</i> <i>S300</i>	MUD SERVICE <i>2400HH</i> <i>3400HH</i>
TIRE SIZE	Page 16	Page 26	Page 26	Page 27	Page 28	Page 29	Pgs. 30 & 33	Pgs. 30 & 33	Pgs. 31 & 34	Page 32	Pgs. 32-33
35x12.50-18	ES195	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S296	3431HH
37x12.50-18	ES199	QV859	-	-	2539Q	-	3235QC	3835QC	3135SLC	S298	3435HH
37x13.50-18	ES199	QV869	-	2316	-	-	3235QC	3835QC	3135SLC	S298	3435HH
38x15.50-18	-	QV881	-	-	-	-	-	-	-	-	-
33x12.50-20	ES188	QV757	-	1678	2536Q	2335LW	3229QC	3829QC	3129SLC	S295	3429HH
35x12.50-20	ES195	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S296	3431HH
35x13.50-20	ES199	QV761	QV853	1681	2539Q	-	3231QC	3831QC	3131SLC	S298	3431HH
37x12.50-20	ES199	QV859	-	-	2539Q	-	3235QC	3835QC	3135SLC	S298	3435HH
37x13.50-20	ES199	QV869	-	2316	-	-	3235QC	3835QC	3135SLC	-	3435HH
38x14.50-20	-	QV881	-	-	-	-	-	-	-	-	-
40x15.50-20	-	QV891	-	3355	-	-	3255QC	3855QC	3155SLC	-	3455HH
33x12.50-22	ES188	QV757	-	1678	2536Q	2335LW	3229QC	3829QC	3129SLC	S295	3429HH
37x13.50-24	ES199	QV869	-	2316	-	-	3235QC	3835QC	3135SLC	-	3435HH



LIGHT TRUCK/SUV



VOLT LT

PREMIUM LIGHT TRUCK/SUV

Volt LT is built for larger tires on light trucks and SUVs. They also give better traction than ladder-style chains and provide longer wear using cross cables made of alloy rollers. The diagonal cross cable design offers a smooth ride and easy installation.

RUBBER ADJUSTERS INCLUDED



⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	BUNGEE
QV729	13	QV1742	QV1174
QV735	13		QV1176
QV741	14	QV1744	
QV747	15	QV1746	
QV751	15		
QV753	16	QV1748	
QV757	17		
QV761	19	QV1750	



STANDARD PACKAGING
Packed 1 Pair Per Bag
2 Pair Per Master Carton

HIGH VOLT

PREMIUM EMERGENCY VEHICLES

(POLICE, FIRE & AMBULANCE)

High Volt cable chain is engineered to meet the high-performance needs of emergency vehicles. Long lasting alloy rollers and high strength aircraft cable provide maximum traction and durability. Easy installation with no rubber adjusters needed.



⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
QV539	11	QV9380
QV547	12	QV9384
QV555	12	QV9388
QV563	12	
QV571	12	QV9390
QV575	13	QV9394
QV579	13	
QV583	13	QV9398



STANDARD PACKAGING
Packed 1 Pair Per Plastic Box
4 Pair Per Master Carton

LOW VOLT LT



With clearances on passenger vehicles getting smaller, the Low Volt design provides a safe alternative to SAE Class "S" chains with a minimal clearance profile on the inside of the tire. Following along with the Volt product line, the Low Volt offers easy installation, alloy rollers for longer life, and the ability to fit a wider range of tires than many of the comparable link tire chain products.

FOR TIRE FITMENTS VISIT: WWW.QUALITYCHAINCORP.COM

RUBBER ADJUSTERS INCLUDED



⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	BUNGEE
QV429	10	QV1174
QV435	10	
QV441	11	QV1176
QV447	12	
QV451	12	



STANDARD PACKAGING
Packed 1 Pair Per Bag
2 Pair Per Master Carton



LIGHT TRUCK / SUV

COBRA JR™ CABLE CHAIN

Tough carbon steel rollers provide traction and long wear. The low profile steel rollers allow increased tire-to-road contact, resulting in better stability, plus a considerable reduction in noise and vibration.



RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS

⚠ DO NOT USE ON TRAILERS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
1661	10	8818	13.5"	75"
1663	13			85"
1665	11	8820	14.5"	74.5"
1669	12			80"
1673	12			75"
1675	14	8822	15.5"	85"
1678	14			90.5"
1679	14	8823	16.25"	85"
1680	15	8824	17.5"	
1681	16	8826	17"	



STANDARD PACKAGING
Packed 1 Pair Per Bag
(Boxes available upon request)



For Traction That
Bites!

DIAMOND BACK LIGHT TRUCK

5.5 MM

European Hoop Style Diamond Back Chain

Constructed of alloy steel with a square link design. Provides a smooth ride and maximum tire coverage.

For use with light trucks, SUVs, vans and RVs.

Rubber adjuster OR pull chain tightening systems for quick and easy installation.

RUBBER ADJUSTERS INCLUDED

⚠ DO NOT USE ON TRAILERS

RUBBER ADJUSTER TYPE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
2514Q	27	2561
2527Q	28	2567



RUBBER ADJUSTER TYPE



STANDARD PACKAGING
Packed 1 Pair Per Bag
2 Pair Per Master Carton



INSIDE FASTENER

PULL CHAIN TYPE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
2515Q	23	2594
2517Q	23	2596
2519Q	26	2563
2521Q	26	2565
2529Q	27	2569
2533Q	25	2573
2536Q	28	2576
2539Q	30	2579



PULL CHAIN TYPE

FOR REPAIR PARTS, SEE PAGE 15

DIAMOND BACK LIGHTWEIGHT

3.7 MM

Light Weight European Hoop Style Diamond Back Chain

Provides a smooth ride and maximum tire coverage. Constructed of alloy steel with a square link design. Less weight for easier handling.

Rubber adjuster OR pull chain tightening systems for quick and easy installation.

RUBBER ADJUSTERS INCLUDED

⚠ DO NOT USE ON TRAILERS

RUBBER ADJUSTER TYPE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
2314LW	16	2361LW
2319LW	15	2363LW
2321LW	15	2365LW
2327LW	17	2367LW



STANDARD PACKAGING
Packed 1 Pair Per Bag
2 Pair Per Master Carton



RUBBER ADJUSTER TYPE



INSIDE FASTENER

PULL CHAIN TYPE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
2315LW	14	2394LW
2317LW	13	2396LW
2328LW	17	2373LW
2329LW	16	2369LW
2335LW	17	2375LW
2337LW	17	2377LW



PULL CHAIN TYPE

FOR REPAIR PARTS, SEE PAGE 15

HIGHWAY SERVICE CHAIN

- REGULAR NON-CAM AND **CAM STYLE**
- SINGLE AND DUAL TRIPLE MOUNT
- ALSO AVAILABLE: LONG MILEAGE ALLOY (LMC)

RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



SINGLE



DUAL TRIPLE

NOT FOR PLOW, FORKLIFT, TOW TRUCK OR OFF-ROAD USE.
SEE PAGE 31 FOR THESE APPLICATIONS.

SINGLE MOUNT (1 PR/BAG)

DUAL TRIPLE MOUNT (1/2 PR/BAG)

REGULAR		CAM STYLE		REGULAR		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)		
-	-	2209QC	21	-	-	-	-	6219	5.5 MM
-	-	2211QC	23	-	-	4211QC	46		
2214	27	2214QC	29	4214	50	4214QC	54	6221	
2216	22	2216QC	23	-	-	4216QC	40		
2219	25	2219QC	25	4219	44	4219QC	46		
2221	25	2221QC	27	4221	47	4221QC	50		
2228	29	2228QC	30	4228	51	4228QC	56	6225	
2229	25	2229QC	25	4229	45	4229QC	52		

V-BAR CHAIN

- REGULAR NON-CAM AND **CAM STYLE**
- SINGLE AND DUAL TRIPLE MOUNT
- ICE BREAKERS WELDED ONTO CROSS LINKS



RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



SINGLE



DUAL TRIPLE

NOT FOR PLOW, FORKLIFT, TOW TRUCK OR OFF-ROAD USE.
SEE PAGE 31 FOR THESE APPLICATIONS.

SINGLE MOUNT (1 PR/BAG)

DUAL TRIPLE MOUNT (1/2 PR/BAG)

REGULAR		CAM STYLE		REGULAR		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)		
-	-	2809QC	26	-	-	-	-	6819	5.5 MM
2811	25	2811QC	26	-	-	-	-		
2814	32	2814QC	34	4814	55	4814QC	57		
2816	24	2816QC	25	-	-	-	-	6821	
2819	26	2819QC	27	4819	51	4819QC	50		
2821	28	2821QC	29	4821	55	4821QC	54		
2828	31	2828QC	33	4828	57	4828QC	60	6825	
2829	27	2829QC	28	4829	53	4829QC	55		

SQUARE LINK ALLOY & TWISTED SQUARE LINK ALLOY

- **CAM STYLE**
- **FOR HIGHWAY AND LIGHT OFF-ROAD USE**
- **SINGLE AND DUAL TRIPLE MOUNT**

ALSO AVAILABLE: NON-CAM STYLE (SL & SLTWIST)

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



SQUARE



TWISTED SQUARE



SINGLE MOUNT (1 PR/BAG)

DUAL TRIPLE MOUNT (1/2 PR/BAG)

CAM STYLE		TWISTED CAM STYLE		CAM STYLE		TWISTED CAM STYLE		CROSS CHAIN (SQUARE & TWISTED)	WIRE SIZE
STOCK NUMBER	WT/PR (LBS)	STOCK NUMBER	WT/PR (LBS)	STOCK NUMBER	WT/PR (LBS)	STOCK NUMBER	WT/PR (LBS)		
2114SLC	30	2114SLCTWIST	28	4114SLC	55	4114SLCTWIST	55	6221SL & 6221SLTWIST	5.5 MM
2116SLC	24	2116SLCTWIST	26	-	-	-	-		
2119SLC	26	2119SLCTWIST	27	4119SLC	44	4119SLCTWIST	47		
2121SLC	29	2121SLCTWIST	29	4121SLC	52	4121SLCTWIST	54		
2128SLC	31	2128SLCTWIST	28	4128SLC	55	4128SLCTWIST	57	6225SL & 6225SLTWIST	
2129SLC	26	2129SLCTWIST	27	4129SLC	56	-	-		

HEAVY DUTY SQUARE LINK ALLOY

- **RHD = NON-CAM STYLE**
- **HDQC = CAM STYLE**
- **HEAVY DUTY FOR OFF-ROAD, PLOW, FORKLIFT AND TOW TRUCK USE**
- **SINGLE AND DUAL TRIPLE MOUNT**

ALSO AVAILABLE: TWISTED SQUARE LINK STYLE
(ADD TWIST TO END OF PART NUMBER)

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



SINGLE

DUAL TRIPLE

SINGLE MOUNT (1 PR/BAG)

DUAL TRIPLE MOUNT (1/2 PR/BAG)

REGULAR		CAM STYLE		REGULAR		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WT/PR (LBS)	STOCK NUMBER	WT/PR (LBS)	STOCK NUMBER	WT/PR (LBS)	STOCK NUMBER	WT/PR (LBS)		
2114RHD	39	2114HDQC	42	4114RHD	79	4114HDQC	80	6251SL	7 MM
2119RHD	36	2119HDQC	37	4119RHD	64	4119HDQC	75		
2121RHD	39	2121HDQC	39	4121RHD	73	4121HDQC	84		
2128RHD	39	2128HDQC	43	4128RHD	86	4128HDQC	92		
2129RHD	35	2129HDQC	45	4129RHD	66	4129HDQC	65	6253SL	

NORDIC™ STUDDED ALLOY

- SINGLE AND DUAL TRIPLE MOUNT
- PREMIUM STUDDED TYPE LADDER CHAIN WITH AGGRESSIVE STUDDED TIPS FOR EXCELLENT TRACTION IN EXTREME CONDITIONS

ALSO AVAILABLE: CAM STYLE (ADD QC TO END OF PART NUMBER)



RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



SINGLE



DUAL TRIPLE

SINGLE
(1 PR/BAG)

DUAL TRIPLE
(1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
285/75-16; 285/70-17; 295/70-17; 285/75-17 33x12.50x15; 33x12.50x17	S295	48	-	-	6915	7 MM
315/70-16; 315/70-17; 305/65-18; 35x12.50x17 35x12.50x18	S296	53	-	-		
325/65-18; 37x12.50x17; 37x13.50x17; 37x13.50x18	S298	66	-	-		
235/75-16; 245/75-16; 215/85-16; 225/85-16; 245/70-17; 225/70-17.5; 31x10.50x15; 32x9.50x15	S315	44	S715	81	6912	7 MM
265/75-16; 265/70-17; 235/80-17; 225/70-19.5 32x11.50x15	S320	48	S720	86		
245/85-16; 265/85-16; 265/70-18; 275/70-18 245/70-19.5; 265/70-19.5	S322	53	S722	86		

MUD SERVICE

- SINGLE AND DUAL TRIPLE MOUNT
- HEAVY DUTY CROSS CHAIN WITH EXTRA HEAVY HOOKS
- OFF-ROAD AND MUD USE APPLICATIONS

RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



SINGLE



DUAL TRIPLE

SINGLE
(1 PR/BAG)

DUAL TRIPLE
(1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
205/75-16; 215/75-15; 225/70-15	2433HH	35	-	-	6256HH	8 MM
225/75-15; 235/75-16; 225/70-16; 235/75-16 215/85-16; 215/70-17.5; 235/70-16; 215/70-16 225/55-18	2435HH	39				
7.50-16; 275/60-15; 245/70-15; 265/70-15; 265/75-15 225/70-19.5; 245/75-16; 235/85-16; 235/80-17	2437HH	44	4412HH	78		
245/65-17; 255/70-17; 265/70-17; 275/70-17 275/60-18; 245/70-19.5	2439HH	44	4425HH	86	6260HH	8 MM
305/70-16; 285/75-16; 285/70-17; 275/70-17.5 305/50-20; 275/60-20; 295/75-16	2440HH	48	-	-		
245/85-15; 315/75-16	2441HH	71	4435HH	123	6434HH	10 MM



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

WIDE BASE CHAIN

- REGULAR AND **CAM STYLE** FOR HIGHWAY USE APPLICATIONS



NOT FOR PLOW, FORKLIFT, TOW TRUCK OR OFF-ROAD USE.
SEE PAGE 34 FOR THESE APPLICATIONS.

REGULAR (1 PR/BAG) **CAM STYLE** (1 PR/BAG)

STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
3210	27	3210QC	28	6225	5.5 MM
3227	35	3227QC	36	6253	7 MM
3228	38	3228QC	40		
3229	38	3229QC	39		
3231	40	3231QC	43	6259	
3235	44	3235QC	47		



HIGHWAY SERVICE

RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS



LIGHT TRUCK/SUV

V-BAR WIDE BASE CHAIN

- REGULAR AND **CAM STYLE** FOR HIGHWAY USE APPLICATIONS
- ICE BREAKERS WELDED ONTO CROSS LINKS



NOT FOR PLOW, FORKLIFT, OR TOW TRUCK USE.
SEE PAGE 34 FOR THESE APPLICATIONS.

REGULAR (1 PR/BAG) **CAM STYLE** (1 PR/BAG)

STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
3810	31	3810QC	30	6825	5.5 MM
3827	40	3827QC	42	6853	7 MM
3828	41	3828QC	44		
3829	46	3829QC	47		
3831	45	3831QC	46	6859	
3835	49	3835QC	50		



V-BAR

MUD SERVICE WIDE BASE CHAIN

- OFF-ROAD AND MUD USE APPLICATIONS
- HEAVY DUTY CROSS CHAIN WITH EXTRA HEAVY HOOKS

WIDE BASE (1 PR/BAG)

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
3410HH	34	6253	7 MM
3427HH	54	6453HH	10 MM
3428HH	60		
3429HH	64	6434HH	
3431HH	70		
3435HH	76		



MUD SERVICE

SQUARE LINK ALLOY WIDE BASE

- SLC - **CAM** STYLE FOR HIGHWAY AND LIGHT OFF-ROAD USE
- SLCTWIST - TWISTED SQUARE LINK **CAM** STYLE
- ALSO AVAILABLE: NON-CAM = SL & NON-CAM TWISTED SQUARE = SLTWIST

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0216
SEE PAGE 107 FOR DETAILS

TYPE SLC (1 PR/BAG)


STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
3110SLC	28	6225SL
3127SLC	39	6253SL
3128SLC	40	
3129SLC	42	6259SL
3131SLC	51	
3135SLC	54	

TYPE SLCTWIST (1 PR/BAG)

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
3110SLCTWIST	42	6225 SLTWIST	5.5 MM
3127SLCTWIST	45	6253 SLTWIST	7 MM
3128SLCTWIST	46		
3129SLCTWIST	48	6259 SLTWIST	
3131SLCTWIST	53		
3135SLCTWIST	57		



SQUARE LINK



HD SQUARE LINK ALLOY WIDE BASE

- RHD = NON-CAM STYLE & HDQC = **CAM STYLE**
- HEAVY DUTY FOR OFF-ROAD, PLOW, FORKLIFT & TOW TRUCK USE
- ALSO AVAILABLE: HEAVY DUTY TWISTED SQUARE LINK STYLE
(ADD TWIST TO END OF PART NUMBER)

REGULAR (1 PR/BAG)

STOCK NUMBER	WEIGHT PER PAIR (LBS)
3128RHD	48
3129RHD	48
3131RHD	57
3135RHD	59

CAM STYLE (1 PR/BAG)

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
3128HDQC	50	6260SL	8 MM
3129HDQC	50	6263SL	
3131HDQC	58		
3135HDQC	60		



HD SQUARE LINK

COMMERCIAL TRUCK



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT TRUCK <i>QV800</i>	KING COBRA <i>2300 3300</i>	HIGHWAY SINGLE <i>2200QC 3200QC</i>	HWY DUAL TRIPLES <i>4200QC</i>	V-BAR SINGLE <i>2800QC 3800QC</i>	LT. WEIGHT ALLOY SINGLE <i>2200CAML 3200CAML-7</i>	LMC ALLOY SINGLE <i>2200LMC 3200LMC</i>	SQUARELINK SINGLE <i>2100SLC 3100SLC</i>	MUD SERVICE <i>2400HH 3400HH</i>	NORDIC STUDDED <i>S300</i>
TIRE SIZE	Pgs. 38-39	Page 41	Page 42	Pgs. 44 & 52	Page 44	Page 44	Pgs. 45 & 52	Pgs. 45 & 52	Pgs. 46 & 53	Pgs. 47 & 52	Page 50
8.25-15	-	QV835	-	2228QC	4228QC	2828QC	-	2228LMC	2128SLC	-	-
9.00-15	-	QV837	-	2237QC	4237QC	2837QC	-	2237LMC	2137SLC	-	S322
10.00-15	-	QV853	-	-	-	-	-	-	-	-	-
9.5-17.5	ES195	QV837	-	-	-	-	-	-	-	-	-
10-17.5	-	QV841	-	2228QC	4228QC	2828QC	-	2228LMC	2128SLC	-	-
15-19.5	-	-	-	3265QC	-	-	-	3265LMC	3165SLC	-	-
16.5-19.5	-	-	3355	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	-
18-19.5	-	-	-	3257QC	-	-	-	3257LMC	3157SLC	-	-
7.00-20	-	QV583	1663	2233QC	4233QC	2833QC	-	2233LMC	2133SLC	-	S322
7.50-20	ES199	-	-	2237QC	4237QC	2837QC	-	2237LMC	2137SLC	2441HH	S322
8.25-20	ES205	QV859	2339	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	2441HH	S332
9.00-20	ES205	QV869	2341	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	2445HH	S342
10.00/90-20	-	QV877	-	2245QC	4245QC	2845QC	2245CAML	2245LMC	2145SLC	-	-
10.00-20	ES225	QV881	2345	2245QC	4245QC	2845QC	2245CAML	2245LMC	2145SLC	2448HH	S343HD
11.00-20	ES245	QV887	2351	2251QC	4251QC	2851QC	-	2251LMC	2151SLC	2452HH	S355HD
12.00-20	ES245	QV896	-	3261QC	-	3861QC	-	3261LMC	3161SLC	3461HH	-
13/80-20	-	-	2345	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2448HH	-
14/80-20	-	QV892	-	2257QC	4257QC	2857QC	-	2257LMC	2157SLC	3455HH	-
38/18.00-20	-	QV897	3369	-	-	-	-	-	-	3469HH	-
10.00-22	-	QV887	2349	2249QC	4249QC	2849QC	2249CAML	2249LMC	2149SLC	2452HH	S344HD
11.00-22	ES245	QV891	-	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2452HH	-
7-22.5	-	QV751	1663	2233QC	4233QC	2833QC	-	2233LMC	2133SLC	2439HH	S320
8-22.5	-	-	-	2237QC	4237QC	2837QC	-	2237LMC	2137SLC	-	S322
9-22.5	ES205	QV859	2339	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	2441HH	S332
10-22.5	ES205	QV869	2341	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	2445HH	S343HD
11-22.5	ES225	QV881	2345	2245QC	4245QC	2845QC	2245CAML	2245LMC	2145SLC	2448HH	S343HD
12-22.5	ES245	QV887	2351	2251QC	4251QC	2851QC	-	2251LMC	2151SLC	2452HH	S355HD
12.5-22.5	-	QV887	2351	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2452HH	S355HD
15-22.5	-	-	-	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	-
16.5-22.5	-	QV896	3371	3271QC	-	3871QC	-	3271LMC	3171SLC	3471HH	-
18-22.5	-	QV818	-	3261QC	-	3861QC	-	3261LMC	3161SLC	3461HH	-
11.00-24	-	QV891	-	2253QC	4253QC	2853QC	-	2253LMC	2153SLC	2470HH	S355HD
12.00-24	-	QV899	-	2257QC	4257QC	2857QC	-	2257LMC	2157SLC	-	S379HD
11-24.5	ES245	QV887	2349	2249QC	4249QC	2849QC	2249CAML	2249LMC	2149SLC	2452HH	S344HD
12-24.5	-	-	-	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2486HH	-
325/80-16	-	QV859	-	3251QC	-	-	-	-	3151SLC	-	-
305/85-16	-	QV853	-	-	-	-	-	-	-	-	-
325/75-17	-	QV853	-	2226QC	4226QC	2826QC	-	-	2126SLC	-	-
295/75-17.5	-	QV859	-	2226QC	4226QC	2826QC	-	-	2126SLC	-	-
375/60-18	-	QV853	-	-	-	-	-	-	-	-	-
445/65-19.5	-	QV896	3371	3271QC	-	3871QC	-	3271LMC	3171SLC	3471HH	S379HD
245/70-19.5	ES188	QV835	1675	2228QC	4228QC	2828QC	-	2228LMC	2128SLC	2439HH	S322
255/70-19.5	-	QV835	-	2228QC	4228QC	2828QC	-	2228LMC	2128SLC	-	-
265/70-19.5	ES188	QV837	-	2237QC	4237QC	2837QC	-	2237LMC	2137SLC	-	S332
275/70-19.5	-	QV837	-	2237QC	4237QC	2837QC	-	2237LMC	2137SLC	-	-
285/70-19.5	ES195	QV853	-	2246QC	4246QC	2846QC	-	2246LMC	2146SLC	-	S342
295/70-19.5	-	QV853	-	-	-	-	-	-	-	-	-
305/70-19.5	ES199	-	-	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	-	S343HD
265/75-19.5	-	QV837	-	2237QC	4237QC	2837QC	-	2237LMC	2137SLC	-	-
285/65-20	-	QV859	1681	2226QC	4226QC	2826QC	-	-	2126SLC	3431HH	-



TRUCK



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.



NOTE: Part numbers that are **BOLD ITALIC** meet and/or exceed S.A.E. Class "S" Clearance requirements.



* Most tire chains are available in CAM (QC) and NON-CAM versions.

	EASYSOX <i>ES</i>	VOLT TRUCK <i>QV800</i>	KING COBRA <i>2300 3300</i>	HIGHWAY SINGLE <i>2200QC 3200QC</i>	HWY DUAL TRIPLES <i>4200QC</i>	V-BAR SINGLE <i>2800QC 3800QC</i>	LT. WEIGHT ALLOY SINGLE <i>2200CAML 3200CAML-7</i>	LMC ALLOY SINGLE <i>2200LMC 3200LMC</i>	SQUARELINK SINGLE <i>2100SLC 3100SLC</i>	MUD SERVICE <i>2400HH 3400HH</i>	NORDIC STUDD <i>S300</i>
TIRE SIZE	Pgs. 38-39	Page 41	Page 42	Pgs. 44 & 52	Page 44	Page 44	Pgs. 45 & 52	Pgs. 45 & 52	Pgs. 46 & 53	Pgs. 47 & 52	Page 50
400/70-20	-	QV892	3355	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	-
335/80-20	-	-	-	3254QC	-	-	-	3254LMC	3154SLC	-	-
365/80-20	-	QV892	-	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	-
395/85-20	-	-	-	3261QC	-	3861QC	-	3261LMC	3161SLC	3461HH	-
315/60-22	-	QV865	-	-	-	-	-	-	-	-	-
445/50-22.5	ES445	QV897	3369	3269QC	-	3869QC	3269CAML-7	3269LMC	3169SLC	3469HH	S372HD
455/50-22.5	ES455	QV897	3369	3269QC	-	3869QC	3269CAML-7	3269LMC	3169SLC	3469HH	-
425/55-22.5	-	QV896	3371	3271QC	-	3871QC	-	3271LMC	3171SLC	3471HH	S377HD
445/55-22.5	-	QV897	3369	3269QC	-	3869QC	3269CAML-7	3269LMC	3169SLC	3469HH	S377HD
455/55-22.5	ES455	QV899	3371	3271QC	-	3871QC	-	3271LMC	3171SLC	3471HH	S377HD
295/60-22.5	-	QV859	-	3231QC	-	3831QC	-	3231LMC	3131SLC	-	-
285/65-22.5	-	QV869	-	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	-	-
385/65-22.5	ES385	QV892	3355	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	S372HD
425/65-22.5	-	QV896	3371	3271QC	-	3871QC	-	3271LMC	3171SLC	3471HH	S377HD
445/65-22.5	-	QV818	-	3261QC	-	3861QC	-	3261LMC	3161SLC	3461HH	S382HD
225/70-22.5	-	QV583	1669	2233QC	4233QC	2833QC	-	2233LMC	2133SLC	-	S332
245/70-22.5	-	QV853	-	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	2441HH	S332
255/70-22.5	ES199	QV859	2339	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	2441HH	S332
275/70-22.5	ES199	QV869	-	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	2445HH	S342
295/70-22.5	ES205	QV877	2343	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	-	-
305/70-22.5	ES205	QV881	2345	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	2448HH	-
315/70-22.5	ES205	QV881	2345	-	-	-	-	-	-	-	-
365/70-22.5	-	QV892	3355	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	-
425/70-22.5	-	-	3371	3271QC	-	3871QC	-	3271LMC	3171SLC	3471HH	-
235/75-22.5	-	-	-	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	-	S332
245/75-22.5	ES199	QV859	-	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	2441HH	S332
255/75-22.5	-	QV859	2339	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	-	-
265/75-22.5	ES205	QV865	-	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	2445HH	S342
275/75-22.5	-	QV877	2343	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	2448HH	-
285/75-22.5	ES205	QV877	2343	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	2448HH	S343HD
295/75-22.5	ES205	QV877	2343	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	2448HH	S343HD
235/80-22.5	ES199	QV859	2339	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	2441HH	S332
245/80-22.5	-	QV859	2339	2239QC	4239QC	2839QC	-	2239LMC	2139SLC	-	-
255/80-22.5	ES205	QV865	-	2241QC	4241QC	2841QC	-	2241LMC	2141SLC	2441HH	S342
275/80-22.5	ES205	QV881	2343	2245QC	4245QC	2845QC	2245CAML	2245LMC	2145SLC	2445HH	S343HD
285/80-22.5	ES225	QV881	2351	2251QC	4251QC	2851QC	-	2251LMC	2151SLC	-	-
295/80-22.5	ES225	QV881	2351	2251QC	4251QC	2851QC	-	2251LMC	2151SLC	2448HH	S355HD
305/80-22.5	-	QV881	2347	2251QC	4251QC	2851QC	-	2251LMC	2151SLC	2452HH	-
315/80-22.5	ES245	QV887	2349	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2486HH	S355HD
315/80-22.5	ES245	QV892	2349	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2486HH	S355HD
365/80-22.5	-	-	3355	3255QC	-	3855QC	3255CAML-7	3255LMC	3155SLC	3455HH	-
275/85-22.5	-	-	-	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	-	S343HD
305/85-22.5	-	QV887	-	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2486HH	S344HD
320/75-24	-	QV887	2351	2251QC	4251QC	2851QC	-	2251LMC	2151SLC	2452HH	-
285/70-24.5	-	QV877	2343	2245QC	4245QC	2845QC	2245CAML	2245LMC	2145SLC	-	-
285/75-24.5	ES225	QV881	2347	2249QC	4249QC	2849QC	2249CAML	2249LMC	2149SLC	2452HH	S344HD
305/75-24.5	-	QV887	-	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2452HH	S344HD
315/75-24.5	-	-	3355	2255QC	4255QC	2855QC	-	2255LMC	2155SLC	2452HH	S355HD
275/80-24.5	ES225	QV877	2347	2247QC	4247QC	2847QC	2247CAML	2247LMC	2147SLC	2452HH	S344HD
285/80-24.5	-	QV881	2351	2249QC	4249QC	2849QC	2249CAML	2249LMC	2149SLC	2452HH	S344HD

MICHELIN



TRUCK

Quick and Easy to Install

EASYSOX



COMMERCIAL TRUCK

THE TRUE ALTERNATIVE TO TRADITIONAL TRACTION

LIGHT WEIGHT: EASIER TO HANDLE AND STORE!

LESS BULKY: CAN BE APPLIED TO VEHICLES
WITH EXTREMELY LOW CLEARANCE!

**SAFE TO USE WITH FAIRINGS,
COWLINGS OR AIR DEFLECTORS!**

LOWER RISK: OF VEHICLE DAMAGE, NO METAL OR
PLASTIC COMPONENTS THAT CAN
STRIKE VEHICLE OR SCUFF WHEELS!

EASY AS...



WWW.EASYSOX.COM

DISCLAIMER:

EASYSOX ARE GUARANTEED FOR WORKMANSHIP AND MATERIAL ONLY.
THE CONSUMER ACCEPTS ALL LIABILITY IN USE OF THIS PRODUCT. ALL SALES ARE FINAL.

EASY INSTALLATION:

INSTALL EASYSOX IN A SAFE PLACE AWAY FROM TRAFFIC. AFTER BRINGING VEHICLE TO A COMPLETE STOP, PUT VEHICLE IN PARK, TURN OFF ENGINE AND ENGAGE PARKING BRAKE.



1

LAY EASYSOX OVER THE DRIVE AXLE TIRES. STARTING FROM THE TOP OF THE TIRE, WORK THE EASYSOX OVER THE TREADFACE AND WRAP OVER THE INNER SIDEWALL OF THE TIRE, WORKING YOUR WAY DOWN TOWARD THE ROAD SURFACE.



2

PULL VEHICLE FORWARD (ABOUT A HALF REVOLUTION OF TIRE) UNTIL THE TIRE IS RESTING ON THE TOP OF THE MOUNTED SECTION OF THE EASYSOX. CONTINUE TO PULL THE FABRIC OVER THE INNER SIDEWALL UNTIL IT IS EVENLY DISTRIBUTED AROUND THE ENTIRE TIRE.

IT'S JUST THAT EASY!



3

COMMERCIAL TRUCK



EASYSOX TIPS:

- ACCELERATE SLOWLY.
- DO NOT BRAKE HARD.
- DO NOT SPIN TIRES WHILE EASYSOX ARE MOUNTED AS IT MAY DAMAGE THE FABRIC.
- MAKE SURE EASYSOX ARE TEST FITTED BEFORE FIRST USE.
- EASYSOX ARE RECOMMENDED FOR SHORT DISTANCE DRIVING ONLY.
- CHECK EASYSOX PERIODICALLY FOR WEAR AND PROPER PLACEMENT.
- FOR SAFER OPERATION, EASYSOX CAN BE INSTALLED ON ALL WHEEL POSITIONS OF VEHICLE.
- DO NOT PARK FOR EXTENDED PERIODS WITH EASYSOX MOUNTED AS THEY MAY FREEZE TO THE ROAD.
- AFTER EACH USE LAY EASYSOX OUT TO DRY BEFORE RETURNING TO BAG FOR STORAGE.
- WHEN THE FABRIC ON THE TREAD FACE IS MORE THAN 50% WORN, REMOVE AND DISCARD IN A PROPER RECEPTACLE.

COMMERCIAL TRUCK FITMENT CHART

TIRE SIZE	EASYSOX NUMBER
245/70-19.5; 265/70-19.5	ES188
285/70-19.5; 9.5-17.5	ES195
255/70-22.5; 7.50-20; 305/70-19.5	ES199
275/70-22.5; 245/75-22.5; 235/80-22.5	
295/70-22.5; 295/75-22.5; 8.25-20	ES205
9.00-20; 9-22.5; 10-22.5; 305/70-22.5	
315/70-22.5; 265/75-22.5; 285/75-22.5	
255/80-22.5; 275/80-22.5	ES225
11-22.5; 10.00-20; 285/80-22.5	
295/80-22.5; 285/75-24.5 275/80-24.5	ES245
11-24.5; 315/80-22.5; 11.00-20; 11.00-22	
12.00-20; 12-22.5	ES385
385/65-22.5	
445/50-22.5	ES445
455/50-22.5; 455/55-22.5	ES455

PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



For more info please visit our website:
WWW.EASYSOX.COM



EASYSOX are an environmentally friendly traction alternative. No steelmaking or zinc plating involved in the manufacturing process.

EMERGENCY TRUCK CHAIN

LINK AND WEB FASTENER CHAINS

- **EMERGENCY USE ONLY**
 - **EASY ON AND OFF INSTALLATION**
 - **MUST USE WHEELS WITH HOLES OR SLOTS FOR PROPER MOUNTING/USE**
- NOTE: V-BAR VERSION IS AVAILABLE**

EMERGENCY TRUCK CHAIN WITH LINK FASTENER

STOCK NUMBER	APPLICATION	NO. OF CROSS CHAINS	STANDARD PACKAGING	WEIGHT PER PAIR (LBS)	PICTURE NUMBER
AEMC1013	19.5 - 24.5	2	1 Pair	13	2
AEMC1399	19.5 - 24.5	1		6	1
AEMC445	Super Single	2		15	2

EMERGENCY TRUCK CHAIN WITH WEB FASTENER

STOCK NUMBER	APPLICATION	NO. OF CROSS CHAINS	STANDARD PACKAGING	WEIGHT PER PAIR (LBS)	PICTURE NUMBER
AEMC1013S	19.5 - 24.5	2	1 Pair	13	4
AEMC1399S	19.5 - 24.5	1		6	3
AEMC445S	Super Single	2		15	4



PACKED 1 PAIR PER BAG

UNIVERSAL CHAIN HANGER

STOCK NUMBER	APPLICATION	STANDARD PACKAGING	WEIGHT PER PKG (LBS)
CH-1	Universal Chain Hanger (Hinged Lid)	1 Per Box	31
CH-1LID	Replacement Lid for Chain Hanger		8



VOLT TRUCK

PREMIUM COMMERCIAL TRUCK

Volt Truck cable chains are designed with the truck driver in mind. Easy installation, long life and great traction are critical. The cross chains are made of manganese alloy rollers providing unbeatable longevity and the cross cable design offers a very smooth ride and reduces vibration.

RUBBER ADJUSTERS and ADJUSTER TOOL INCLUDED



SINGLE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	BUNGEE
QV835	34	QV8259	QV1882
QV837	35	QV8261	
QV841	35		
QV853	36	QV8263	
QV859	36		
QV865	36		
QV869	36		
QV877	38	QV8265	
QV881	37	QV8263	QV1870
QV887	39	QV8265	



SINGLE

WIDE BASE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	BUNGEE
QV891	40	QV8267	QV1882
QV892	40		
QV896	47	QV8275	
QV897	43	QV8269	QV1870
QV899	44	QV8277	
QV818	45	QV8265	QV1874



WIDE BASE



QV1897

Adjuster Tool



QV1893

Repair Pliers
(see page 103)



STANDARD PACKAGING
(Packed 1 Pair Per Cardboard Box)



TRUCK

KING COBRA™ CABLE CHAIN

- SINGLE, DUAL TRIPLE AND WIDE BASE MOUNT
- MADE OF MANGANESE ALLOY SPRING ROLLERS
- EXCEPTIONAL TRACTION AND DURABILITY



RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



SINGLE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
2339	22	8611	14.89"	88.5"
2341	21			94"
2343	23	8615	15.94"	
2345	22	8619	16.88"	
2347	23	8623	17.44"	
2349	23			100.5"
2351	25	8627	18"	103.6"



SINGLE

DUAL TRIPLE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
4339	33	8611	14.89"	88.5"
4341	35			94"
4343	37	8615	15.94"	
4345	38	8619	16.88"	
4347	39	8623	17.44"	
4349	40			100.5"



DUAL TRIPLE

WIDE BASE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
3355	29	8635	21"	98"
3369	30	8639	24"	92.5"
3371	30	8637	23"	99"



WIDE BASE



STANDARD PACKAGING

- Singles Packed In Pairs
- Dual Triples Packed In 1/2 Pairs (Bags Optional)



FASTENER

COBRA™ CABLE CHAIN

- SINGLE, DUAL TRIPLES AND WIDE BASE MOUNT
- FULL 4" TIGHTENING CAM FASTENER
- HEAVY DUTY SIDE CABLE AND CARBON STEEL ROLLERS
- HEAT TREATED AND CASE HARDENED FOR LONGER WEAR

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



For Traction That
Bites!

SINGLE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
2315	17	8825	16.5"	102.5"
2316	17			108.25"



SINGLE

DUAL TRIPLE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
4314	29	8825	16.5"	96.25"
4315	31			102.5"
4317	37			114.25"



DUAL TRIPLE

WIDE BASE

STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	CROSS CHAIN WIDTH (INCHES)	OVERALL LENGTH (INCHES)
3061	23	8814	22.96"	119.8"
3065	22	8815	24.35"	87.9"
3069	21			101.8"
3071	20			106.9"



WIDE BASE



STANDARD PACKAGING

- Singles Packed In Pairs
- Dual Triples Packed In 1/2 Pairs (Bags Optional)



FASTENER

HIGHWAY SERVICE CHAIN

- REGULAR NON-CAM AND **CAM STYLE**
- SINGLE AND DUAL TRIPLE MOUNT

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY

PART # 0218
SEE PAGE 107 FOR DETAILS



NOT FOR PLOW, FORKLIFT, TOW TRUCK, FIRE TRUCK OR OFF-ROAD USE.
SEE PAGE 46 FOR THESE APPLICATIONS.

PREMIUM CHAIN AVAILABLE.
JUST ADD AN "A" BEFORE THE PART NUMBER.



SINGLE



DUAL TRIPLE

SINGLE MOUNT (1 PR/BAG)

REGULAR		CAM STYLE	
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)
2239	42	2239QC	44
2241	46	2241QC	48
2245	49	2245QC	51
2247	48	2247QC	50
2249	50	2249QC	53
2251	66	2251QC	68
2255	67	2255QC	70
2257	78	2257QC	79

DUAL TRIPLE MOUNT (1/2 PR/BAG)

REGULAR		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)		
4239	76	4239QC	82	6251	7 MM
4241	83	4241QC	87		
4245	91	4245QC	90		
4247	88	4247QC	90	6253	8 MM
4249	91	4249QC	95		
4251	116	4251QC	120	6260	
4255	127	4255QC	128	6263	8 MM
4257	138	4257QC	140		

V-BAR CHAIN

- REGULAR NON-CAM AND **CAM STYLE**
- SINGLE AND DUAL TRIPLE MOUNT
- ICE BREAKERS WELDED ONTO CROSS LINKS

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY

PART # 0218
SEE PAGE 107 FOR DETAILS



NOT FOR PLOW, FORKLIFT, TOW TRUCK OR FIRE TRUCK USE.
SEE PAGE 46 FOR THESE APPLICATIONS.

PREMIUM CHAIN AVAILABLE.
JUST ADD AN "A" BEFORE THE PART NUMBER.



STANDARD BAG



SINGLE



DUAL TRIPLE



SINGLE MOUNT (1 PR/BAG)

REGULAR		CAM STYLE	
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)
2839	44	2839QC	49
2841	51	2841QC	54
2845	52	2845QC	56
2847	52	2847QC	54
2849	55	2849QC	58
2851	71	2851QC	72
2855	73	2855QC	75
2857	86	2857QC	87

DUAL TRIPLE MOUNT (1/2 PR/BAG)

REGULAR		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)		
4839	85	4839QC	94	6822	7 MM
4841	91	4841QC	104		
4845	100	4845QC	104		
4847	104	4847QC	107	6853	8 MM
4849	103	4849QC	112		
4851	131	4851QC	133	6860	
4855	140	4855QC	140	6863	8 MM
4857	152	4857QC	157		

LIGHT WEIGHT HIGHWAY ALLOY CHAIN

LIGHT WEIGHT HIGHWAY ALLOY CHAIN WITH CAMS, THE FUTURE OF TRUCK CHAINS!

- MADE OF HARDENED ALLOY STEEL - **CAM STYLE**
- UP TO 25% LIGHTER THAN STANDARD CARBON CHAIN
- CAN RUN 2-3 TIMES LONGER THAN CARBON CHAIN
- PERFECT FOR ON-ROAD FLEETS
- SINGLE AND DUAL TRIPLE MOUNT

 NOT FOR PLOW, FORKLIFT, TOW TRUCK, FIRE TRUCK OR OFF-ROAD USE.
SEE PAGE 46 FOR THESE APPLICATIONS.



SINGLE



DUAL TRIPLE

SINGLE MOUNT (1 PR/BAG)

CAM STYLE		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)		
2245CAML	39	4245CAML	75	6251CL	5.9 MM
2247CAML	38	4247CAML	73	6253CL	
2249CAML	42	4249CAML	81		



STANDARD BAG

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS

LONG MILEAGE ALLOY

- CONSTRUCTED OF ALLOY STEEL FOR LONGER WEAR
- CAN RUN 3-4 TIMES LONGER THAN CARBON TRUCK CHAIN
- PERFECT FOR ON-ROAD FLEETS
- **CAM STYLE**, SINGLE AND DUAL TRIPLE MOUNT

 NOT FOR PLOW, FORKLIFT, TOW TRUCK, FIRE TRUCK OR OFF-ROAD USE.
SEE PAGE 46 FOR THESE APPLICATIONS.



SINGLE



DUAL TRIPLE

SINGLE MOUNT (1 PR/BAG)

CAM STYLE		CAM STYLE		CROSS CHAIN	WIRE SIZE
STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)		
2239LMC	45	4239LMC	88	6251LM	7 MM
2241LMC	49	4241LMC	89		
2245LMC	52	4245LMC	93		
2247LMC	50	4247LMC	90		
2249LMC	54	4249LMC	98	6253LM	8 MM
2251LMC	66	4251LMC	123	6260LM	
2255LMC	73	4255LMC	126	6263LM	



STANDARD BAG

SQUARE LINK ALLOY

- FOR HIGHWAY AND LIGHT OFF-ROAD USE
- MADE FROM HARDENED ALLOY STEEL
- GREAT TRACTION IN SNOW AND ICE
- TYPE SLC = **CAM STYLE** 7 MM & 8 MM

ALSO AVAILABLE: TYPE SL = NON-CAM STYLE
7 MM & 8 MM

RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



STANDARD BAG



SINGLE

DUAL TRIPLE



SINGLE
(1 PR/BAG)

DUAL TRIPLE
(1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
7.50-20; 8-22.5; 9.00-15; 265/70-19.5	2137SLC	50	4137SLC	91	6251SL	7 MM
8.25-20; 9-22.5; 245/70-22.5; 255/70-22.5	2139SLC	54	4139SLC	97		
9.00-20; 10-22.5; 275/70-22.5	2141SLC	57	4141SLC	107		
11-22.5; 10.00-20; 275/80-22.5	2145SLC	58	4145SLC	112		
285/75-22.5; 295/75-22.5; 275/85-22.5	2147SLC	58	4147SLC	108	6253SL	8 MM
11-24.5; 10.00-22; 285/75-24.5; 285/80-24.5	2149SLC	66	4149SLC	124		
11.00-20; 12-22.5; 295/80-22.5; 305/85-22.5	2151SLC	71	4151SLC	129		
315/80-22.5; 11.00-22; 12-24.5	2155SLC	77	4155SLC	138	6263SL	

OFF-ROAD HEAVY DUTY SQUARE LINK ALLOY

- DESIGNED SPECIFICALLY FOR EQUIPMENT IN EXTREME APPLICATIONS (LOGGING, MINING, OIL FIELDS, PLOWS, AND MORE)
- MADE WIDER, LONGER AND WITH HEAVIER WIRE DIAMETERS
- SINGLE AND DUAL TRIPLE MOUNT
- REGULAR NON-CAM AND **CAM STYLE**

RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



SINGLE

DUAL TRIPLE



HEAVY DUTY **CAM STYLE**

SINGLE
(1 PR/BAG)

DUAL TRIPLE
(1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
9.00-20; 10-22.5; 275/70-22.5	2141HDQC	66	4141HDQC	121	6260SL	8 MM
11-22.5; 10.00-20; 275/80-22.5	2145HDQC	71	4145HDQC	129		
11-24.5; 10.00-22; 285/75-24.5; 285/80-24.5	2150HDQC	74	4150HDQC	139	6263SL	

HEAVY DUTY NON-CAM STYLE

9.00-20; 10-22.5; 275/70-22.5	2141RHD	65	4141RHD	117	6260SL	8 MM
11-22.5; 10.00-20; 275/80-22.5	2145RHD	69	4145RHD	129		
11-24.5; 10.00-22; 285/75-24.5; 285/80-24.5	2150RHD	75	4150RHD	138	6263SL	

TWISTED SQUARE LINK ALLOY

- FOR HIGHWAY AND LIGHT OFF-ROAD USE
- MADE FROM HARDENED ALLOY STEEL
- GREAT TRACTION IN SNOW AND ICE
- TWISTED SQUARE LINK FOR A SMOOTHER RIDE
- SINGLE AND DUAL TRIPLE MOUNT

ALSO AVAILABLE: HEAVY-DUTY 8 MM
TYPE HDQCTWIST = CAM STYLE
TYPE RHDTWIST = NON-CAM STYLE

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



SINGLE

DUAL TRIPLE



SINGLE
(1 PR/BAG)

DUAL TRIPLE
(1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
7.50-20; 8-22.5; 9.00-15; 265/70-19.5	2137SLCTWIST	52	4137SLCTWIST	94	6251SL TWIST	7 MM
8.25-20; 9-22.5; 245/70-22.5; 255/70-22.5	2139SLCTWIST	54	4139SLCTWIST	99		
9.00-20; 10-22.5; 275/70-22.5	2141SLCTWIST	59	4141SLCTWIST	107		
11-22.5; 10.00-20; 275/80-22.5	2145SLCTWIST	61	4145SLCTWIST	114		
285/75-22.5; 295/75-22.5; 275/85-22.5	2147SLCTWIST	63	4147SLCTWIST	116	6253SL TWIST	8 MM
11-24.5; 10.00-22; 285/75-24.5; 285/80-24.5	2149SLCTWIST	68	4149SLCTWIST	125	6260SL TWIST	
11.00-20; 12-22.5; 295/80-22.5; 305/85-22.5	2151SLCTWIST	74	4151SLCTWIST	134	6263SL TWIST	
315/80-22.5; 11.00-22; 12-24.5	2155SLCTWIST	76	4155SLCTWIST	174	6263SL TWIST	

MUD SERVICE

- HEAVY DUTY CROSS CHAIN
- EXTRA HEAVY HOOKS
- SINGLE AND DUAL TRIPLE MOUNT

ALSO AVAILABLE: IN CAM STYLE
(ADD QC TO THE END OF PART NUMBER)

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



SINGLE

DUAL TRIPLE



PREMIUM CHAIN AVAILABLE.
JUST ADD AN "A" BEFORE THE PART NUMBER.

SINGLE
(1 PR/BAG)

DUAL TRIPLE
(1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
9-22.5; 245/70-22.5; 255/70-22.5; 255/80-22.5	2441HH	71	4435HH	123	6434HH	10 MM
9.00-20; 10-22.5; 275/70-22.5; 275/80-22.5	2445HH	78	4437HH	133		
11-22.5; 10.00-20; 285/75-22.5; 295/75-22.5	2448HH	85	4448HH	158		
11-24.5; 10.00-22; 11.00-20; 12-22.5; 285/75-24.5	2452HH	93	4461HH	180		
275/80-24.5; 315/75-24.5					6438HH	
11.00-24	2470HH	108	4470HH	201		
315/80-22.5; 12-24.5	2486HH	100	4486HH	186		

PREMIUM RALLYE/POLAR-S

- **PREMIUM** ALLOY DIAMOND PATTERN CHAIN
- DESIGNED TO BE LIGHT WEIGHT, REVERSIBLE, DURABLE AND GIVE EXCELLENT TRACTION FOR HEAVY TRUCKS AND BUSES
- POLAR-S TYPE MADE WITH LINK-OVER-LINK DESIGN FOR EXTRA TRACTION AND DURABILITY
- SINGLE, DUAL TRIPLE AND WIDE BASE MOUNT



9/32" - 7 MM

SINGLE RALLYE

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
11-22.5; 10.00-20; 275/80-22.5 315/70-22.5	310	77	310XC
11-24.5; 10.00-22; 285/75-24.5 315/80-22.5; 285/80-24.5; 12-22.5	315	73	315XC



SINGLE RALLYE

9/32" - 7 MM

DUAL TRIPLE RALLYE

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
11-22.5; 10.00-20; 275/80-22.5 315/70-22.5	310DT	138	310XC
11-24.5; 10.00-22; 285/75-24.5 315/80-22.5; 285/80-24.5; 12-22.5	315DT	139	315XC

7/32" - 5.5 MM

WIDE BASE POLAR-S

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN
385/65-22.5	385	66	385XC
445/50-22.5; 425/65-22.5	445	70	445XC



WIDE BASE POLAR-S



TRUCK



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
 EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

ASVQ EXTREME

- MADE FROM BORON ENHANCED ALLOY STEEL FOR RUGGED USE AND LONGER LIFE
- HASSLE FREE INSTALLATION WITH THE QUICK AND EASY PULL CHAIN TIGHTENING SYSTEM
- DESIGNED SPECIFICALLY FOR EQUIPMENT IN THE MOST EXTREME APPLICATIONS, BOTH ON AND OFF ROAD
- THE UNIQUE ASYMMETRICAL PATTERN ALLOWS FOR CONTINUOUS CONTACT WITH THE ROAD'S SURFACE, CREATING AN EXCEPTIONALLY SMOOTH RIDE
- IDEAL FOR VEHICLES THAT REQUIRE THE UTMOST IN LATERAL TRACTION CONTROL (SNOW PLOWS, UTILITY AND EMERGENCY VEHICLES)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	WIRE SIZE
11-22.5	ASVQ94	90	7 MM
11-24.5; 315/80-22.5	ASVQ97	94	
385/65-22.5	ASVQ01	98	
425/65-22.5	ASVQ155	102	
445/65-22.5	ASVQ160	110	8 MM

ASVQ



TRUCK

NORDIC™ STUDDED ALLOY

- PREMIUM STUDDED TYPE LADDER CHAIN WITH AGGRESSIVE TRACTION IN EXTREME CONDITIONS
- MADE WITH BORON ENHANCED ALLOY STEEL
- SINGLE AND DUAL TRIPLE MOUNT
- LIGHT WEIGHT 7MM BUILT WITH 6MM SIDE CHAIN AND 6-LINK SPACING



RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS

9/32" - 7 MM

SINGLE (1 PR/BAG)

DUAL TRIPLE (1/2 PR/BAG)

TIRE SIZE	NON-CAM	CAM STYLE	WT / PR (LBS)	NON-CAM	CAM STYLE	WT / PR (LBS)	CROSS CHAIN
	STOCK NUMBER	STOCK NUMBER		STOCK NUMBER	STOCK NUMBER		
11-22.5; 10.00-20; 285/75-22.5	S343LW	S343LWQC	49	S743LW	S743LWQC	93	6913
295/75-22.5; 275/80-22.5; 275/85-22.5							
11-24.5; 10.00-22; 305/85-22.5	S344LW	S344LWQC	52	S744LW	S744LWQC	97	
305/75-24.5; 275/80-24.5; 285/80-24.5							
315/80-22.5; 11.00-20; 295/80-22.5	S355LW	S355LWQC	57	S755LW	S755LWQC	108	6915L
12-22.5; 315/75-24.5							
385/65-22.5	S372LW	S372LWQC	59	-	-	-	6916L
425/65-22.5; 445/55-22.5; 455/55-22.5	S377LW	S377LWQC	67	-	-	-	6918L
445/65-22.5; 14.00-20	S382LW	S382LWQC	74	-	-	-	6920L

5/16" - 8 MM

SINGLE (1 PR/BAG)

DUAL TRIPLE (1/2 PR/BAG)

TIRE SIZE	NON-CAM	CAM STYLE	WT / PR (LBS)	NON-CAM	CAM STYLE	WT / PR (LBS)	CROSS CHAIN
	STOCK NUMBER	STOCK NUMBER		STOCK NUMBER	STOCK NUMBER		
11-22.5; 10.00-20	S343HD	S343HDQC	76	S743HD	S743HDQC	116	6923
11-24.5; 10.00-22	S344HD	S344HDQC	81	S744HD	S744HDQC	124	
315/80-22.5; 11.00-20	S355HD	S355HDQC	88	S755HD	S755HDQC	165	6925
385/65-22.5	S372HD	S372HDQC	91	-	-	-	6926
425/65-22.5; 445/55-22.5							
455/55-22.5	S377HD	S377HDQC	97	-	-	-	6931
445/65-22.5; 14.00-20	S382HD	S382HDQC	103	-	-	-	6932



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@CHAINQUEST.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

PREMIUM STUDDED ALLOY


- SINGLE AND DUAL TRIPLE MOUNT
- **PREMIUM** STUDDED TYPE LADDER CHAIN WITH AGGRESSIVE STUDDED TIPS FOR EXCELLENT TRACTION IN EXTREME CONDITIONS



MADE IN
NORWAY

NORSE

Trygg Studded chain available. See TRYGG pages 54-56 for details.



RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS

SINGLE (1 PR/BAG)

DUAL TRIPLE (1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	STOCK NUMBER	WEIGHT PER PAIR (LBS)	CROSS CHAIN	WIRE SIZE
11-24.5; 10.00-22	3949N	68	-	-	6915N	7 MM
11-22.5; 10.00-20	3545N	72	4545N	133	6923N	8 MM
11-24.5; 10.00-22	3549N	76	4549N	144		
11-24.5; 10.00-22	3649N	105	4649N	189	6927N	10 MM
12-24.5; 11.00-22	3655N	115	4655N	197		
12.00-24	3657N	126	4657N	230	6928N	



TRUCK



WIDE BASE TRUCK CHAIN

- **CAM STYLE** FOR HIGHWAY USE APPLICATIONS
- **LIGHT WEIGHT ALLOY (CAML-7)** UP TO 25% LIGHTER THAN CARBON CHAIN; CAN RUN 2-3 TIMES LONGER
- **LONG MILEAGE ALLOY (LMC)** CAN RUN 3-4 TIMES LONGER THAN STANDARD CARBON CHAIN

ALSO AVAILABLE: NON-CAM STYLE

! NOT FOR PLOW, FORKLIFT, TOW TRUCK, FIRE TRUCK OR OFF-ROAD USE.
SEE PAGE 53 FOR THESE APPLICATIONS.

**RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY**
PART # 0218
SEE PAGE 107 FOR DETAILS



HIGHWAY (QC)



LIGHT WEIGHT ALLOY (CAML-7)



LONG MILEAGE (LMC)

HIGHWAY 8 MM (1 PR/BAG)

LT. WT. 7MM ALLOY (1 PR/BAG)

LONG MILEAGE 8MM ALLOY (1 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN
385/65-22.5; 12-24.5; 12.00-20 16.5-19.5; 15-22.5; 13/80-20 365/70-22.5; 14/80-20 365/80-22.5	3255QC	71	7213	3255CAML-7	55	7213CL	3255LMC	70	7213LM
445/65-22.5; 395/85-20 12.00-20; 18-22.5	3261QC	83	7214	-	-	-	3261LMC	84	7214LM
15-19.5; 7.00-20	3265QC	64	7215	-	-	-	3265LMC	64	7215LM
445/50-22.5; 445/55-22.5	3269QC	68		3269CAML-7	55	7215CL	3269LMC	70	
425/65-22.5; 425/55-22.5 455/55-22.5	3271QC	75		-	-	-	3271LMC	76	

WIDE BASE MUD SERVICE TRUCK CHAIN

- OFF-ROAD AND MUD READY
- HEAVY DUTY CROSS CHAIN WITH EXTRA HEAVY HOOKS
- FOR SUPER WIDE SINGLE TIRES

**RUBBER ADJUSTERS
OR SPIDER BUNGEEES
ARE SOLD SEPARATELY**
PART # 0218
SEE PAGE 107 FOR DETAILS

HEAVY DUTY MUD SERVICE (1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT PER PR (LBS)	CROSS CHAIN	WIRE SIZE
385/65-22.5; 12-24.5; 12.00-20; 16.5-19.5; 15-22.5; 13/80-20; 365/70-22.5; 14/80-20 365/80-22.5	3455HH	92	6445	10 MM
445/65-22.5; 395/85-20; 12.00-20; 18-22.5	3461HH	104	7420	
445/50-22.5; 445/55-22.5	3469HH	95	6630	
425/65-22.5; 425/55-22.5; 455/55-22.5	3471HH	102		



WIDE BASE SQUARE LINK

- FOR HIGHWAY AND LIGHT OFF-ROAD USE
- MADE FROM HARDENED ALLOY STEEL
- GREAT TRACTION IN SNOW AND ICE
- TWISTED SQUARE LINKS FOR A SMOOTHER RIDE
- FOR WIDE BASE SUPER SINGLE TIRES



Square Link



Twisted Square Link

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



SQUARE LINK



TWISTED SQUARE LINK

SQUARE LINK CAM STYLE (1 PR/BAG)

TWISTED SQUARE LINK CAM STYLE (1 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN	WIRE SIZE
385/65-22.5; 12-24.5; 12.00-20 16.5-19.5; 15-22.5; 13/80-20 365/70-22.5; 14/80-20 365/80-22.5	3155SLC	78	7213SL	3155SLCTWIST	80	7213SLTWIST	8 MM
445/65-22.5; 395/85-20 12.00-20; 18-22.5	3161SLC	78	7215SL	3161SLCTWIST	80	7214SLTWIST	
15-19.5; 7.00-20	3165SLC	80		3165SLCTWIST	81	7215SLTWIST	
445/50-22.5; 445/55-22.5	3169SLC	80		3169SLCTWIST	82		
425/65-22.5; 425/55-22.5 455/55-22.5	3171SLC	84		3171SLCTWIST	84		

WIDE BASE HEAVY DUTY SQUARE LINK

- RHD = NON-CAM STYLE
- HDQC = CAM STYLE
- HEAVY DUTY FOR OFF-ROAD, PLOW, LOGGING, MINING OR TOW TRUCK APPLICATIONS

ALSO AVAILABLE: HEAVY DUTY TWISTED SQUARE LINK-10 MM
TYPE HDQCTWIST - CAM STYLE
TYPE RHD TWIST - NON CAM STYLE

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



CAM STYLE



NON-CAM STYLE



CAM STYLE (1 PR/BAG)

NON-CAM STYLE (1 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN	WIRE SIZE
385/65-22.5; 12-24.5; 12.00-20 16.5-19.5; 15-22.5; 13/80-20 365/70-22.5; 14/80-20; 365/80-22.5	3155HDQC	108	3155RHD	108	7213HDSL	10 MM
445/65-22.5; 395/85-20; 12.00-20; 18-22.5	3161HDQC	100	3161RHD	99	E6530S	
7.00-20; 15-19.5	3165HDQC	85	3165RHD	88		
445/50-22.5; 445/55-22.5	3169HDQC	121	3169RHD	121		
425/65-22.5; 425/55-22.5; 455/55-22.5	3171HDQC	140	3171RHD	140		



TRUCK

TRYGG SUPER 2000



TRYGG

- CONSTRUCTED OF NICKLE-HARDENED ALLOY STEEL
- LIGHT AND STRONG; 35% WEIGHT REDUCTION COMPARED TO STANDARD CHAINS
- TALLER OVERSIZED RECTANGULAR STUDS TO INCREASE GRIP AND STRENGTH
- SINGLE (6-LINK SPACING)
- TIGHT (4-LINK SPACING)



STANDARD PACKAGING

Packed 1 Pair Per Bag
(Duals Packed 1/2 Pair Per Bag)



MADE IN
NORWAY



TIGHT



SINGLE

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



TRUCK



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

9/32" - 7 MM NON-CAM STYLE

SINGLE (1 PR/BAG)

TIGHT (1 PR/BAG)

DUAL TRIPLE (1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN
7.50-16; 215/85-16	490053	33	492053	42	-	-	307581
215/75-17.5; 235/70-16; 235/75-15	490062	33	492062	42	-	-	307582
225/70-19.5; 235/75-17.5; 235/85-16	490063	33	492063	42	-	-	307582
245/70-19.5; 245/75-17.5; 245/85-16; 255/85-16	490073	37	492073	48	-	-	307583
10-16.5; 265/70-15	490082	33	492082	42	-	-	307584
8.25-20; 9-22.5; 255/70-22.5	490165	42	492165	42	494165	81	307583
9.00-20; 10-22.5	490364	47	492364	61	-	-	307583
11-22.5; 295/75-22.5; 10.00-20; 275/80-22.5; 285/75-22.5; 285/80-22.5	490374	48	492374	64	494374	90	307584
11-24.5; 10.00-22; 295/75-24.5	490375	51	492375	66	494375	95	307584
12-22.5; 11.00-20; 295/80-22.5; 305/75-24.5; 315/75-22.5	490384	51	492384	66	494384	95	307585
12.00-20	490385	55	492385	70	494385	101	307585
12.00-24	490386	59	492386	81	494386	110	307585
315/80-22.5	490394	54	492394	76	494394	106	307586
14.00-24; 385/95-25	490408	73	492408	97	494408	130	307587
14.00-20; 13.50-20	490416	62	492416	81	494416	123	307588
385/65-22.5	490424	59	492424	79	494424	112	307589
425/65-22.5	490444	66	492444	88	494444	123	307591
445/65-22.5	490446	75	492446	97	494446	123	307591

TRYGG

9/32" - 7 MM CAM STYLE

SINGLE (1 PR/BAG)

DUAL TRIPLE (1/2 PR/BAG)

TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN
7.50-16; 215/85-16	491053	33	-	-	307581
215/75-17.5; 235/70-16; 235/75-15	491062	33	-	-	307582
225/70-19.5; 235/75-17.5; 235/85-16	491063	33	-	-	307582
245/70-19.5; 245/75-17.5; 255/85-16	491073	37	-	-	307583
10-16.5; 265/70-15	491082	33	-	-	307584
8.25-20; 9-22.5; 255/70-22.5	491165	42	495165	81	307583
9.00-20; 10-22.5	491364	47	-	-	307583
11-22.5; 295/75-22.5; 10.00-20; 275/80-22.5; 285/75-22.5; 285/80-22.5	491374	48	495374	90	307584
11-24.5; 10.00-22; 295/75-24.5	491375	51	495375	95	307584
12-22.5; 11.00-20; 295/80-22.5; 305/75-24.5; 315/75-22.5	491384	51	495384	95	307585
12.00-20	491385	55	495385	101	307585
12.00-24	491386	59	495386	110	307585
315/80-22.5	491394	56	495394	108	307586
14.00-24; 385/95-25	491408	73	495408	130	307587
14.00-20; 13.50-20	491416	62	495416	123	307588
385/65-22.5	491424	59	495424	112	307589
425/65-22.5	491444	66	495444	123	307591
445/65-22.5	491446	75	495446	123	307591

TRYGG STUDDED TRUCK

- ALL PURPOSE WITH SUPERIOR TRACTION
- DOUBLE DUTY (2-LINK SPACING)



SINGLE



DOUBLE DUTY



DUAL TRIPLE

SINGLE (1 PR/BAG)

5/16" - 8 MM

NON-CAM WITH **CAM**

5/16" - 8 MM

DOUBLE DUTY

TIRE SIZE	STOCK NUMBER	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN
9.00-20; 10-22.5; 275/80-22.5	450364	457364	68	-	-	307081
11-22.5; 295/75-22.5; 10.00-20 285/75-22.5	460200	460201	75	-	-	
11-24.5; 10.00-22; 295/75-24.5	460220	460221	79	462220	131	
12-22.5; 11.00-20; 295/80-22.5	460222	460223	81	462222	179	307082
385/65-22.5	460424	460425	88	462424	145	307088
12-24.5; 12.00-20; 11.00-22	460230	460231	88	462230	145	307082
12.00-24	460232	460233	92	462232	152	307083
315/80-22.5	460394	460395	82	462394	134	307085
425/65-22.5	460444	460845	88	462444	145	307088
445/65-22.5	460445	460846	106	462445	174	

RUBBER ADJUSTERS OR SPIDER BUNGEEES ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS

DUAL TRIPLE (1/2 PR/BAG)

5/16" - 8 MM
NON-CAM

5/16" - 8 MM
WITH **CAM**

TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN
9.00-20; 10-22.5; 275/80-22.5	454364	125	457365	125	307081
11-22.5; 295/75-22.5; 10.00-20 285/75-22.5	464200	136	464201	136	
11-24.5; 10.00-22; 295/75-24.5	464220	145	464221	145	
12-22.5; 11.00-20; 295/80-22.5	464222	152	464223	152	307082
12-24.5; 12.00-20; 11.00-22	464230	161	464231	161	
12.00-24	464232	163	464233	163	307083
315/80-22.5	464394	156	464395	156	307085



STANDARD PACKAGING
Packed 1 Pair Per Bag
(Duals Packed 1/2 Pair Per Bag)

TRYGG 7MM SQUARE ICE



- DEEP CASE HARDENING AND THROUGH HARDENING RESULTS IN EXCELLENT RESISTANCE TO WEAR; PROVIDING USERS WITH INDUSTRY LEADING SERVICE LIFE
- 6 MM SHORT LINK GRADE 80 SIDE CHAIN WITH 7 MM CROSS CHAIN PROVIDES 15% WEIGHT REDUCTION WITHOUT ANY LOSS IN TRACTION OR SERVICE LIFE
- LEVER-STYLE FASTENERS KEEP THE CHAINS TIGHT TO THE TIRE, SAVING INSTALLATION TIME AND IMPROVING PERFORMANCE
- 6-LINK SPACING

TRYGG 8MM SQUARE ICE

- MADE WITH NICKEL, MANGANESE AND BORON FOR EXCELLENT RESISTANCE TO WEAR
- SQUARE LINKS BITE INTO ICE AND HARD-PACKED SNOW
- 6 MM SHORT LINK GRADE 80 SIDE CHAIN
- RELIABLE AND COST EFFECTIVE
- 6-LINK SPACING



SINGLE

DUAL TRIPLE

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS

SINGLE (1 PR/BAG)
SQUARE ICE
9/32" - 7 MM
NON-CAM WITH CAM

SQUARE ICE
5/16" - 8 MM
NON-CAM WITH CAM

TIRE SIZE	STOCK NUMBER	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN 7MM	8MM
225/85-16; 235/85-16	475080	475081	33	-	-	-	304744	-
255/75-22.5	475085	475086	40	-	-	-	304745	-
8.25-20; 9-22.5; 255/70-22.5	475089	475189	43	-	-	-	304744	-
9.00-20; 10-22.5; 275/80-22.5	475090	475091	45	-	-	-	304745	-
11-22.5; 295/75-22.5; 10.00-20	475100	475101	46	475200	475201	73	304746	304884
285/75-22.5; 295/70-22.5	475110	475111	48	475220	475221	75	304747	304884
11-24.5; 10.00-22; 295/75-24.5	475120	475121	53	475170	475171	81	304748	304886
315/80-22.5	475130	475131	55	475230	475231	86	304749	304887
12.00-20	-	-	-	475824	475825	80	-	304890
12.00-24	475125	475126	62	475325	475326	94	304754	304892
385/65-22.5	475144	475145	60	-	-	-	304754	-
445/50-22.5	475127	475128	61	475427	475428	92	304750	304890
425/65-22.5								
445/65-22.5								

DUAL TRIPLE (1/2 PR/BAG)
SQUARE ICE
9/32" - 7 MM
NON-CAM WITH CAM

SQUARE ICE
5/16" - 8 MM
NON-CAM WITH CAM

TIRE SIZE	STOCK NUMBER	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN 7MM	8MM
11-22.5; 295/75-22.5; 10.00-20	469100	469101	84	469200	469201	132	304746	304884
285/75-22.5; 295/70-22.5	469110	469111	87	469220	469221	136	304747	304884
11-24.5; 10.00-22; 295/75-24.5	469120	469121	93	469170	469171	147	304748	304886
315/80-22.5	469130	469131	100	469230	469231	154	304749	304887
12.00-20								
12.00-24								

TRYGG SCAN TRAC

- DESIGNED FOR HIGHWAY TRACTION AND FRONT WHEEL APPLICATIONS
- LIGHT AND STRONG 5 MM (3/16")
- WEAR BARS MAINTAIN AN EXCELLENT GRIP AND INCREASE DURABILITY
- **CAM STYLE**



STANDARD PACKAGING
Packed 1/2 Pair Per Box



SINGLE

DUAL TRIPLE

TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN W/HOOKS
215/70-16; 205/75-16; 225/70-15	477055	24	-	-	478457
215/75-17.5; 215/85-16; 225/75-15	477060	24	477061	46	478457
8.75-16.5; 30x9.50-15; 205/75-17.5; 225/75-16	477070	24	-	-	478457
7.50-16; 225/75-17.5; 245/75-16	477080	26	-	-	478495
9.5-17.5; 265/70-17	477081	26	-	-	478495
245/70-19.5	477083	29	-	-	478517
265/70-19.5	477084	29	-	-	478517
255/70-22.5	477085	31	-	-	478495
295/60-22.5	477086	31	-	-	478537
275/70-22.5; 255/80-22.5	477087	31	-	-	478537
295/70-22.5	477088	35	-	-	478537
8.25-20; 9-22.5	477089	31	-	-	478495
9.00-20; 10-22.5	477090	33	-	-	478497
11-22.5; 10.00-20; 295/75-22.5; 305/70-22.5	477100	35	477101	64	478537
315/70-22.5					
11-24.5; 10.00-22; 11.00-20; 12-22.5	477110	35	477111	64	478537
295/80-22.5					
315/80-22.5	477112	35	-	-	478537
245/70-17.5; 225/70-19.5	477126	24	-	-	478517
445/50-22.5	477190	40	-	-	478657
35x12.50-15	477220	31	-	-	478537
285/70-19.5; 33x12.50-15	477250	31	-	-	478495
385/65-22.5; 365/80-20	477320	37	-	-	478575
455/40-22.5	477323	35	-	-	478577
425/65-22.5	477325	42	-	-	478657
445/65-22.5	477327	44	-	-	478617

RUBBER ADJUSTERS
OR SPIDER BUNGIES
ARE SOLD SEPARATELY
PART # 0218
SEE PAGE 107 FOR DETAILS



PATTERN CLOSE-UP

TRYGG TRUCK GROUSER

- DROP FORGED GROUSERS WITH 10 MM (3/8") RINGS
- TIGHTENING RAIL IS STANDARD
- WIDE ROUNDED BASE REDUCES TIRE WEAR
- GROUSERS ARE SHAPED TO THE RINGS SO THEY CAN'T LAY DOWN
- MADE FOR SNOW BLOWER EQUIPPED COMMERCIAL TRUCKS



TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)
445/65-22.5	503008	240



GROUSER REPAIR KIT
PART # 520110



GROUSER CLOSE-UP



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

LOADER / GRADER



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

	ROUND TWIST 2600	SQUARELINK 6500	NORDIC STUDDUED 2900	MAX TRACK H-PATTERN 6500MT	NORDIC STUDDUED H-PATTERN 2900SHP	DIAMOND PATTERN DRQ 500/600 DRQ	SWISS FLEXI 570000
TIRE SIZE	Page 62	Page 62	Page 63	Page 64	Page 64	Page 65	Page 69
13.00-24	2612	6512	2912	6515MT	2915SHP	-	-
13.00-25	2612	6512	2912	6515MT	2915SHP	-	-
13.6-28	2612	6512	2912	6515MT	2915SHP	-	570921
14.00-20	2612	6512	2912	-	2915SHP	-	-
14.00-21	2612	6512	2912	-	-	-	-
14.00-24	2615	6515	2915	6515MT	2915SHP	540DRQ	570762
14.00-25	2615	6515	2915	6515MT	2915SHP	540DRQ	570762
14.5-20	2612	6512	2912	-	-	-	-
14.75/80-20	2612	6512	2912	-	2915SHP	-	-
14.9-24	2612	6512	2912	6515MT	2915SHP	-	570935
15-19.5 R4 TIRE	3265HD	-	-	-	-	-	-
15.5-25	2612	6512	2912	6515MT	2915SHP	-	570760
16.00-20	2624	6524	2924	6524MT	2924SHP	-	-
16.00-21	2624	6524	2924	6524MT	2924SHP	-	-
16.00-24	2627	6527	2927	6527MT	2927SHP	-	570781
16.00-25	2627	6527	2927	6527MT	2927SHP	-	570781
16.9-24	2615	6515	2915	6515MT	2915SHP	-	570945
16.9-26	2615	6515	2915	6515MT	2915SHP	-	-
16.9-28 R1-R4	-	-	-	6515MT	2915SHP	-	570950
16.9-30	-	-	-	6515MT	2915SHP	-	570950
17.5/65-20	2627	6527	2927	-	-	-	-
17.5L-24	2615	6515	2915	6515MT	2915SHP	-	-
17.5-25	2624	6524	2924	6524MT	2924SHP	580DRQ	570762
18.00-25	2636	6536	2936	-	-	-	570782
18.00-26	2636	6536	2936	-	-	-	-
18.00-33	2642	6542	-	-	-	-	-
18.4-30	-	-	-	6533MT	2933SHP	-	570950
18.4-34	-	-	-	6545MT	2945SHP	-	570950
19.5L-24	2627	6527	2927	6527MT	2927SHP	-	-
20.5-25	2633	6533	2933	6533MT	2933SHP	592DRQ	570764
20.8-34	-	-	-	6545MT	2945SHP	-	-
21L-24	2636	6536	2936	6533MT	2933SHP	-	-
23.1-26	-	-	-	6545MT	2945SHP	-	570970
23.5-25	2645	6545	2945	6545MT	2945SHP	602DRQ	570766
25/65-25	2645	6545	2945	6545MT	2945SHP	-	-
25.5-25	2645	6545	2945	-	2945SHP	-	-
26.5-25	2657	6557	2957	-	2957SHP	620DRSQ	570768
29.5-25	2672	6572	2972	-	2972SHP	-	570772
29.5-29	2675	6575	2975	-	2975SHP	-	-
35/65-33	-	6580	-	-	-	-	-
38/18.00-20	2612	6512	2912	-	-	-	-
44/18.00-20	2612	6512	2912	-	-	-	-
405/70-18	2612	6512	2912	-	-	-	570930
445/65-19.5	2612	6512	2912	-	2912SHP	-	-
400/70-20	2612	6512	2912	-	-	-	-
405/70-20	2612	6512	2912	-	-	-	570930
375/75-20	2612	6512	2912	-	-	-	-



LOADER / GRADER




MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
 EMAIL: INFO@CHAINQUEST.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

	ROUND TWIST 2600	SQUARE LINK 6500	NORDIC STUDDED 2900	MAX TRACK H-PATTERN 6500MT	NORDIC STUDDED H-PATTERN 2900SHP	DIAMOND PATTERN DRQ 500/600 DRQ	SWISS FLEXI 570000
TIRE SIZE	Page 62	Page 62	Page 63	Page 64	Page 64	Page 65	Page 69
355/80-20	3257	3157RHD	-	-	-	-	570926
360/80-20	2612	6512	2912	-	2912SHP	-	-
395/80-20	2615	6515	2915	-	-	-	-
395/85-20	2615	6515	2915	-	-	-	570930
495/55-22.5	2612	6512	2912	-	-	-	-
420/70-24	2624	6524	2924	6515MT	2915SHP	-	570945
440/70-24	2615	6515	2915	6515MT	2915SHP	-	570945
445/70-24	2615	6515	2915	6515MT	2915SHP	-	570945
460/70-24	2615	6515	2915	6515MT	2915SHP	-	570945
495/70-24	2627	6527	2927	6527MT	2927SHP	-	570955
500/70-24	2627	6527	2927	6527MT	2927SHP	-	570955
380/85-24	2612	6512	2912	-	-	-	570935
420/85-24	2615	6515	2915	6515MT	2915SHP	-	570945
385/95-24	2615	6515	2915	6515MT	2915SHP	540DRQ	-
550/65-25	2636	6536	2936	6533MT	2933SHP	-	-
600/65-25	2642	6542	-	-	-	-	-
650/65-25	-	-	-	-	-	620DRSQ	-
750/65-25	2657	6557	2957	-	2957SHP	-	570803
555/70-25	2636	6536	2936	-	2933SHP	-	-
755/70-25	2657	6557	2957	-	2957SHP	-	-
385/95-25	2615	6515	2915	6515MT	2915SHP	540DRQ	-
620/75-26	-	-	-	6545MT	2945SHP	-	-
420/85-26	-	-	-	6515MT	2915SHP	-	-
440/65-28	2612	6512	2912	6515MT	2915SHP	-	570945
340/85-28	2612	6512	2912	6515MT	2915SHP	-	570921
875/65-29	2675	6575	2975	-	2975SHP	-	-
800/65-32	2657	6557	2957	-	2957SHP	-	-
480/85-34	-	-	-	6545MT	2945SHP	-	-
710/70-38	2657	6557	2957	-	2957SHP	-	-



LOADER / GRADER

LOADER/GRADER CHAIN

- REGULAR ROUND TWIST LINK AND V-BAR WITH ICE BREAKERS
- **PREMIUM** STOCK NUMBERS MADE OF ALLOY STEEL BEGIN WITH AN "A"
- FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.

ALSO AVAILABLE: 2-LINK SPACING (ADD "-2" TO THE END OF THE PART #)



SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



4-LINK SPACING PICTURED

TIRE SIZE	STOCK NUMBER	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	WIRE SIZE
13.00-24; 13.00-25; 14.00-20; 14.00-21; 15.5-25; 14.75/80-20	2612	A2612	113	6630 / A6630	10 MM
44/18.00-20; 445/65-19.5; 495/55-22.5; 360/80-20; 400/70-20	2612V	A2612V	126	6830 / A6830	
14.00-24; 14.00-25; 395/85-20; 385/95-24; 385/95-25; 17.5L-24	2615	A2615	128	6630 / A6630	
	2615V	A2615V	144	6830 / A6830	
17.5-25; 16.00-20; 16.00-21; 420/70-24	2624	A2624	153	6640 / A6640	11 MM
16.00-24; 16.00-25; 17.5/65-20; 19.5L-24	2627	A2627	175		
20.5-25	2633	A2633	192	6650 / A6650	
18.00-25; 18.00-26; 21L-24; 555/70-25; 550/65-25	2636	A2636	202		
18.00-33; 600/65-25	2642	A2642	244		
23.5-25; 25.5-25	2645	A2645	368	6660 / A6660	13.5 MM
26.5-25; 750/65-25; 755/70-25; 800/65-32; 710/70-38	2657	A2657	456	6670 / A6670	
29.5-25	2672	A2672	516	6680 / A6680	
29.5-29; 875/65-29	2675	A2675	531		

SQUARE LINK ALLOY

- ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- REVERSIBLE - CAN BE RUN ON BOTH SIDES
- SQUARE LINK DESIGN FOR INCREASED TRACTION
- FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.

ALSO AVAILABLE: WITH SHACKLES INSTEAD OF HOOKS



SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



2-LINK SPACING PICTURED

4-LINK SPACING			2-LINK SPACING				
TIRE SIZE	STOCK NUMBER	WEIGHT/ PR (LBS)	STOCK NUMBER	WEIGHT/ PR (LBS)	SIDE CHAIN	CROSS CHAIN	WIRE SIZE
13.00-24; 15.5-25; 495/55-22.5; 360/80-20 400/70-20	6512	132	6512-2	209	AL40375H	E6530S	10 MM
14.00-24 SPECIAL	6514	100	6514-2	183	AL40312H	E6520S	8 MM
14.00-24; 14.00-25; 395/85-20; 17.5L-24	6515	149	6515-2	227	AL40375H	E6530S	10 MM
17.5-25; 16.00-20; 420/70-24	6524	199	6524-2	326	AL40437H	E6540SH	11 MM
16.00-24; 16.00-25; 17.5/65-20; 19.5L-24	6527	233	6527-2	372		E6550SH	
20.5-25	6533	258	6533-2	428			
18.00-25; 18.00-26; 21L-24; 555/70-25; 550/65-25	6536	242	6536-2	388			
18.00-33; 600/65-25	6542	292	6542-2	488			
23.5-25; 25.5-25	6545	302	6545-2	492	AL40531H	E6560SH	13.5MM
26.5-25; 750/65-25; 755/70-25; 800/65-32; 710/70-38	6557	372	6557-2	612		E6570SH	
29.5-25	6572	412	6572-2	696		E6580SH	
29.5-29; 875/65-29	6575	554	6575-2	854			
35/65-33	6580	608	6580-2	995			



LOADER / GRADER

PREMIUM SQUARE LINK ALLOY

- **PREMIUM** ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- **REVERSIBLE** - CAN BE RUN ON BOTH SIDES
- **SQUARE LINK DESIGN** FOR INCREASED TRACTION
- **FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.**

ALSO AVAILABLE: WITH SHACKLES INSTEAD OF HOOKS



SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



4-LINK SPACING

2-LINK SPACING

4-LINK SPACING PICTURED

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)	SIDE CHAIN	CROSS CHAIN	WIRE SIZE
13.00-24; 15.5-25; 495/55-22.5; 360/80-20; 400/70-20	6512N	122	6512-2N	219	AL40375H	E6530N	10 MM
14.00-24 SPECIAL	6514N	105	6514-2N	188	AL40312H	E6520N	8 MM
14.00-24; 14.00-25; 395/85-20; 385/95-25; 17.5L-24	6515N	148	6515-2N	274	AL40375H	E6530N	10 MM
17.5-25; 16.00-20; 420/70-24	6524N	177	6524-2N	286	AL40437H	E6540N	11 MM
16.00-24; 16.00-25; 17.5/65-20; 19.5L-24	6527N	212	6527-2N	386		E6550N	13.5 MM
20.5-25	6533N	250	6533-2N	412	AL40531H	E6560N	
23.5-25; 25.5-25	6545N	296	6545-2N	504		E6570N	
26.5-25; 750/65-25; 755/70-25; 800/65-32; 710/70-38	6557N	389	6557-2N	635		E6580N	
29.5-25	6572N	420	6572-2N	705		E6590N	
29.5-29; 875/65-29	6575N	586	6575-2N	869			
35/65-33	6580N	631	6580-2N	1012			

NORDIC™ STUDDED ALLOY

- **PREMIUM** ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- **STUDDED LINK** WITH EXTRA HARD STUD TIPS
- **EXCELLENT TRACTION** IN EXTREME CONDITIONS
- **FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.**



SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



4-LINK SPACING

2-LINK SPACING

4-LINK SPACING PICTURED

TIRE SIZE	PREMIUM STOCK NO.	WEIGHT/ PR (LBS)	CROSS CHAIN	2 LINK STOCK NO.	WEIGHT/ PR (LBS)	CROSS CHAIN	WIRE SIZE
13.00-24; 13.00-25; 14.00-20; 14.00-21; 15.5-25	2912	126	6930N	-	-	-	10 MM
14.75/80-20; 44/18.00-20; 445/65-19.5; 495/55-22.5							
360/80-20; 400/70-20	2915	148	6940N	2915-2	242	6930N	11 MM
14.00-24; 14.00-25; 395/85-20; 385/95-24; 17.5L-24	2924	198		2924-2	350	6940N	
17.5-25; 16.00-20; 16.00-21; 420/70-24	2927	244	6950N	2927-2	450	6940N	
16.00-24; 16.00-25; 19.5L-24; 17.5/65-20	2933	261		2933-2	460	6950N	13.5 MM
20.5-25	2936	248	6960N	-	-	-	
18.00-25; 18.00-26; 21L-24; 555/70-25; 550/65-25	2945	324	6970N	2945-2	566	6960N	
23.5-25; 25.5-25	2957	482	6980N	2957-2	850	6970N	
26.5-25; 750/65-25; 755/70-25; 800/65-32; 710/70-38	2972	528		-	-	-	
29.5-25	2975	558		-	-	-	
29.5-29; 875/65-29							

MAXTRACK H-PATTERN

- H-PATTERN STYLE ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- SQUARE LINK WITH LINK-OVER-LINK DESIGN FOR BETTER TRACTION
- FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.



SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



3/8"- 10 MM

7/16"- 11 MM

17/32"- 13.5 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN
13.00-24	6512MT-10	202	8901	6515MT-11	296	8903	-	-	-
14.00-24; 15.5-25; 16.9-24; 17.5L-24	6515MT-10	214	8902	6527MT-11	356	8904	-	-	-
16.00-24; 16.00-25; 19.5L-24	6527MT-10	236	-	6524MT-11	286	8905	6524MT-13	320	8907
17.5-25; 16.00-20	-	-	-	6533MT-11	346	8906	6533MT-13	442	8908
20.5-25; 550/65-25	-	-	-	6545MT-11	384	-	6545MT-13	512	8909
23.5-25; 25/65-25	-	-	-						

NORDIC™ STUDDED H-PATTERN

- PREMIUM ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- STUDDED LINK WITH EXTRA HARD STUD TIPS
- EXCELLENT TRACTION IN EXTREME CONDITIONS
- H-PATTERN DESIGN PROVIDES SMOOTHER RIDE
- FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.



SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



3/8"- 10 MM

7/16"- 11 MM

17/32"- 13.5 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN
13.00-24	2912SHP-10	231	8501	2915SHP-11	278	8503	-	-	-
14.00-24; 15.5-25; 16.9-24; 17.5L-24	2915SHP-10	235	8502	2927SHP-11	281	8504	-	-	-
16.00-24; 16.00-25; 19.5L-24	2927SHP-10	258	-	2924SHP-11	338	-	2924SHP-13	378	8507
17.5-25; 16.00-20	-	-	-	2933SHP-11	406	8505	2933SHP-13	400	8508
20.5-25; 550/65-25	-	-	-	2945SHP-11	476	8506	2945SHP-13	554	-
23.5-25; 25/65-25	-	-	-	-	-	-	2957SHP-13	640	8510
26.5-25	-	-	-	-	-	-	2972SHP-13	649	8511
29.5-25	-	-	-	-	-	-	-	-	-
29.5-29; 875/65-29	-	-	-	-	-	-	2975SHP-13	701	-

PREMIUM DIAMOND PATTERN

- **PREMIUM** DIAMOND PATTERN HIGH-ALLOY CHAIN FOR SNOW REMOVAL APPLICATIONS
- FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.
- PULL CHAIN TIGHTENING SYSTEM

SINGLE DIAMOND (TYPE DRQ)

SINGLE DIAMOND WITH WEAR BARS (TYPE WBQ)

DOUBLE DIAMOND (TYPE DRSQ)

DOUBLE DIAMOND WITH WEAR BARS (TYPE WBSQ)

DRQ SINGLE DIAMOND

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	WIRE SIZE
14.00-24	538DRQ	256	8 MM
	540DRQ	344	10 MM
17.5-25	580DRQ	362	11 MM
20.5-25	592DRQ	449	
23.5-25	602DRQ	484	

WBQ SINGLE DIAMOND w/ WEAR BARS

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)	WIRE SIZE
14.00-24	540WBQ	383	10 MM
16.00-24	560WBQ	376	
17.5-25	580WBQ	403	
20.5-25	590WBQ	379	
	592WBQ	510	11 MM
	600WBQ	477	10 MM
23.5-25	602WBQ	553	11 MM
	613WBQ	794	13.5 MM

DRSQ DOUBLE DIAMOND

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)
14.00-24	540DRSQ	390
17.5-25	580DRSQ	394
20.5-25	590DRSQ	492
	592DRSQ	556
23.5-25	600DRSQ	571
	602DRSQ	596
26.5-25	620DRSQ	741

WBSQ DOUBLE DIAMOND w/ WEAR BARS

STOCK NUMBER	WEIGHT PER PAIR (LBS)	WIRE SIZE
540WBSQ	453	10 MM
580WBSQ	450	
590WBSQ	576	
-	-	11 MM
600WBSQ	627	10 MM
-	-	11 MM
-	-	



SINGLE DIAMOND (DRQ PICTURED)



DOUBLE DIAMOND (DRSQ PICTURED)



LOADER / GRADER

DIAMOND BACK SQUARE LINK

- ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- DIAMOND BACK PATTERN DESIGN PROVIDES A SMOOTHER RIDE
- FOR PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.

REGULAR
DIAMOND PATTERN
(TYPE DP)



U-GRIP
DIAMOND PATTERN
(TYPE DPU)



LINK-OVER-LINK
DIAMOND PATTERN
(TYPE WDP)



WEAR BAR
DIAMOND PATTERN
(TYPE WB)



**SHACKLE STYLE
ADJUSTERS
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107**



NOTE: NOT INTENDED FOR MINING APPLICATIONS.

3/8"- 10 MM

TYPE WDP PICTURED

TIRE SIZE	DP STOCK NUMBER	WEIGHT/ PR (LBS)	DPU STOCK NUMBER	WEIGHT/ PR (LBS)	WDP STOCK NUMBER	WEIGHT/ PR (LBS)	WB STOCK NUMBER	WEIGHT/ PR (LBS)
14.00-24; 15.5-25; 17.5L-24; 16.9-24	-	-	2715DPU-10	354	-	-	2715WB-10	282
16.00-24; 16.00-25; 19.5L-24	2727DP-10	282	2727DPU-10	378	2727WDP-10	306	2727WB-10	344

7/16"- 11 MM

TIRE SIZE	DP STOCK NUMBER	WEIGHT/ PR (LBS)	DPU STOCK NUMBER	WEIGHT/ PR (LBS)	WDP STOCK NUMBER	WEIGHT/ PR (LBS)	WB STOCK NUMBER	WEIGHT/ PR (LBS)
16.00-24; 16.00-25; 19.5L-24	2727DP-11	388	2727DPU-11	438	2727WDP-11	436	2727WB-11	448
17.5-25; 16.00-20	-	-	-	-	6524WDP-11	375	6524WB-11	416
20.5-25; 18.00-25; 18.4-30; 21L-24	-	-	2733DPU-11	472	6533WDP-11	496	6533WB-11	568
23.5-25; 21.00-25; 20.8-34; 25/65-25	-	-	2745DPU-11	538	-	-	-	-

17/32"- 13.5 MM

TIRE SIZE	DP STOCK NUMBER	WEIGHT/ PR (LBS)	DPU STOCK NUMBER	WEIGHT/ PR (LBS)	WDP STOCK NUMBER	WEIGHT/ PR (LBS)	WB STOCK NUMBER	WEIGHT/ PR (LBS)
17.5-25; 16.00-20	-	-	2724DPU-13	516	6524WDP-13	450	6524WB-13	590
20.5-25; 18.00-25; 18.4-30; 21L-24	-	-	-	-	6533WDP-13	648	6533WB-13	740
23.5-25; 21.00-25; 20.8-34; 25/65-25	-	-	-	-	6545WDP-13	648	6545WB-13	738
26.5-25	-	-	2757DPU-13	900	6557WDP-13	814	6557WB-13	934
29.5-25	-	-	-	-	2772WDP-13	968	2772WB-13	1136
29.5-29	-	-	2775DPU-13	940	-	-	-	-

5/8"- 16 MM

TIRE SIZE	DP STOCK NUMBER	WEIGHT/ PR (LBS)	DPU STOCK NUMBER	WEIGHT/ PR (LBS)	WDP STOCK NUMBER	WEIGHT/ PR (LBS)	WB STOCK NUMBER	WEIGHT/ PR (LBS)
29.5-29	-	-	2775DPU-16	1550	-	-	-	-



LOADER / GRADER

NORDIC™ SUPER GRIP STUDDED



- **PREMIUM** ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- **STUDDED** LINK WITH EXTRA HARD STUD TIPS
- **BEST** FOR AGGRESSIVE OFF-ROAD APPLICATIONS
- **CONTINUOUS** PATTERN PROVIDES EXCELLENT TRACTION IN ALL DIRECTIONS FOR STUDS TO DIG INTO TERRAIN



	3/8"- 10 MM		7/16"- 11 MM		17/32"- 13.5 MM	
TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)
13.00-24	-	-	-	-	-	-
14.00-24; 15.5-25; 16.9-24	2915NSG-10	295	2915NSG-11	324	-	-
17.5-25; 16.00-20; 17.5L-24	-	-	2924NSG-11	337	2924NSG-13	370
16.00-24; 16.00-25; 19.5L-24	-	-	2927NSG-11	336	2927NSG-13	465
20.5-25; 550/65-25; 555/70-25	-	-	2933NSG-11	361	2933NSG-13	504
23.5-25; 625/70-20	-	-	2945NSG-11	427	2945NSG-13	594

**SHACKLE STYLE
ADJUSTERS**
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



LOADER / GRADER

TRYGG BEAVER

- TRACTION & RELIABILITY
- LONG LASTING CHAIN
- HIGH TECH CHAIN FOR HEAVY DUTY MACHINERY
- 1/2" - 13 MM RINGS



TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)
16.00-24; 16.00-25	505021	596
16.00-24L5; 16.00-25L5	505022	596
17.5-25	505041	539
20.5-25	505051	625
20.5-25L5	505052	686
23.5-25	505061	717
23.5-25L5	505062	790
26.5-25	505068	946
26.5-25L5	505069	1041
29.5-25	505070	1144
29.5-25L5	505773	1243
29.5-29	505774	1208
29.5-29L5	505775	1327
35/65-33	505821	1628
35/65-33L5	505822	1791



BEAVER / LYNX CLOSE-UP



TRYGG LYNX

- MADE FOR CONSTRUCTION & SNOW CLEARING USE
- HEAVY DROP FORGED GROUSERS
- THREE SQUARE STUDS ENSURE BETTER TRACTION
- 1/2" - 13 MM RINGS

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)
17.5-25; 14.00-24	506050	460
20.5-25; 525/80-25	506051	506
23.5-25; 605/80-25	506052	601
23.5-25L5	506067	585
26.5-25; 685/80-25	506068	629
26.5-25L5	506069	634



LOADER / GRADER



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
 EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

TRYGG SWISS FLEXI

- AVAILABLE IN 8 MM AND 11.5 MM
- SUPER HARDENED WEAR BARS GIVE EXCELLENT GRIP AND ENSURE LONG SERVICE LIFE
- AGGRESSIVE AND SMOOTH RUNNING
- GREAT FOR SNOW PLOWS
- TENSIONING CHAIN AND MOUNTING INSTRUCTIONS INCLUDED



SWISS FLEXI CLOSE-UP



5/16"- 8 MM

STOCK NO: 570945 WEIGHT(LBS): 266	STOCK NO: 570950 WEIGHT(LBS): 326	STOCK NO: 570955 WEIGHT(LBS): 319	STOCK NO: 570960 WEIGHT(LBS): 328	STOCK NO: 570965 WEIGHT(LBS): 236	STOCK NO: 570970 WEIGHT(LBS): 370	STOCK NO: 570980 WEIGHT(LBS): 473
14.00-24 14.00-25 15.5-25 16.9-24	16.9-28 16.9-30 18.4-26 440/80-30	17.5-25 480/65-28 480/80-26 500/70-24	16.00-24 16.00-25 18.00-24 18.00-25	540/65-24 540/65-28	20.5-25 540/65-30	23.5-25 23.5-25L5 650/65-38 650/65-42



29/64"- 11.5 MM

STOCK NO: 570760 WEIGHT(LBS): 332	STOCK NO: 570762 WEIGHT(LBS): 359	STOCK NO: 570781 WEIGHT(LBS): 400	STOCK NO: 570782 WEIGHT(LBS): 429	STOCK NO: 570764 WEIGHT(LBS): 416	STOCK NO: 570766 WEIGHT(LBS): 476	STOCK NO: 570768 WEIGHT(LBS): 546	STOCK NO: 570772 WEIGHT(LBS): 620
14.00-24 15.5-25	14.00-25 17.5-25	16.00-24 16.00-25	18.00-24 18.00-25	20.5-25	23.5-25	26.5-25	29.5-25

TRYGG GROUSER

- DROP FORGED GROUSERS WITH 3/8" - 10 MM RINGS
- TIGHTENING RAIL IS STANDARD
- WIDE ROUNDED BASE REDUCES TIRE WEAR
- GROUSERS ARE SHAPED TO THE RINGS SO THEY CAN'T LAY DOWN

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)
14.00-24	503040	244
16.00-24	503041	297
18.00-24	503042	341
15.5-25	503048	242
17.5-25	503050	253
385/95-25	503051	338
20.5-25	503051	338
23.5-25	503052	391



GROUSER REPAIR KIT
PART # 520110



GROUSER CLOSE-UP



LOADER / GRADER

TRYGG SMT FLEXI



- A PERFECT FIT WITHOUT THE USE OF TOOLS
- SMT FLEXI USES STEEL ENHANCED WITH BORON, NICKEL, CHROMIUM AND MANGANESE; FULLY HARDENED FOR MAXIMUM DURABILITY
- HARDENED 10 MM HOOKS AND 8 MM SIDE CHAIN ARE STANDARD ON BOTH SIDES
- OPTIONAL TIGHTENING RAIL AVAILABLE, PART #336030

5/16"- 8 MM

3/8"- 9.5 MM

STOCK NO: 602903 WEIGHT(LBS): 165	STOCK NO: 602904 WEIGHT(LBS): 143	STOCK NO: 602907 WEIGHT(LBS): 156	STOCK NO: 603901 WEIGHT(LBS): 262	STOCK NO: 603903 WEIGHT(LBS): 216	STOCK NO: 603906 WEIGHT(LBS): 222
14.9-24	14.5-20	16/70-20 365/80-20 375/75-20 405/70-18 405/70-20	16.00-24 16.00-25 16.9-28 16.9-30 18.4-26 440/80-28	13.00-24 13.00-25 13.6-28 14.00-20 14.9-24 14.9-28 15.5-25	14.00-24 14.00-25 14.9-28 16.9-24
STOCK NO: 602910 WEIGHT(LBS): 187	STOCK NO: 602911 WEIGHT(LBS): 202		STOCK NO: 603907 WEIGHT(LBS): 183	STOCK NO: 603908 WEIGHT(LBS): 273	STOCK NO: 603911 WEIGHT(LBS): 233
440/65-28 420/70-24 460/70-24 400/80-24 440/70-24 445/70-24 460/65-24 420/65-24 445/65-22.5	17.5-25 19.5L-24 440/80-24 480/65-28		14.5-20 365/80-20 375/75-20 400/70-18 405/70-18	20.5-25 540/65-30	17.5-25 19.5L-24 440/80-24 480/65-28



**SHACKLE STYLE
ADJUSTERS**
ARE SOLD SEPARATELY
PART #0294, #0296
SEE PAGE 107



SMT FLEXI LINK
PART # 335508



FLEXI LINK CLOSE-UP

TRYGG SMT

- OVERSIZED STUDS INCREASE GRIP AND LAST LONGER
- SMT PATTERN HOLDS THE CHAIN ON TOP OF THE TIRE LUGS, KEEPING THE STUDS IN CONSTANT CONTACT WITH THE TERRAIN
- SMT COMBO FITS MORE THAN ONE TIRE SIZE
- GREAT FOR USE WITH SNOW CLEARING, FORESTRY AND CONSTRUCTION VEHICLES



3/8"- 9.5 MM 7/16"-11 MM 1/2"- 13 MM 5/8"- 16 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)
14-17.5	603092	160	-	-	-	-	-	-
14.00-24	603780	213	605780	271	-	-	-	-
16.00-24	-	-	605781	308	606781	442	-	-
15-19.5	603110	150	-	-	-	-	-	-
15.5-25	603760	198	605760	251	-	-	-	-
17.5-25	603762	218	605762	277	606762	387	-	-
20.5-25	603764	257	605764	323	606764	425	-	-
20.5-25L5	-	-	605765	345	606765	453	-	-
23.5-25	-	-	-	-	606766	480	608766	813
23.5-25L5	-	-	-	-	-	-	608767	708
26.5-25	-	-	-	-	-	-	608768	805
26.5-25L5	-	-	-	-	-	-	608769	862

SMT COMBO

TIRE SIZE	STOCK NUMBER	INCHES	MM	WEIGHT/ PR (LBS)
17.5-25; 16.9-30	606552	1/2"	13	442
20.5-25; 18.00-25	608965	5/8"	16	717
23.5-25; 18.00-25L5	608968	5/8"	16	860
26.5-25; 26.5-25L5; 29.5-25	608969	5/8"	16	854



LOADER / GRADER



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@CHAINQUEST.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

TRACTOR



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

	ROUND TWIST TRACTOR 0800	SQUARE LINK TRACTOR 0800SL	DUO GRIP H-PATTERN TRACTOR DUO200	DUO GRIP H-PATTERN V-BAR DUO200V	LIGHT WT ALLOY DUO H-PATTERN DUO200-7	TRYGG SWISS FLEXI 570000	TRYGG SMT FLEXI 602000 603000	MAXTRACK SQUARE LINK H-PATTERN 6500MT	PREMIUM STUDDUED H-PATTERN 2900SHP
TIRE SIZE	Page 76	Page 76	Page 77	Page 77	Page 77	Page 78	Page 79	Page 81	Page 81
7.50-18	0836	0836SL	DUO239	DUO239V	DUO239-7	-	-	-	-
7.50-20	0836	0836SL	DUO239	DUO239V	DUO239-7	-	-	-	-
8.3-16	3227	3127RHD	-	-	-	-	-	-	-
8.3-24	0822	-	-	-	-	-	602905	-	-
9.5-16	0829	0829SL	-	-	-	-	-	-	-
9.5-18	0822	-	-	-	-	-	-	-	-
9.5-20	0832	0832SL	DUO214	-	DUO214-7	-	602905	-	-
9.5-24	0832	0832SL	DUO214	-	DUO214-7	-	602905	-	-
9.5-28	0836	0836SL	DUO214	-	DUO214-7	-	-	-	-
9.5-32	0838	0838SL	DUO226	-	DUO226-7	-	-	-	-
9.5-48	-	-	DUO236	-	DUO236-7	-	-	-	-
10/75-15.3	1501	1501HDSL	-	-	-	-	602908	1501MT	-
10-16.5	1501	1501HDSL	-	-	-	-	602908	1501MT	-
10-32	-	-	DUO218	-	DUO218-7	-	-	-	-
10-38	-	-	DUO232	-	DUO232-7	-	-	-	-
10.5/80-18	0832	0832SL	-	-	-	-	-	-	-
11.00-16	0822	-	-	-	-	-	-	-	-
11-28	-	-	DUO218	-	DUO218-7	-	-	-	-
11-36	-	-	DUO232	-	DUO232-7	-	-	-	-
11-38	-	-	DUO232	-	DUO232-7	-	-	-	-
11.2-16	-	-	DUO214	-	DUO214-7	-	-	-	-
11.2-24	0838	0838SL	DUO226	-	DUO226-7	570926	602902	-	-
11.2-28	0838	0838SL	DUO229	-	DUO229-7	570921	602902	-	-
11.2-32	-	-	DUO218	-	DUO218-7	-	-	-	-
11.2-34	0846	-	DUO224	-	DUO224-7	-	-	-	-
11.2-36	0846	-	DUO224	-	DUO224-7	-	-	-	-
11.2-38	0862	-	DUO232	-	DUO232-7	-	-	-	-
11.2-44	-	-	DUO236	-	DUO236-7	-	-	-	-
12-28	-	-	DUO242	DUO242V	DUO242-7	-	-	-	-
12-36	-	-	DUO246	DUO246V	DUO246-7	-	-	-	-
12-16.5	1502	1502HDSL	-	-	-	-	602908	1502MT	-
12.4-16	0836	0836SL	DUO239	DUO239V	DUO239-7	-	-	-	-
12.4-24	0859	0859SL	DUO242	DUO242V	DUO242-7	570921	603910	-	-
12.4-28	0856	-	DUO218	-	DUO218-7	570921	603910	-	-
12.4-34	0876	-	DUO262	DUO262V	-	-	-	-	-
12.4-36	0862	-	DUO232	-	DUO232-7	-	603904	-	-
12.4-38	0862	-	DUO232	-	DUO232-7	-	603904	-	-
12.4-40	-	-	DUO246	DUO246V	DUO246-7	-	-	-	-
12.4-42	0866	-	DUO246	DUO246V	DUO246-7	-	-	-	-
12.5-18	0834	0834SL	DUO210	-	DUO210-7	-	602906	-	-
12.5/80-18	0834	0834SL	DUO210	-	DUO210-7	-	602906	-	-
13.00-24	-	-	DUO242	DUO242V	DUO242-7	-	603903	6515MT	2915SHP
13.5-16.1	0838	0838SL	DUO214	-	DUO214-7	-	-	-	-
13.6-16	0850	-	-	-	-	570926	602904	-	-
13.6-24	0856	-	DUO240	DUO240V	DUO240-7	570921	603907	-	-
13.6-26	0858	-	DUO240	DUO240V	DUO240-7	-	-	-	-
13.6-28	0859	0859SL	DUO242	DUO242V	DUO242-7	570921	603903	6515MT	2915SHP
13.6-36	0866	-	DUO246	DUO246V	DUO246-7	-	603904	-	-
13.6-38	0866	-	DUO246	DUO246V	DUO246-7	-	603904	-	-
13.9-36	0866	-	DUO246	DUO246V	DUO246-7	-	-	-	-
14-17.5	1503	1503HDSL	-	-	-	-	603092	1503MT	-
14.00-24	-	-	DUO262	DUO262V	-	570945	603906	6515MT	2915SHP
14.5-20	0858	-	-	-	-	-	603907	-	-
14.9-24	0859	0859SL	DUO242	DUO242V	DUO242-7	570935	603903	6515MT	2915SHP

TRACTOR



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

TIRE SIZE	ROUND TWIST TRACTOR 0800	SQUARELINK TRACTOR 0800SL	DUO GRIP H-PATTERN TRACTOR DUO200	DUO GRIP H-PATTERN V-BAR DUO200V	LIGHT WT ALLOY DUO H-PATTERN DUO200-7	TRYGG SWISS FLEXI 570000	TRYGG SMT FLEXI 602000 603000	MAXTRACK SQUARELINK H-PATTERN 6500MT	PREMIUM STUDDER H-PATTERN 2900SHP
	Page 76	Page 76	Page 77	Page 77	Page 77	Page 78	Page 79	Page 81	Page 81
14.9-26	0869	-	DUO250	DUO250V	DUO250-7	570935	603903	-	-
14.9-28	0869	-	DUO250	DUO250V	DUO250-7	570935	603906	-	-
14.9-30	0876	-	DUO252	DUO252V	DUO252-7	570935	603906	-	-
14.9-38	0871	-	DUO254	-	-	-	603901	-	-
14.9-46	-	-	DUO256	DUO256V	-	-	-	-	-
15-19.5 R4 TIRE	0859	0859SL	DUO239	DUO239V	DUO239-7	-	603110	-	-
15-22.5	0852	-	-	-	-	-	-	-	-
15.5-38	0879	-	DUO270	DUO270V	-	-	603901	-	-
16.9-24	0874	0874SL	DUO262	DUO262V	-	570945	603906	6515MT	2915SHP
16.9-26	0876	-	DUO262	DUO262V	-	-	603906	6515MT	2915SHP
16.9-28 R1-R4	0876	-	DUO262	DUO262V	-	570950	603901	6515MT	2915SHP
16.9-30	0877	-	DUO266	DUO266V	-	570950	603901	-	-
16.9-32	0877	-	DUO266	DUO266V	-	-	-	-	-
16.9-34	0879	-	DUO270	DUO270V	-	570950	603901	-	-
16.9-38	0880	-	DUO272	DUO272V	-	570950	603902	-	-
16.9-46	-	-	DUO256	DUO256V	-	-	-	-	-
17.5L-24	0874	0874SL	DUO262	DUO262V	-	-	603911	6515MT	2915SHP
17.5-25	-	-	DUO268	DUO268V	-	570762	603911	6524MT	2924SHP
18.4-16.1	0881	-	DUO264	DUO264V	-	-	-	-	-
18.4-24	0883	0883SL	DUO268	DUO268V	-	-	-	-	-
18.4-26	0883	0883SL	DUO268	DUO268V	-	570950	-	-	-
18.4-28	0884	-	DUO269	DUO269V	-	-	-	-	-
18.4-30	0885	0885SL	DUO271	DUO271V	-	570950	603901	6533MT	2933SHP
18.4-34	0887	-	DUO273	DUO273V	-	570950	603902	6545MT	2945SHP
18.4-38	0889	0889SL	DUO272	DUO272V	-	-	603909	-	-
18.4-42	0894	0894SL	DUO277	DUO277V	-	-	-	-	-
18.4-46	-	-	DUO277	DUO277V	-	-	-	-	-
19.5L-24	0883	0883SL	DUO268	DUO268V	-	-	603911	6527MT	2927SHP
19.5L-28	0876	-	DUO262	DUO262V	-	-	-	-	-
19.5L-30	0877	-	DUO266	DUO266V	-	-	-	-	-
20.5-46	-	-	DUO286	-	-	-	-	-	-
20.8-34	0890	-	DUO272	DUO272V	-	-	-	6545MT	2945SHP
20.8-38	0892	-	DUO276	-	-	-	-	-	-
20.8-42	-	-	DUO286	-	-	-	-	-	-
21L-24	0885	0885SL	DUO271	DUO271V	-	-	-	6533MT	2933SHP
21.5-16	0882	-	-	-	-	-	-	-	-
21.5L-16.1	0882	-	-	-	-	-	-	-	-
23.1-26	0891	-	DUO280	-	-	570970	-	-	-
23.1-28	-	-	DUO280	-	-	-	-	-	-
23.1-30	0893	-	DUO281	-	-	-	-	-	-
23.1-34	0895	-	DUO282	-	-	-	-	-	-
24.5-32	-	-	DUO278	-	-	-	-	-	-
40/19-19.5	-	-	DUO264	DUO264V	-	-	-	-	-
41/14-20	0858	-	DUO240	DUO240V	DUO240-7	-	602904	-	-
43/16-20	0852	-	DUO239	DUO239V	DUO239-7	570940	602907	-	-
44X18.00-20	0874	0874SL	-	-	-	-	-	-	-
260/70-16.5	1501	1501HDSL	-	-	-	-	602908	1501MT	-
320/65-18	0836	0836SL	DUO239	DUO239V	DUO239-7	-	-	-	-
335/80-18	0834	0834SL	DUO210	-	DUO210-7	570926	602909	-	-
340/80-18	0836	0836SL	-	-	-	570926	-	-	-
300/70-20	0832	0832SL	DUO214	-	DUO214-7	-	602906	-	-
360/70-20	0838	0838SL	DUO218	-	DUO218-7	570926	602904	-	-
400/70-20	0858	-	-	-	-	-	603907	-	-
320/85-20	0838	0838SL	DUO218	-	DUO218-7	-	-	-	-



TRACTOR

MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM

EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

	ROUND TWIST TRACTOR 0800	SQUARE LINK TRACTOR 0800SL	DUO GRIP H-PATTERN TRACTOR DUO200	DUO GRIP H-PATTERN V-BAR DUO200V	LIGHT WT ALLOY DUO H-PATTERN DUO200-7	TRYGG SWISS FLEXI 570000	TRYGG SMT FLEXI 602000 603000	MAXTRACK SQUARE LINK H-PATTERN 6500MT	PREMIUM STUDDED H-PATTERN 2900SHP
TIRE SIZE	Page 76	Page 76	Page 77	Page 77	Page 77	Page 78	Page 79	Page 81	Page 81
420/65-24	0859	0859SL	DUO242	DUO242V	DUO242-7	570940	603905	-	-
440/65-24	0858	-	DUO240	DUO240V	DUO240-7	570940	603905	-	-
540/65-24	0874	0874SL	-	-	-	570965	-	-	-
320/70-24	0838	0838SL	DUO226	-	DUO226-7	570926	602902	-	-
360/70-24	0852	-	DUO242	DUO242V	DUO242-7	570921	603907	-	-
380/70-24	0858	-	DUO240	DUO240V	DUO240-7	570930	603907	-	-
400/70-24	0858	-	DUO240	DUO240V	DUO240-7	-	-	-	-
420/70-24	0869	-	DUO250	DUO250V	DUO250-7	570945	603905	6515MT	2915SHP
440/70-24	0874	0874SL	DUO262	DUO262V	-	570945	603905	-	-
445/70-24	0874	0874SL	DUO262	DUO262V	-	570945	603905	-	-
460/70-24	0874	0874SL	DUO262	DUO262V	-	570945	602910	-	-
480/70-24	0874	0874SL	DUO262	DUO262V	-	570955	603911	-	-
495/70-24	0883	0883SL	DUO268	DUO268V	-	570955	603911	-	-
500/70-24	0883	0883SL	DUO268	DUO268V	-	570955	603911	-	-
400/80-24	0859	0859SL	DUO242	DUO242V	DUO242-7	570935	603905	-	-
240/85-24	0832	0832SL	DUO214	-	DUO214-7	-	602905	-	-
280/85-24	0836	0836SL	DUO226	-	DUO226-7	570926	602902	-	-
320/85-24	0852	-	DUO242	DUO242V	DUO242-7	570921	603910	-	-
340/85-24	0858	-	DUO240	DUO240V	DUO240-7	570921	603907	-	-
380/85-24	0859	0859SL	DUO242	DUO242V	DUO242-7	570935	603903	-	-
420/85-24	0874	0874SL	DUO262	DUO262V	-	570945	603906	-	-
540/65-26	0876	-	DUO262	DUO262V	-	570965	-	-	-
420/70-26	0876	-	DUO262	DUO262V	-	-	-	-	-
480/70-26	-	-	DUO262	DUO262V	-	-	-	-	-
520/70-26	0883	0883SL	DUO268	DUO268V	-	-	-	-	-
480/80-26	0883	0883SL	DUO268	DUO268V	-	570955	-	-	-
420/85-26	0876	-	DUO262	DUO262V	-	-	603906	-	-
460/85-26	0883	0883SL	DUO268	DUO268V	-	570950	-	-	-
420/65-28	0856	-	DUO218	-	DUO218-7	-	-	-	-
440/65-28	0859	0859SL	DUO242	DUO242V	DUO242-7	570945	603905	-	-
480/65-28	0869	-	DUO250	DUO250V	DUO250-7	570955	603911	-	-
540/65-28	0876	-	DUO262	DUO262V	-	570965	-	-	-
600/65-28	0877	-	DUO266	DUO266V	-	-	-	-	-
320/70-28	0838	0838SL	DUO229	-	DUO229-7	570921	-	-	-
360/70-28	0856	-	DUO218	-	DUO218-7	570921	-	-	-
380/70-28	0859	0859SL	DUO242	DUO242V	DUO242-7	570935	603903	-	-
480/70-28	0876	-	DUO262	DUO262V	-	570955	-	-	-
420/80-28	0869	-	DUO250	DUO250V	DUO250-7	-	-	-	-
440/80-28	0884	-	DUO269	DUO269V	-	-	603901	-	-
320/85-28	0856	-	DUO218	-	DUO218-7	570921	603910	-	-
340/85-28	0859	0859SL	DUO242	DUO242V	DUO242-7	570921	603903	-	-
380/85-28	0869	-	DUO250	DUO250V	DUO250-7	570935	603906	-	-
420/85-28	0876	-	DUO262	DUO262V	-	570950	603901	-	-
540/65-30	0877	-	DUO266	DUO266V	-	570970	603908	-	-
420/70-30	0876	-	DUO252	DUO252V	DUO252-7	570945	603906	-	-
480/70-30	0877	-	DUO266	DUO266V	-	570960	603908	-	-
520/70-30	0885	0885SL	DUO271	DUO271V	-	570970	603908	-	-
620/70-30	0892	-	-	-	-	-	-	-	-
620/75-30	0893	-	DUO281	-	-	-	-	-	-
380/85-30	0876	-	DUO252	DUO252V	DUO252-7	570935	603906	-	-
420/85-30	0877	-	DUO266	DUO266V	-	570950	603901	-	-
460/85-30	0885	0885SL	DUO271	DUO271V	-	570950	603901	-	-
480/85-30	-	-	-	-	-	-	-	6533MT	2933SHP
420/90-30	0877	-	DUO266	DUO266V	-	-	-	-	-

TRACTOR



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@CHAINQUEST.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

TIRE SIZE	ROUND TWIST TRACTOR 0800 Page 76	SQUARE LINK TRACTOR 0800SL Page 76	DUO GRIP H-PATTERN TRACTOR DUO200 Page 77	DUO GRIP H-PATTERN V-BAR DUO200V Page 77	LIGHT WT ALLOY DUO H-PATTERN DUO200-7 Page 77	TRYGG SWISS FLEXI 570000 Page 78	TRYGG SMT FLEXI 602000 603000 Page 79	MAXTRACK SQUARE LINK H-PATTERN 6500MT Page 81	PREMIUM STUDDED H-PATTERN 2900SHP Page 81
650/75-32	-	-	DUO278	-	-	-	-	-	-
230/90-32	-	-	DUO226	-	DUO226-7	-	-	-	-
210/95-32	0856	-	DUO240	DUO240V	DUO240-7	-	-	-	-
230/95-32	0856	-	DUO226	-	DUO226-7	-	-	-	-
540/65-34	0885	0885SL	DUO271	DUO271V	-	570970	603908	-	-
600/65-34	0887	-	DUO273	DUO273V	-	570975	603909	-	-
480/70-34	0879	-	DUO270	DUO270V	-	570960	603908	-	-
500/70-34	0879	-	DUO270	DUO270V	-	-	-	-	-
520/70-34	0887	-	DUO273	DUO273V	-	570970	603909	-	-
620/75-34	0895	-	DUO282	-	-	-	-	-	-
320/85-34	0876	-	DUO262	DUO262V	-	-	-	-	-
380/85-34	0879	-	DUO266	DUO266V	-	-	-	-	-
385/85-34	0885	0885SL	DUO271	DUO271V	-	-	-	-	-
420/85-34	0879	-	DUO270	DUO270V	-	570950	603902	-	-
460/85-34	0887	-	DUO273	DUO273V	-	570950	603902	-	-
480/85-34	0887	-	DUO273	DUO273V	-	-	-	-	-
290/95-34	0876	-	DUO262	DUO262V	-	-	-	-	-
320/95-34	0876	-	DUO262	DUO262V	-	-	-	-	-
320/85-36	0877	-	DUO266	DUO266V	-	-	603904	-	-
340/85-36	0885	0885SL	DUO271	DUO271V	-	-	603904	-	-
210/95-36	0856	-	DUO218	-	DUO218-7	-	-	-	-
270/95-36	0876	-	DUO262	DUO262V	-	-	-	-	-
540/65-38	0880	-	DUO272	DUO272V	-	570970	603909	-	-
650/65-38	0892	-	DUO276	-	-	570980	-	-	-
480/70-38	0880	-	DUO272	DUO272V	-	-	603909	-	-
580/70-38	0892	-	DUO276	-	-	570975	-	-	-
710/70-38	-	-	DUO286	-	-	-	-	-	-
380/80-38	0871	-	DUO254	-	-	-	-	-	-
480/80-38	0889	0889SL	DUO272	DUO272V	-	-	603909	-	-
320/85-38	0885	0885SL	DUO271	DUO271V	-	-	603904	-	-
340/85-38	0879	-	DUO270	DUO270V	-	-	603904	-	-
380/85-38	0879	-	DUO270	DUO270V	-	-	603901	-	-
420/85-38	0880	-	DUO272	DUO272V	-	570950	603902	-	-
460/85-38	0889	0889SL	DUO272	DUO272V	-	-	603909	-	-
520/85-38	0892	-	DUO276	-	-	-	603909	-	-
290/90-38	0862	-	DUO232	-	DUO232-7	-	-	-	-
230/95-38	-	-	DUO272	DUO272V	-	-	-	-	-
270/95-38	-	-	DUO266	DUO266V	-	-	-	-	-
230/95-40	-	-	DUO266	DUO266V	-	-	-	-	-
650/65-42	-	-	DUO286	-	-	570980	-	-	-
580/70-42	-	-	DUO286	-	-	-	-	-	-
620/70-42	-	-	DUO286	-	-	-	-	-	-
480/80-42	0894	0894SL	DUO277	DUO277V	-	-	-	-	-
520/85-42	-	-	DUO286	-	-	-	-	-	2975SHP
320/90-42	0880	-	DUO272	DUO272V	-	-	-	-	-
420/80-46	-	-	DUO256	DUO256V	-	-	-	-	-
480/80-46	0894	0894SL	DUO277	DUO277V	-	-	-	-	-
520/85-46	-	-	DUO286	-	-	-	-	-	-
380/90-46	0892	-	DUO256	DUO256V	-	-	-	-	-
230/95-48	-	-	DUO236	-	DUO236-7	-	-	-	-



TRACTOR



FIELDMASTER TRACTOR CHAIN

- ROUND TWIST & SQUARE LINK LADDER STYLE
- EXCELLENT TRACTION FOR TRACTORS AND BACKHOES
- PACKED 1/2 PAIR PER BAG

(3227 PACKED 1 PAIR PER BAG)

NOTE: We can custom build most chains if a size or part number is not listed.

RUBBER OR SHACKLE
STYLE ADJUSTERS
ARE SOLD SEPARATELY
PART #0220, #0294
OR #0296, SEE PAGE 107



ROUND TWIST
4-LINK PICTURED

SQUARE LINK
2-LINK PICTURED

⚠ NOTE: NOT INTENDED FOR LOADER/GRADER USE.

ROUND TWIST 4-LINK SPACING	WEIGHT/ PR (LBS)	ROUND TWIST 2-LINK SPACING	WEIGHT/ PR (LBS)	ROUND TWIST CROSS CHAIN	SQUARE LINK 4-LINK SPACING	WEIGHT/ PR (LBS)	SQUARE LINK 2-LINK SPACING	WEIGHT/ PR (LBS)	SQUARE LINK CROSS CHAIN	WIRE SIZE
3227	35	-	-	6253	-	-	-	-	-	7 MM
0822	72	-	-	-	-	-	-	-	-	-
0829	60	0829-2	118	6434	0829SL	60	0829SL-2	140	6434SL	-
0832	78	0832-2	156	-	0832SL	58	0832SL-2	100	-	-
0834	78	0834-2	142	-	0834SL	95	0834SL-2	183	-	-
0836	82	0836-2	142	6445	0836SL	85	0836SL-2	152	6445SL	-
0838	104	-	-	-	0838SL	85	0838SL-2	152	-	-
0846	121	-	-	-	-	-	-	-	-	-
0850	76	-	-	7420	-	-	-	-	-	-
0852	92	-	-	-	-	-	-	-	-	-
0856	102	-	-	6445	-	-	-	-	-	-
0858	108	-	-	-	-	-	-	-	-	-
0859	112	0859-2	200	7420	0859SL	110	0859SL-2	200	7420SL	10 MM
0862	124	-	-	6445	-	-	-	-	-	-
0866	146	-	-	-	-	-	-	-	-	-
0869	118	-	-	7420	-	-	-	-	-	-
0871	154	-	-	-	-	-	-	-	-	-
0874	134	0874-2	248	-	0874SL	122	-	-	-	-
0876	150	-	-	-	-	-	-	-	-	-
0877	155	-	-	7426	-	-	-	-	E6530S	-
0879	162	-	-	-	-	-	-	-	-	-
0880	168	-	-	-	-	-	-	-	-	-
0881	134	-	-	-	-	-	-	-	-	-
0882	152	-	-	-	-	-	-	-	-	-
0883	168	0883-2	315	-	0883SL	213	0883SL-2	380	-	-
0884	186	-	-	9562	-	-	-	-	E6540SH	-
0885	180	0885-2	320	-	0885SL	172	0885SL-2	326	-	-
0887	213	-	-	-	-	-	-	-	-	-
0889	220	0889-2	421	-	0889SL	220	-	-	-	-
0890	236	-	-	6650	-	-	-	-	-	-
0891	212	-	-	9567	-	-	-	-	-	-
0892	256	-	-	6650	-	-	-	-	-	-
0893	256	-	-	9567	-	-	-	-	-	-
0894	240	0894-2	455	9562	0894SL	226	0894SL-2	438	E6540SH	11 MM
0895	266	-	-	9567	-	-	-	-	-	-

TRACTOR

DUO GRIP TRACTOR CHAIN

- H-PATTERN KEEPS CHAIN CLEAR OF LUGS
- BEST TRACTION FOR TRACTORS AND BACKHOES WITH LESS SIDE SLIP
- 7 MM ALLOY FOR USE ON TRACTORS WITH LIMITED CLEARANCE AROUND FENDERS
- PACKED 1/2 PAIR PER BAG

RUBBER OR SHACKLE
STYLE ADJUSTERS
ARE SOLD SEPARATELY
PART #0220, #0294
OR #0296, SEE PAGE 107

⚠ NOTE: NOT INTENDED FOR LOADER/GRADER, SKIDDER USE.

ROUND TWIST
DUO GRIP H-PATTERN



V-BAR DUO GRIP
H-PATTERN



STOCK NUMBER	WEIGHT/ PR (LBS)	CROSS CHAIN	V-BAR STOCK NUMBER	WEIGHT/ PR (LBS)	V-BAR CROSS CHAIN	WIRE SIZE	LIGHT WT ALLOY STOCK NUMBER	WEIGHT/ PR (LBS)	LIGHT WT ALLOY CROSS CHAIN	WIRE SIZE
DUO210	103	DUO293	-	-	-	10 MM	DUO210-7	87	DUO293LW	7 MM
DUO214	104	DUO292	-	-	-		DUO214-7	88	DUO292LW	
DUO218	135	DUO293	-	-	-		DUO218-7	114	DUO293LW	
DUO224	138	DUO292	-	-	-		DUO224-7	117	DUO292LW	
DUO226	105		-	-			DUO226-7	92		
DUO229	138	DUO293	-	-	-		DUO229-7	118	DUO293LW	
DUO232	164		-	-			DUO232-7	139		
DUO236	203		-	-			DUO236-7	172		
DUO239	114	DUO295	DUO239V	124	DUO295V		DUO239-7	94	DUO295LW	
DUO240	122		DUO240V	134			DUO240-7	98		
DUO242	136	DUO294	DUO242V	150	DUO294V		DUO242-7	109	DUO294LW	
DUO246	172		DUO246V	190			DUO246-7	146		
DUO250	136	DUO295	DUO250V	150	DUO295V		DUO250-7	109	DUO295LW	
DUO252	164		DUO252V	180			DUO252-7	139		
DUO254	184	DUO296	-	-	-		-	-	-	
DUO256	222	DUO297	DUO256V	244	DUO297V		-	-	-	
DUO262	154		DUO262V	176			-	-		
DUO264	118	DUO298	DUO264V	130	DUO298V		-	-	-	
DUO266	172	DUO297	DUO266V	189	DUO297V		-	-	-	
DUO268	148	DUO298	DUO268V	168	DUO298V		-	-	-	
DUO269	178		DUO269V	195			-	-		
DUO270	180	DUO297	DUO270V	198	DUO297V		-	-	-	
DUO271	176	DUO298	DUO271V	194	DUO298V		-	-	-	
DUO272	214		DUO272V	235			-	-		
DUO273	190		DUO273V	209			-	-		
DUO276	226	DUO299	-	-	-		-	-	-	
DUO277	240	DUO298	DUO277V	290	DUO298V		-	-	-	
DUO278	258	DUO301	-	-	-		-	-	-	
DUO280	186	DUO299	-	-	-		-	-	-	
DUO281	206		-	-			-	-		
DUO282	208		-	-			-	-		
DUO286	268	DUO301	-	-	-		-	-	-	



TRYGG SWISS FLEXI



- AVAILABLE IN 8 MM AND 11.5 MM
- SUPER HARDENED WEAR BARS GIVE EXCELLENT GRIP AND ENSURE LONG SERVICE LIFE
- AGGRESSIVE AND SMOOTH RUNNING
- GREAT FOR SNOW PLOWS
- TENSIONING CHAIN AND MOUNTING INSTRUCTIONS INCLUDED



5/16"- 8 MM

STOCK NO: 570921 WEIGHT(LBS): 244	STOCK NO: 570926 WEIGHT(LBS): 205	STOCK NO: 570930 WEIGHT(LBS): 227	STOCK NO: 570940 WEIGHT(LBS): 227	STOCK NO: 570950 WEIGHT(LBS): 326	STOCK NO: 570955 WEIGHT(LBS): 319	STOCK NO: 570965 WEIGHT(LBS): 236	STOCK NO: 570975 WEIGHT(LBS): 285	
11.2-28	11.2-20	14.9-20	420/65-20	16.9-28	480/65-24	520/60-28	580/70-38	
12.4-24	11.2-24	380/70-20	440/65-24	16.9-30	480/65-28	540/65-26	600/55-38	
12.4-28	12.4-20	380/70-24	455/70-20	16.9-34	480/70-24	STOCK NO: 570970 WEIGHT(LBS): 370	600/60-34	
13.6-24	12.5-18	405/70-24	460/65-24	16.9-38	480/70-28		600/60-38	
13.6-28	13.6-16	STOCK NO: 570935 WEIGHT(LBS): 264	STOCK NO: 570945 WEIGHT(LBS): 266	18.4-26	495/70-24		600/65-30	
280/85-28	14/80-20			18.4-30	500/70-24		600/65-34	
320/70-28	320/70-20			18.4-34	STOCK NO: 570960 WEIGHT(LBS): 328	520/70-30 520/70-34 540/65-30 540/65-34 540/65-38 540/70-30	600/65-38	
320/85-24	320/70-24			420/70-34			600/70-30	
320/85-28	320/80-18			420/85-28			600/70-34	
340/85-24	320/85-20			420/85-30			STOCK NO: 570980 WEIGHT(LBS): 473	
360/70-24	340/75-20	14.9-24	16.9-24	480/70-30 480/70-34				
360/70-28	355/80-20	14.9-26	420/70-28					
365/85-20	360/70-20	14.9-28	420/70-30					
	360/80-20	14.9-30	420/85-24	440/80-30			650/60-34	
		380/70-28		440/80-34			650/60-38	
		380/85-24		460/85-30			650/65-34	
		380/85-28		460/85-34			650/65-38	
		380/85-30						

TRYGG SMT COMBO



- OVERSIZED STUDS INCREASE GRIP AND LAST LONGER
- SMT PATTERN HOLDS THE CHAIN ON TOP OF THE TIRE LUGS, KEEPING THE STUDS IN CONSTANT CONTACT WITH THE TERRAIN
- SMT COMBO FITS MORE THAN ONE TIRE SIZE
- GREAT FOR USE WITH SNOW CLEARING, TRACTORS, FORESTRY AND CONSTRUCTION VEHICLES

TIRE SIZE	STOCK NUMBER	INCHES	MM	WEIGHT/ PR (LBS)
18.4-30; 16.9-30; 16.9-34	606552	1/2"	13	442
23.1-34; 20.8-38	608968	5/8"	16	860



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
 EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

TRYGG SMT FLEXI



- A PERFECT FIT WITHOUT THE USE OF TOOLS
- SMT FLEXI USES STEEL ENHANCED WITH BORON, NICKEL, CHROMIUM AND MANGANESE; FULLY HARDENED FOR MAXIMUM DURABILITY
- HARDENED 10 MM HOOKS AND 8 MM SIDE CHAIN ARE STANDARD ON BOTH SIDES
- OPTIONAL TIGHTENING RAIL AVAILABLE, PART #336030



5/16"- 8 MM

3/8"- 9.5 MM

STOCK NO: 602901 WEIGHT(LBS): 167	STOCK NO: 602904 WEIGHT(LBS): 143	STOCK NO: 602908 WEIGHT(LBS): 106	STOCK NO: 603901 WEIGHT(LBS): 262	STOCK NO: 603904 WEIGHT(LBS): 235	STOCK NO: 603907 WEIGHT(LBS): 183
12.4-28 12.4-32 13.6-28	12.4-20 12.5-20 13.6-16 14/80-20 320/70-24 340/75-20 360/70-20 365/80-20	10.0/75-15.3 260/70-16.5 10-16.5 12-16.5	14.9-38 15.5-38 16.9-28 16.9-30 16.9-34 18.4-26 420/85-28 420/85-30 460/85-30	12.4-36 12.4-38 13.6-36 13.6-38	13.6-24 14.9-20 340/85-24 360/70-24 380/70-24
STOCK NO: 602902 WEIGHT(LBS): 147	STOCK NO: 602905 WEIGHT(LBS): 130	STOCK NO: 602909 WEIGHT(LBS): 123	STOCK NO: 603902 WEIGHT(LBS): 282	STOCK NO: 603905 WEIGHT(LBS): 207	STOCK NO: 603908 WEIGHT(LBS): 273
11.2-24 11.2-28 12.4-24 280/85-24 320/70-24 320/85-24	8.25-20 8.3-24 9.5-20 9.5-24	12.5-18 15.0/55-17 15.5/55-18 335/80-18 365/70-18	16.9-38 18.4-30 18.4-34 420/85-34 460/85-30 460/85-34 480/70-34 480/70-38	16.0/70-24 405/70-24 440/65-24 455/70-20	480/70-30 480/70-34 520/70-30 540/65-30 540/65-34
STOCK NO: 602903 WEIGHT(LBS): 165	STOCK NO: 602906 WEIGHT(LBS): 130	STOCK NO: 602910 WEIGHT(LBS): 187	STOCK NO: 603903 WEIGHT(LBS): 216	STOCK NO: 603906 WEIGHT(LBS): 222	STOCK NO: 603909 WEIGHT(LBS): 317
13.6-24 14.9-24 360/70-24 380/70-24 380/85-24 400/60-26.5 400/80-24 425/75-20	10.5-20 11.2-20 12.5/80-18 12.5/80-20 260/80-20 300/70-20	420/70-24 460/70-24 445/70-24 405/70-24 440/65-24 16.0/70-24	13.6-28 14.9-26 380/70-28 380/85-24 380/85-28	14.9-28 14.9-30 16.9-24 16.9-26 380/85-28 380/85-30 420/70-28 420/70-30 420/85-24	18.4-38 460/85-30 460/85-38 480/70-38 520/70-34 520/70-38 540/65-38 600/65-34
	STOCK NO: 602907 WEIGHT(LBS): 156	STOCK NO: 602911 WEIGHT(LBS): 202			STOCK NO: 603910 WEIGHT(LBS): 194
	360/70-20 380/70-20	19.5L-24 480/65-28 480/70-24 495/70-24 480/65-24			12.4-24 12.4-28 13.6-24 320/85-24
				STOCK NO: 603911 WEIGHT(LBS): 233	
				480/65-24 480/65-28 480/70-24 495/70-24	


OPTIONAL TIGHTENING RAIL PART # 336030



RUBBER OR SHACKLE
STYLE ADJUSTERS
ARE SOLD SEPARATELY
PART #0220, #0294
OR #0296, SEE PAGE 107



**SMT FLEXI LINK
PART # 335508**



TRACTOR

TRYGG FAST TRAC



- RECTANGULAR STUDS PROVIDE 30% LARGER GRIP-AREA
- THE PROFESSIONAL CHOICE FOR SNOW CLEARING
- CHAIN "ROLLS" EASILY AND MEETS THE ROAD AS SMOOTH AS POSSIBLE
- WORKS WELL WITH LIMITED SPACE UNDER THE FENDERS
- REMOVABLE TAIL SECTION AND SIDE CHAIN LINKS FOR EASY ADJUSTMENT

5/16"- 8 MM

STOCK NO: 581020	STOCK NO: 581025	STOCK NO: 581030	STOCK NO: 581035	STOCK NO: 581040
WEIGHT(LBS): 187	WEIGHT(LBS): 170	WEIGHT(LBS): 146	WEIGHT(LBS): 139	WEIGHT(LBS): 103
14.9-28	18.4-26	13.00-24	11.2-24	11.2-16
14.9-30	14.00-24/25	14.9-20	11.2-28	12.4-16
14.9-38	17.5-25 STD	14.9-24	12.00-24	13.6-16
15.5-38	480/60-28	15.5-25	12.4-20	325/95-24
16.00-24/25	480/65-24	43x16x20	12.4-24	320/85-24
16.9-24	480/65-28	340/85-28	12.4-28	320/85-28
16.9-26	480/70-24	360/70-24	13.6-24	340/80-24
16.9-28	480/70-28	360/70-28	13.6-28	
16.9-30	495/70-25	360/80-24	280/85-28	
16.9-34	500/60-26.5	365/80-20	300/70-24	
17.5-25 L5	500/65-26.5	365/85-20	320/70-24	
18.4-26	500/65-28	375/75-20	320/70-28	
20.5-25	520/60-28	380/70-20	320/85-24	
380/85-28	520/65-24	380/70-24	320/85-28	
380/85-30	520/65-28	380/70-28	325/95-24	
385/95-25	525/65-20.5	380/85-24	340/80-24	
400/80-28	540/65-24	395/80-20	340/85-24	
420/70-30	540/65-28	400/65-24	360/70-20	
420/70-34		400/80-24	360/80-20	
420/85-28		405/70-18		
420/85-30		405/70-20		
420/85-34		405/70-24		
440/80-24		420/65-20		
440/80-28		420/65-24		
440/80-30		420/70-24		
440/80-34		420/85-24		
460/65-24		440/65-24		
480/65-28		440/65-28		
480/70-28				
525/80-25				



TRYGG

RUBBER OR SHACKLE
STYLE ADJUSTERS
ARE SOLD SEPARATELY
PART #0220, #0294
OR #0296, SEE PAGE 107

SQUARE STUDS CLOSE UP



**SIDE CHAIN
ADJUSTMENT
LINKS**

MAXTRACK H-PATTERN

- H-PATTERN STYLE ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- SQUARE LINK WITH LINK-OVER-LINK DESIGN FOR BETTER TRACTION
- FOR TRACTORS, BACKHOES, PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.

FOR 8 MM USE:

**RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0216
SEE PAGE 107**

FOR 10 MM & UP USE:

**RUBBER OR SHACKLE
STYLE ADJUSTERS
ARE SOLD SEPARATELY
PART #0220, #0294
OR #0296, SEE PAGE 107**

**NOTE: 1500MT SERIES ARE A SQUARE LINK H-PATTERN DESIGN.
LINK-OVER-LINK ONLY AVAILABLE ON 6500MT SERIES.**

5/16" - 8 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN
10x16.5	1501MT	75	8914
12x16.5	1502MT	82	8918
14x17.5	1503MT	99	



6500MT SERIES PICTURED



LINK-OVER-LINK CLOSE-UP

3/8" - 10 MM

7/16" - 11 MM

17/32" - 13.5 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN
13.6-28; 420/70-24	6512MT-10	202	8901	6515MT-11	296	8903	-	-	-
17.5L-24; 16.9-24; 16.9-28	6515MT-10	214	8902				-	-	-
19.5L-24	6527MT-10	236		6527MT-11	356	8904	-	-	-
18.4-30; 21L-24; 480/85-30	-	-	-	6533MT-11	346	8906	6533MT-13	442	8908
18.4-34; 20.8-34	-	-	-	6545MT-11	384		6545MT-13	512	8909

NORDIC™ STUDDED H-PATTERN

- **PREMIUM** ALLOY STEEL CONSTRUCTION FOR MAXIMUM LIFE
- STUDDED LINK WITH EXTRA HARD STUD TIPS
- EXCELLENT TRACTION IN EXTREME CONDITIONS
- H-PATTERN DESIGN PROVIDES SMOOTHER RIDE
- FOR TRACTORS, BACKHOES, PLOWS, GRADERS, FORKLIFTS, SCRAPERS, LOADERS, ETC.



**RUBBER OR SHACKLE
STYLE ADJUSTERS
ARE SOLD SEPARATELY
PART #0220, #0294
OR #0296, SEE PAGE 107**



3/8" - 10 MM

7/16" - 11 MM

17/32" - 13.5 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN	STOCK NUMBER	WT/ PR (LBS)	CROSS CHAIN
13.6-28; 420/70-24	2912SHP-10	231	8501	2915SHP-11	278	8503	-	-	-
17.5L-24; 16.9-24; 16.9-28	2915SHP-10	235	8502				-	-	-
19.5L-24	2927SHP-10	258		2927SHP-11	281	8504	-	-	-
18.4-30; 21L-24; 480/85-30	-	-	-	2933SHP-11	406	8505	2933SHP-13	400	8508
18.4-34; 20.8-34	-	-	-	2945SHP-11	476	8506	2945SHP-13	554	
520/85-42	-	-	-	-	-	-	2975SHP-13	701	8511



TRACTOR

GARDEN TRACTOR & SNOW BLOWER



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.

NOTE: We can custom build most chains if a size or part number is not listed in this fitment chart. Call or visit www.qualitychaincorp.com for more info.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

TIRE SIZE	SNOW BLOWER GARDEN TRACTOR 1300	H-PATTERN SNOW BLOWER HP1300
	Page 83	Page 83
3.40x3.00-5	1309	-
4-8	1301	-
4.10x3.50-4	1309	-
4.10x3.50-5	1317	-
4.10x3.50-6	1317	-
4.80-8	1301	-
5-8	1322	-
5.70-8	1322	-
5.90-15	1303	HP1303
6-12	1311	HP1311
6-16	1307	HP1307
7-12	1304	HP1304
7-16	1307	HP1307
7.2-16	1307	HP1307
8-12	1304	HP1304
8-15	1307	HP1307
8-16	1325	HP1325
10-3	1306	-
10-2.75	1306	-
10.25-3.25	1306	-
10.5-2.75	1306	-
12-3	1317	-
12x3.50-6	1317	-
12x4-6	1317	-

TIRE SIZE	SNOW BLOWER GARDEN TRACTOR 1300	H-PATTERN SNOW BLOWER HP1300
	Page 83	Page 83
12x7-4	1321	-
12-12	1318	HP1318
12.25x3.50-6	1317	-
12.5x4.50-6	1321	-
13x4-5	1321	-
13x4-6	1321	-
13x5-6	1321	-
13x5-7	1321	-
13x5-8	1321	-
13x6.50-6	1301	-
14x4-6	1301	-
15x5-6	1314	-
15x6-6	1314	-
16x6.50-8	1308	HP1308
18x6.50-8	1312	HP1312
18x8.50-8	1326	HP1326
18x8.50-10	1326	HP1326
18x9.50-8	1323	HP1323
20x8-8	1308	HP1308
20x8-10	1308	HP1308
20x10-8	1302	HP1302
20x10-10	1302	HP1302
22x7-12	1304	HP1304
22x9.50-12	1303	HP1303

TIRE SIZE	SNOW BLOWER GARDEN TRACTOR 1300	H-PATTERN SNOW BLOWER HP1300
	Page 83	Page 83
22x9.50-15	1303	HP1303
22x10-8	1308	HP1308
22x10-10	1308	HP1308
23x7.50-12	1311	HP1311
23x8.50-12	1304	HP1304
23x8.50-14	1304	HP1304
23x9.50-12	1303	HP1303
23x10.50-12	1303	HP1303
24x8.50-14	1303	HP1303
24x12-12	1318	HP1318
25x8.50-14	1307	HP1307
25x8.50-15	1307	HP1307
26x12-12	1318	HP1318
27x8.50-14	1307	HP1307
27x8.50-15	1307	HP1307
27x12-12	1318	HP1318
28x8.50-15	1307	HP1307
29x12-15	1325	HP1325
33x12.50-15	1325	HP1325
215/50-10	1326	HP1326
280/70-16	1325	HP1325
305/60-12	1318	HP1318

GARDEN TRACTOR & SNOW BLOWER CHAIN

- CHAINS DESIGNED FOR SNOW BLOWERS & GARDEN TRACTORS
- 2-LINK SPACING LADDER STYLE OR H-PATTERN FOR BETTER TIRE COVERAGE, A SMOOTHER RIDE AND INCREASED TRACTION
- PACKED 1 PAIR PER BAG

STOCK NUMBER	WEIGHT/ PR (LBS)	OVERALL LENGTH (INCHES)	X-CHAIN WIDTH (INCHES)	X-CHAIN PER 1/2 PAIR	WIRE DIAMETER (MM)	H-PATTERN STOCK NUMBER	WEIGHT/ PR (LBS)	OVERALL LENGTH (INCHES)	PATTERN WIDTH (INCHES)	PATTERNS PER 1/2 PAIR	WIRE DIAMETER (MM)
1301	8	37.5"	8.76"	13	5.2 MM	-	-	-	-	-	-
1302	15	46.7"	14.78"	16	5.2 MM	HP1302	26	46.7"	14.78"	7	5.5 MM
1303	15	57"	14.28"	20	5.2 MM	HP1303	26	57"	14.28"	10	5.5 MM
1304	24	65.5"	12.02"	22	5.2 MM	HP1304	35	65.5"	12.02"	11	5.5 MM
1306	5	22.2"	5.48"	9	4 MM	-	-	-	-	-	-
1307	27	77"	12.74"	27	5.2 MM	HP1307	44	77"	12.74"	13	5.5 MM
1308	19	50.5"	12.02"	17	5.2 MM	HP1308	36	50.5"	12.02"	8	5.5 MM
1309	4	24.4"	6.06"	10	4 MM	-	-	-	-	-	-
1311	15	57.5"	11.1"	20	5.2 MM	HP1311	28	57.5"	11.1"	9	5.5 MM
1312	10	44.1"	11.52"	14	5.2 MM	HP1312	21	44.1"	11.52"	7	5.5 MM
1314	10	38.8"	10.18"	13	5.2 MM	-	-	-	-	-	-
1317	5	31.1"	6.06"	13	4 MM	-	-	-	-	-	-
1318	29	64.8"	16.62"	22	5.2 MM	HP1318	40	64.8"	16.62"	10	5.5 MM
1321	8	33"	9.64"	11	4.5 MM	-	-	-	-	-	-
1322	15	46.7"	10.18"	15	5.2 MM	-	-	-	-	-	-
1323	11	37.6"	14.78"	13	5.2 MM	HP1323	23	37.6"	14.78"	6	5.5 MM
1325	41	79"	20.36"	20	8 MM	HP1325	52	86.5"	17.5"	11	8 MM
1326	10	38.9"	12.94"	13	5.2 MM	HP1326	21	38.9"	12.94"	6	5.5 MM

**New Specs
& Fitments!**



**RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0213, #0217
SEE PAGE 107**



GARDEN TRACTOR /
SNOW BLOWER

FORKLIFT



PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

	ROUND TWIST 2-LINK 1400-2	SQUARE LINK 2-LINK 1400-2SL	FORKLIFT CABLE 1400
TIRE SIZE	Page 85	Page 85	Page 85
250x15	1408-2	1408-2SL	1400-15
300x15	1409-2	1409-2SL	-
6.00x9	1401-2	1401-2SL	-
6.50x10	1401-2	1401-2SL	1400-12
7x14	1401-2	1401-2SL	-
7.00x12	1403-2	1403-2SL	1400-12
7.00x15	1404-2	1404-2SL	1400-15
7.50x15	1405-2	1405-2SL	1400-15
7.50x16	1409-2	1409-2SL	1400-15
8.15x15	1407-2	1407-2SL	1400-15
8.25x15	1405-2	1405-2SL	1400-15
20x15	1405-2	1405-2SL	1400-15
21x7x15	1401-2	1401-2SL	1400-12
21x8x9	1401-2	1401-2SL	1400-12
21x8x15	1401-2	1401-2SL	1400-12
23x10x12	1407-2	1407-2SL	1400-15
28x8x15	1404-2	1404-2SL	1400-15
28x9x15	1403-2	1403-2SL	1400-12
28x12x15	1409-2	1409-2SL	1400-15
28x12.50-15	1409-2	1409-2SL	1400-15
29x8x15	1403-2	1403-2SL	1400-12
30x8x15	1409-2	1409-2SL	1400-15
180/85-12	1403-2	1403-2SL	1400-12



INDUSTRIAL FORKLIFT TIRE CHAIN

- ROUND TWIST LADDER STYLE CHAIN DESIGNED FOR FORKLIFTS
- 2-LINK SPACING OFFERS BETTER TIRE COVERAGE, A SMOOTHER RIDE AND INCREASED TRACTION



2-LINK SPACING



2-LINK SPACING

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	WIRE SIZE
6.5x10; 21x8x9; 21x7x15; 21x8x15	1401-2	33	6250	7 MM
7.00x12; 28x9x15; 29x8x15; 180/85-12	1403-2	49	6255	8 MM
7.00x15; 28x8x15	1404-2	53	6256	
7.50x15; 8.25x15; 20x15	1405-2	66		
8.15x15; 23x10x12	1407-2	58	6260	
250x15	1408-2	79	6256	
7.50x16; 28x12x15; 30x8x15; 300x15	1409-2	59	6254	7 MM

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0216
SEE PAGE 107

SQUARE LINK ALLOY FORKLIFT TIRE CHAIN

- SQUARE LINK LADDER STYLE CHAIN DESIGNED FOR FORKLIFTS
- ALLOY STEEL FOR LONGER LIFE
- 2-LINK SPACING OFFERS BETTER TIRE COVERAGE, A SMOOTHER RIDE AND INCREASED TRACTION



2-LINK SPACING



2-LINK SPACING

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	WIRE SIZE
6.5x10; 21x8x9; 21x7x15; 21x8x15	1401-2SL	57	6251SL	7 MM
7.00x12; 28x9x15; 29x8x15; 180/85-12	1403-2SL	60	6255SL	8 MM
7.00x15; 28x8x15	1404-2SL	56	6260SL	
7.50x15; 8.25x15; 20x15	1405-2SL	71		
8.15x15; 23x10x12	1407-2SL	82		
250x15	1408-2SL	78		
7.50x16; 28x12x15; 30x8x15; 300x15	1409-2SL	65	6253SL	7 MM

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0216
SEE PAGE 107

UNIVERSAL LIMITED CLEARANCE FORKLIFT CABLE

- CABLE CHAIN FOR FORKLIFTS THAT HAVE LIMITED CLEARANCE
- AVAILABLE IN TWO WIDTHS (12" & 15")
- CUT THE LENGTH TO CUSTOM FIT YOUR TIRE
- TWICE THE NUMBER OF CROSS CABLES FOR BETTER COVERAGE AND A SMOOTHER RIDE

RUBBER ADJUSTERS AND 8" CABLE CUTTER INCLUDED.
1 PAIR PER BAG



TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	WIDTH (INCHES)	CROSS CHAIN	LENGTH (INCHES)	CAN SHORTEN TO (INCHES)
6.5x10; 7.00x12; 21x8x9; 28x9x15; 29x8x15; 21x8x15; 180/85-12	1400-12	19	12"	8860	84"	44"
250x15; 7.00x15; 7.50x15; 7.50x16; 8.15x15; 8.25x15; 20x15	1400-15	27	15"	8862	96"	51"
23x10x12; 28x8x15; 30x8x15						

SKID STEER

PLEASE NOTE: This is a guide only. Actual fitments and clearances may vary. Please check prior to use.



Quality Chain Corp. suggests that you check your vehicle's owner's manual for information about the use of tire chains.

	ROUND TWIST SKID STEER 1500-2	SQUARE LINK SKID STEER 1500HDSL-2	STUDED SKID STEER 1500STUDED-2	TRYGG SMT 602900	TRYGG SAFETY GRIP 513100
TIRE SIZE	Page 87	Page 87	Page 88	Page 88	Page 89
10x16.5	1501-2	1501HDSL-2	1501STUDED-2	602908	513179
12x16.5	1502-2	1502HDSL-2	1502STUDED-2	602908	513179
12.0-18	1503-2	1503HDSL-2	1503STUDED-2	602909	-
12.5/70-16	1502-2	1502HDSL-2	1502STUDED-2	-	-
15-19.5	1504-2	1504HDSL-2	1504STUDED-2	-	513388
14x17.5	1503-2	1503HDSL-2	1503STUDED-2	-	513387
18/625	1504-2	1504HDSL-2	1504STUDED-2	-	-
27x10.50-15	1500-2	1500HDSL-2	1500STUDED-2	-	-
31x5x9	1501-2	1501HDSL-2	1501STUDED-2	-	-
31x6x10	1501-2	1501HDSL-2	1501STUDED-2	-	-
31/10-20	1501-2	1501HDSL-2	1501STUDED-2	-	-
31x12.50-16.5	1502-2	1502HDSL-2	1502STUDED-2	-	-
31x13-16.5	1502-2	1502HDSL-2	1502STUDED-2	-	513179
31x15.5-15	1502-2	1502HDSL-2	1502STUDED-2	602909	513305
33x6x10	1502-2	1502HDSL-2	1502STUDED-2	-	-
33x6x11	1502-2	1502HDSL-2	1502STUDED-2	-	-
33x7x11	1503-2	1503HDSL-2	1503STUDED-2	-	-
33/12-20	1502-2	1502HDSL-2	1502STUDED-2	-	-
33x15.5-16.5	1503-2	1503HDSL-2	1503STUDED-2	-	513305
36x13.5-15	1502-2	1502HDSL-2	1502STUDED-2	-	513305
36/14-20	1503-2	1503HDSL-2	1503STUDED-2	-	513305
39x15-22.5	1507-2	1507HDSL-2	1507STUDED-2	-	-
260/70-16.5	1501-2	1501HDSL-2	1501STUDED-2	602908	513179
300/75-15	1502-2	1502HDSL-2	1502STUDED-2	-	-
305/70-16.5	1502-2	1502HDSL-2	1502STUDED-2	-	-
315/55-20	1502-2	1502HDSL-2	1502STUDED-2	-	-
355/55D625	1507-2	1507HDSL-2	1507STUDED-2	-	-
355/70-17.5	1503-2	1503HDSL-2	1503STUDED-2	-	-
360/85-20	2615-2	6515-2	2915-2	-	-
370/75-28	1508-2	1508HDSL-2	1508STUDED-2	-	-
385/65-19.5	1504-2	1504HDSL-2	1504STUDED-2	-	-
400/75-28	1509-2	1509HDSL-2	1509STUDED-2	-	-
405/70-18	1504-2	1504HDSL-2	1504STUDED-2	-	513396
405/70-20	1504-2	1504HDSL-2	1504STUDED-2	-	513396
445/50D710	2615-2	6515-2	2915-2	-	-

SKID STEER, TELEHANDLER & MAN LIFT TIRE CHAIN

- ROUND TWIST LADDER STYLE CHAIN DESIGNED FOR INDUSTRIAL EQUIPMENT
- 2-LINK SPACING FOR BETTER TIRE COVERAGE AND A SMOOTHER RIDE



2-LINK SPACING



4-LINK SPACING

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	WIRE SIZE
27x10.50-15	1500-2	65	1500	43	6260	8 MM
10x16.5; 31/10-20; 31x6x10; 31x5x9; 260/70-16.5	1501-2	75	1501	43		
12x16.5; 31x15.5-15; 31x13-16.5; 36x13.5-15; 305/70-16.5	1502-2	83	1502	54		
33/12-20; 33x6x11; 33x6x10						
14x17.5; 36/14-20; 33x7x11; 33x15.5-16.5; 355/70-17.5	1503-2	92	1503	56	6268	
355/55D625	1507-2	99	1507	64		
370/75-28	1508-2	112	1508	90		
405/70-20	1504-2	72	1504	60	7215	
400/75-28	1509-2	114	1509	91		

SQUARE LINK ALLOY SKID STEER TIRE CHAIN

- SQUARE LINK LADDER STYLE CHAIN DESIGNED FOR INDUSTRIAL EQUIPMENT
- ALLOY STEEL LINKS FOR LONGER LIFE
- 2-LINK SPACING FOR BETTER COVERAGE, A SMOOTHER RIDE & INCREASED TRACTION
- AVAILABLE IN SQUARE LINK H-PATTERN, REPLACE "HDSL" WITH "MT" (SEE PAGE 81)

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0216
SEE PAGE 107



2-LINK SPACING



4-LINK SPACING

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	WIRE SIZE
27x10.50-15	1500HDSL-2	77	1500HDSL	50	6260SL	8 MM
10x16.5; 31/10-20; 31x6x10; 31x5x9; 260/70-16.5	1501HDSL-2	83	1501HDSL	53	6263SL	
12x16.5; 31x15.5-15; 31x13-16.5; 36x13.5-15; 305/70-16.5	1502HDSL-2	90	1502HDSL	62		
33/12-20; 33x6x11; 33x6x10						
14x17.5; 36/14-20; 33x7x11; 33x15.5-16.5; 355/70-17.5	1503HDSL-2	108	1503HDSL	66	6268SL	
355/55D625	1507HDSL-2	103	1507HDSL	70		
370/75-28	1508HDSL-2	120	1508HDSL	97		
405/70-20	1504HDSL-2	116	1504HDSL	74	7215SL	
400/75-28	1509HDSL-2	123	1509HDSL	99		



NORDIC™ STUDDED SKID STEER TIRE CHAIN

- STUDDED LINKS FOR EXTREME TRACTION IN OFF-ROAD APPLICATIONS
- ALLOY STEEL LINKS FOR LONGER LIFE
- 2-LINK SPACING FOR BETTER TIRE COVERAGE, A SMOOTHER RIDE AND INCREASED TRACTION



2-LINK SPACING

4-LINK SPACING

TIRE SIZE	STOCK NUMBER	WEIGHT / PR (LBS)	STOCK NUMBER	WEIGHT / PR (LBS)	CROSS CHAIN	WIRE SIZE
27x10.50-15	1500STUDDDED-2	92	1500STUDDDED	66	6923N	8 MM
10x16.5; 31/10-20; 31x6x10; 31x5x9; 260/70-16.5	1501STUDDDED-2	97	1501STUDDDED	61		
12x16.5; 31x15.5-15; 31x13-16.5; 36x13.5-15	1502STUDDDED-2	121	1502STUDDDED	74		
305/70-16.5; 33/12-20; 33x6x11; 33x6x10						
14x17.5; 36/14-20; 33x7x11; 33x15.5-16.5; 355/70-17.5	1503STUDDDED-2	108	1503STUDDDED	66	6926N	
355/55D625	1507STUDDDED-2	118	1507STUDDDED	80		
370/75-28	1508STUDDDED-2	171	1508STUDDDED	107		
405/70-20	1504STUDDDED-2	112	1504STUDDDED	70	7915	
400/75-28	1509STUDDDED-2	174	1509STUDDDED	110		

TRYGG SMT SKID STEER TIRE CHAIN

- STUDDED LINKS FOR EXTREME TRACTION IN OFF-ROAD APPLICATIONS
- EASY ADJUSTMENTS WITHOUT THE NEED FOR TOOLS
- CAN BE CUSTOM FIT TO YOUR TIRE WHETHER BRAND NEW OR WORN DOWN.

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0216
SEE PAGE 107

STOCK NO: 602908	STOCK NO: 602909
WEIGHT(LBS): 104	WEIGHT(LBS): 104
10-16.5	12.0-18
12-16.5	31X15.5-15
260/70-16.5	



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@QUALITYCHAINCORP.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

TRYGG SAFETY GRIP SKID STEER TIRE CHAIN

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0216
SEE PAGE 107

- TRYGG SAFETY GRIP 7MM IS A VERSATILE LIGHT WEIGHT CHAIN SUITABLE FOR ALL OPERATIONS
- PERFECT FOR ON ROAD SERVICE AND YARD WORK
- LIGHT WEIGHT, WHICH MAKES FREQUENT MOUNTING AND DISMOUNTING EASIER
- SUITED FOR DRIVING ON CHANGING ROAD CONDITIONS
- WEAR-BARS ON EVERY OTHER LINK TO INCREASE GRIP AND PROLONG THE LIFE OF THE CHAIN
- HARD SPINNING MAY DAMAGE THE CHAIN

**TRYGG SAFETY GRIP 7MM IS MADE TO FIT SEVERAL DIFFERENT TIRE SIZES.
IT IS NORMAL FOR THE USER TO HAVE TO CUT THE CHAIN TO GET A PROPER FIT**

9/32"- 7 MM

STOCK NO: 513179 WEIGHT(LBS): 66	STOCK NO: 513305 WEIGHT(LBS): 57	STOCK NO: 513387 WEIGHT(LBS): 92.5	STOCK NO: 513388 WEIGHT(LBS): 75	STOCK NO: 513396 WEIGHT(LBS): 75
10-16.5 12-16.5 33X13-16.5 260/70-16.5	31X15.5-15 33X15.5-16.5 36X13.5-15 36/14-20	14-17.5	15-19.5	405/70-18 405/70-20



MADE IN
NORWAY



TRYGG



SKID STEER



ATV / UTV

ATV / UTV



TRYGG PREMIUM ATV

- OVERSIZED STUDS PENETRATE ICE AND FROZEN GROUND TO PUSH THROUGH SNOW AND MUD
- FULL FLOATING DIAMOND PATTERN PROTECTS AGAINST TIRE WEAR



PACKED 1 PAIR PER BAG

TIRE SIZE	STOCK NUMBER	TIRE SIZE	STOCK NUMBER	TIRE SIZE	STOCK NUMBER
22x10x10	425220	24x12x12	425240	26x8x12	425225
22x11x8	425220	25x8x12	425230	26x8x14	425225
23x8.5x12	425220	25x10x10	425230	26x10x12	425250
23x10x10	425220	25x10x12	425230	26x10x14	425250
23x10x12	425220	25x10.5x12	425230	26x10.5x12	425250
24x9x10	425220	25x11x10	425240	26x11x12	425250
24x9x11	425220	25x11x12	425240	26x12x12	425250
24x9x12	425220	25x12x9	425240	27x9x12	425250
24x10x11	425230	25x12x10	425240	27x9x14	425250
24x11x10	425230	25x12.5x10	425250	27x12x12	425250
24x11.5x10	425230	25x12.5x12	425250	28x12x12	425255



0213

0217

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0213, #0217
SEE PAGE 107



ATV & UTV CHAIN

V-BAR

- LADDER STYLE WITH ICE BREAKERS
- 2-LINK AND 4-LINK SPACING

U-GRIP

- DIAMOND PATTERN WITH U-GRIP STUDS
- SMOOTH GRIP, MAXIMUM TRACTION

PACKED 1 PAIR PER BAG

RUBBER ADJUSTERS
ARE SOLD SEPARATELY
PART #0213, #0217
SEE PAGE 107



0213



0217

4-LINK V-BAR



2-LINK V-BAR



U-GRIP



TIRE SIZE	V-BAR LADDER 4-LINK SPACING	V-BAR LADDER 2-LINK SPACING	U-GRIP DIAMOND PATTERN	TIRE SIZE	V-BAR LADDER 4-LINK SPACING	V-BAR LADDER 2-LINK SPACING	U-GRIP DIAMOND PATTERN
20x10x9	ATV-A	ATV-A-2	ATV-DBA	25x10x11	ATV-C	ATV-C-2	ATV-DBD
20x11x9	ATV-A	ATV-A-2	ATV-DBA	25x10x12	ATV-C	ATV-C-2	ATV-DBD
21x9x12	ATV-A	ATV-A-2	ATV-DBA	25x10.5x12	ATV-C	ATV-C-2	ATV-DBD
21x10x8	ATV-A	ATV-A-2	ATV-DBA	25x11x9	ATV-C	ATV-C-2	ATV-DBD
22x7x10	ATV-A	ATV-A-2	ATV-DBA	25x11x10	ATV-C	ATV-C-2	ATV-DBD
22x7x11	ATV-A	ATV-A-2	ATV-DBA	25x11x12	ATV-C	ATV-C-2	ATV-DBD
22x9x8	ATV-A	ATV-A-2	ATV-DBA	25x12x9	ATV-C	ATV-C-2	ATV-DBC
22x9x10	ATV-A	ATV-A-2	ATV-DBA	25x12x10	ATV-C	ATV-C-2	ATV-DBC
22x9x11	ATV-A	ATV-A-2	ATV-DBA	25x12x12	ATV-C	ATV-C-2	ATV-DBC
22x10x8	ATV-A	ATV-A-2	ATV-DBA	25x12.5x10	ATV-D	ATV-D-2	ATV-DBC
22x10x9	ATV-A	ATV-A-2	ATV-DBA	25x12.5x12	ATV-D	ATV-D-2	ATV-DBC
22x10x10	ATV-A	ATV-A-2	ATV-DBA	26x8x12	ATV-B	ATV-B-2	ATV-DBB
22x11x8	ATV-A	ATV-A-2	ATV-DBA	26x8x14	ATV-B	ATV-B-2	ATV-DBE
22x11x9	ATV-A	ATV-A-2	ATV-DBA	26x9x12	ATV-C	ATV-C-2	ATV-DBD
23x8x10	ATV-A	ATV-A-2	ATV-DBA	26x9x14	ATV-C	ATV-C-2	ATV-DBD
23x8x11	ATV-A	ATV-A-2	ATV-DBA	26x10x12	ATV-C	ATV-C-2	ATV-DBD
23x8x12	ATV-A	ATV-A-2	ATV-DBA	26x10x14	ATV-C	ATV-C-2	ATV-DBD
23x8.5x12	ATV-A	ATV-A-2	ATV-DBA	26x10.5x12	ATV-C	ATV-C-2	ATV-DBD
23x10x10	ATV-A	ATV-A-2	ATV-DBA	26x11x12	ATV-D	ATV-D-2	ATV-DBC
23x10x12	ATV-A	ATV-A-2	ATV-DBA	26x11x14	ATV-D	ATV-D-2	ATV-DBC
23x10.5x12	ATV-A	ATV-A-2	ATV-DBA	26x12x12	ATV-D	ATV-D-2	ATV-DBD
23x11x10	ATV-A	ATV-A-2	ATV-DBA	27x9x12	ATV-D	ATV-D-2	ATV-DBD
24x8x11	ATV-A	ATV-A-2	ATV-DBA	27x9x14	ATV-D	ATV-D-2	ATV-DBD
24x8x12	ATV-A	ATV-A-2	ATV-DBB	27x10x12	ATV-D	ATV-D-2	ATV-DBD
24x9x10	ATV-B	ATV-B-2	ATV-DBB	27x11x12	ATV-D	ATV-D-2	ATV-DBD
24x9x11	ATV-B	ATV-B-2	ATV-DBA	27x11x14	ATV-D	ATV-D-2	ATV-DBD
24x9x12	ATV-B	ATV-B-2	ATV-DBB	27x12x12	ATV-D	ATV-D-2	ATV-DBF
24x10x11	ATV-B	ATV-B-2	ATV-DBB	28x9x14	ATV-D	ATV-D-2	ATV-DBD
24x10x12	ATV-C	ATV-C-2	ATV-DBB	28x10x12	ATV-D	ATV-D-2	ATV-DBD
24x11x9	ATV-C	ATV-C-2	ATV-DBA	28x11x14	ATV-D	ATV-D-2	ATV-DBD
24x11x10	ATV-C	ATV-C-2	ATV-DBB	28x12x12	ATV-D	ATV-D-2	ATV-DBF
24x11x12	ATV-B	ATV-B-2	ATV-DBB	29x9x14	ATV-D	ATV-D-2	-
24x11.5x10	ATV-C	ATV-C-2	ATV-DBB	29x11x14	2829	2829-2	-
24x12x12	ATV-C	ATV-C-2	-	30x10x15	2829	2829-2	-
24x13x9	ATV-C	ATV-C-2	-	31x10x14	3828	3828-2	-
24x14x12	2829	2829-2	-	32x10x14	3828	3828-2	-
25x8x12	ATV-B	ATV-B-2	ATV-DBA	240/75-10	ATV-B	ATV-B-2	ATV-DBB
25x8.5x12	-	-	ATV-DBE	290/65-10	ATV-C	ATV-C-2	ATV-DBD
25x10x10	ATV-C	ATV-C-2	ATV-DBD				

ATV / UTV



FORESTRY



- STUDDED LINKS ON THE NET STYLE FOR EXTREME TRACTION IN OFF-ROAD APPLICATIONS
- LARGE FORGED LUGS ON RING STYLE
- ALLOY STEEL LINKS FOR LONGER LIFE



NR - NORDIC RING



NTR - NORDIC TIGHT RING



NN - NORDIC NET



FORESTRY

5/8" - 16 MM

NORDIC RING

NORDIC TIGHT RING

NORDIC NET

TIRE SIZE	STOCK NUMBER	WT PER PAIR (LBS)	STOCK NUMBER	WT PER PAIR (LBS)	STOCK NUMBER	WT PER PAIR (LBS)
23.1-26	NR231-16	662	NTR231-16	650	NN231-16	1030
24.5-32; 28L-26	NR245-16	787	-	-	NN245-16	1143
30.5-32	NR305-16	865	-	-	NN305-16	1148

11/16" - 18 MM

TIRE SIZE	STOCK NUMBER	WT PER PAIR (LBS)	STOCK NUMBER	WT PER PAIR (LBS)	STOCK NUMBER	WT PER PAIR (LBS)
24.5-32; 28L-26	NR245-18	891	NTR245-18	650	NN245-18	1298
30.5-32	NR305-18	970	NTR305-18	1000	NN305-18	1366
35.5-32	NR355-18	1043	-	-	NN355-18	1531

1" - 25 MM

TIRE SIZE	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)	STOCK NUMBER	WT/ PR (LBS)
30.5-32	-	-	NTR305-25	1675	-	-
35.5-32	-	-	NTR355-25	1897	-	-
73x44x32	-	-	NTR730-25	1823	-	-

FORESTRY CHAIN



RA
RING
ALLOY

RAT
TIGHT RING
ALLOY

RAM
MULTI RING
ALLOY

NC
STUDDED NET
ALLOY

NCU
U-GRIP NET
ALLOY

WIRE SIZE			RING ALLOY		TIGHT RING ALLOY		MULTI RING ALLOY		STUDDED NET ALLOY		U-GRIP NET ALLOY	
TIRE SIZE	INCHES	MM	STOCK NUMBER	WT / PR (LBS)	STOCK NUMBER	WT / PR (LBS)	STOCK NUMBER	WT / PR (LBS)	STOCK NUMBER	WT / PR (LBS)	STOCK NUMBER	WT / PR (LBS)
23.1-26; 18.4-34	9/16"	14	RA231-14	618	-	-	-	-	-	-	-	-
	5/8"	16	-	-	-	-	-	-	-	-	NCU231-16	930
24.5-32; 28L-26	5/8"	16	-	-	RAT245-16	842	RAM245-16	902	NC245-16	1023	NCU245-16	1092
	11/16"	18	-	-	-	-	-	-	-	-	NCU245-18	1276
	3/4"	19	RA245-19	1194	RAT245-19	1170	RAM245-19	1444	-	-	-	-
	13/16"	20	-	-	-	-	-	-	NC245-20	1512	NCU245-20	1722
35.5-32	3/4"	19	-	-	-	-	RAM355-19	1804	-	-	-	-
	13/16"	20	-	-	-	-	-	-	NC355-20	1926	-	-

TIGHTENING TOOLS & ADJUSTERS

STOCK NUMBER	APPLICATION	STANDARD PACKAGING	WEIGHT PER PKG (LBS)
350100	TRYGG Skidder Installation Tool	1 EACH	9
2506HD	Heavy Duty Installation Tool		14
671425	TRYGG Balder Track Installation Tool		13
0294	Large Link w/Shackle Adjuster (Small Skidder - Light Loader - Tractor)	1 PAIR	10
0296	Giant Link w/Shackle Adjuster (Skidder - Loader - Grader)		28.4



NORDIC™ DOUBLE DIAMOND TOP MOUNT U-GRIP NETLINK



- THESE CHAINS OFFER INCREDIBLE DURABILITY THANKS TO OUR UNIQUE HEAT TREATMENT PROCESS AND LARGE MATERIAL SIZE
- THE USE OF TOP MOUNTED U-STUDS MAXIMIZES TRACTION AND PREVENTS THE CHAIN FROM ROLLING OVER
- DDU CHAINS ARE A GREAT OPTION FOR OPERATORS LOOKING FOR INCREDIBLE TRACTION AND WEAR LIFE
- DOUBLE DIAMOND PATTERN FORMS A NET OVER THE TIRE PROVIDING EXCELLENT COVERAGE



U-GRIP CLOSE-UP

DDU -DOUBLE DIAMOND

TIRE SIZE	STOCK NUMBER	WT / PR(LBS)	MATERIAL SIZE
24.5-32	DDU2453234	1440	19 MM (3/4")
30.5-32	DDU3053234	1473	
35.5-32	DDU3553234	1636	



HEAVY DUTY
INSTALLATION TOOL
SOLD SEPARATELY

PART # 2506HD
SEE PAGE 94



DDU -DOUBLE DIAMOND



FORESTRY



TRYGG SM2D & NET LINK



SM2D

- SM2D HEAVY DUTY TRACTION AND TIRE PROTECTION FOR FORESTRY, CONSTRUCTION AND SNOW CLEARING
- ULTIMATE TRACTION, SMOOTH RIDE, AND TROUBLE-FREE OPERATION.
- UNSURPASSED NUMBER OF STUDS GIVE MAXIMUM GRIP AND INCREASED SERVICE LIFE
- DOUBLE OR TRIPLE DIAMOND TO SUIT TIRE WIDTH
- ALL SM2D/3D VERSIONS HAVE OVERSIZED STUDS TO INCREASE GRIP AND STRENGTH

5/8" - 16 MM

TIRE SIZE	STOCK NUMBER	WT / PR (LBS)
24.5-32	618968	1098
30.5-32	618969	1197

THE SM2D IS MADE IN 7/16" - 11 MM,
1/2" - 13 MM, 5/8" - 16 MM
AND 3/4" - 19 MM

CALL OR SEE MORE ONLINE



NET LINK

- NET LINK IS A VERSATILE MULTIPURPOSE CHAIN FOR USE ON ALL TYPES OF HEAVY EQUIPMENT
- PROVEN DOUBLE DIAMOND DESIGN WITH DOUBLE STUDS PROVIDES FULL TIRE WIDTH TRACTION
- FULLY HARDENED AND ANNEALED ENSURING TROUBLE-FREE PERFORMANCE IN ALL CONDITIONS AND TEMPERATURES

5/8" - 16 MM

TIRE SIZE	STOCK NUMBER	WT / PR (LBS)
23.5-25L5	611368	1146
30.5-32	611371	1223

3/4" - 19 MM

TIRE SIZE	STOCK NUMBER	WT / PR (LBS)
24.5-32	611466	1349
30.5-32	611471	1459
35.5-32	611482	1811

AVAILABLE IN 1/2" - 13 MM, 5/8" - 16 MM, 3/4" - 19 MM AND 7/8" - 22 MM
ALSO AVAILABLE WITHOUT STUDS FOR USE ON ROADS AND LOADING YARDS.

TRYGG SMT COMBO

- OVERSIZED STUDS INCREASE GRIP AND LAST LONGER
- SMT PATTERN HOLDS THE CHAIN ON TOP OF THE TIRE LUGS, KEEPING THE STUDS IN CONSTANT CONTACT WITH THE TERRAIN
- SMT COMBO FITS MORE THAN ONE TIRE SIZE
- GREAT FOR USE WITH SNOW CLEARING, FORESTRY AND CONSTRUCTION VEHICLES

SMT COMBO

TIRE SIZE	STOCK NUMBER	INCHES	MM	WEIGHT / PR (LBS)
23.1-26; 18.4-34	608965	5/8"	16	717
24.5-32; 28L-26	608968	5/8"	16	860
30.5-32	608969	5/8"	16	854



MORE CHAIN STYLES & FITMENTS AVAILABLE ON OUR WEBSITE: WWW.QUALITYCHAINCORP.COM
EMAIL: INFO@CHAINQUEST.COM OR CALL US DIRECT: (503) 614-9664 / CA & NV CUSTOMERS CALL: (916) 409-0408

- TRYGG TROLL IS DESIGNED WITH LARGER GAUGE LINKS AND STUDS AROUND THE CROWN OF THE TIRE WHERE THE PRESSURE AND CONTACT IS THE GREATEST
- STIFF MESH PATTERNS MINIMIZE MOVEMENT AND KEEP STUDS VERTICAL
- DEEP CASE HARDENED ALLOY STEEL ENSURES DURABILITY AND LONG SERVICE LIFE



TRYGG

7/8" - 22 MM

SINGLE DIAMOND

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)
30.5-32	628971	1195
35.5-32	628982	1363

DOUBLE DIAMOND

TIRE SIZE	STOCK NUMBER	WEIGHT PER PAIR (LBS)
30.5-32	628571	1742
35.5-32	628582	2002

UNDERSIDE OF PATTERN



- TIRE FRIENDLY
- SMOOTH UNDERSIDE HAS NO WELDS RESTING ON THE TIRE
- LARGE LEVEL CONTACT SURFACE MINIMIZES RUBBING

CENTER DIAMOND
7/8" - 22MM LINKS
1" - 25MM STUDS



SHOULDER DIAMOND
3/4" - 19MM LINKS
7/8" - 22MM STUDS



DOUBLE DIAMOND PICTURED



FORESTRY

THE GENESIS TRACK SYSTEM WAS DESIGNED TO
MAXIMIZE OPERATIONAL EFFICIENCY WHILE
REDUCING COSTS AND MINIMIZING DOWNTIME.

THE FULLY FORGED 32MM CONNECTING LINKS
OFFER UNMATCHED DEPENDABILITY AND WEAR LIFE.
THE GENESIS TRACKS CAN TACKLE ANY
TERRAIN YOU THROW AT THEM.




FORESTRY

NOKIAN FOREST KING F

TIRE SIZE	STOCK NUMBER	GROUSER PROFILE	WEIGHT PER PAIR (LBS)
710/45-26.5	MT710/45-3211	MOUNTAIN MT86	4693
750/55-26.5	MT750/55-3211	MOUNTAIN MT86	5539
780/50-28.5	MT780/50-3211	MOUNTAIN MT86	5713


NOKIAN FOREST KING F2

TIRE SIZE	STOCK NUMBER	GROUSER PROFILE	WEIGHT PER PAIR (LBS)
780/50-28.5	MT780/50-3231	MOUNTAIN MT86	5800



**MOUNTAIN
MT86**
86MM WIDE

**MECHANICAL
CONNECTORS**
KONNECT-125 / 175 / 225



TRYGG BALDER SINGLE WHEEL TRACK



- STEEP SLOPE RUNNER
- CLIMBING GRIP AND STABILITY ON RUGGED MOUNTAINS
- POWERS THROUGH SNOW, MUD AND ICE
- EXTENDS LIFE OF WORN TIRES
- OUTLASTS CHAINS BY UP TO DOUBLE THE HOURS
- MADE OF BORON ENHANCED ALLOY STEEL



TRYGG

BALDER SKID SINGLE WHEEL

TIRE SIZE	STOCK NUMBER	CROSS BAR LENGTH (IN)	GROUSER PROFILE	WEIGHT PER PAIR (LBS)
30.5-32	670072	38"	26 MM - 1" DOUBLE CLEAT	2977
35.5-32	670083	44"	26 MM - 1" DOUBLE CLEAT	3276



CROSSBAR WITH RAISED RIDGE



DOUBLE CLEATS ON EVERY CROSSBAR
1 3/4" X 7/8" X 1 3/8"



TRACK LOCK

THREE REMOVABLE CROSSBARS ALLOW THE OPERATOR TO KEEP THE TIGHTNESS ADJUSTED PROPERLY AS THE TIRES AND TRACKS WEAR OVER TIME

8 TRACK LOCKS INCLUDED



TRACK LOCK
INSTALLATION TOOL
SOLD SEPARATELY

PART # 671425
SEE PAGE 94



FORESTRY

The background of the image is a dynamic industrial scene. A large, heavy-duty metal chain hangs vertically from the top center. To the right, a welding torch or similar tool is positioned, creating a massive spray of bright, glowing sparks that cascade downwards and outwards, filling the right half of the frame. The sparks have a golden-yellow hue. In the upper left, a large, dark, circular industrial component is visible. The overall lighting is bright, emphasizing the metallic textures and the intense light from the sparks.

REPLACEMENT PARTS & ACCESSORIES

CONTINUOUS CROSS CHAIN

HARDENED TWIST LINK REGULAR AND PREMIUM



Regular



Premium

REGULAR HARDENED

PREMIUM HARDENED

STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
30177	24	A30177	24	1/0	11/64"	4.5 MM	.177	100'
30207	39	A30207	39	3/0	13/64"	5.2 MM	.207	
30218	49	A30218	49	4/0	7/32"	5.5 MM	.218	
30234	51	A30234	51	5/0	1/4"	6.4 MM	.234	
30281	66	A30281	66	6/0	9/32"	7 MM	.281	
30312	40	A30312	40	7/0	5/16"	8 MM	.312	50'
30375	64	A30375	64	9/0	3/8"	10 MM	.375	
30437	92	A30437	92	11/0	7/16"	11 MM	.437	
30531	140	A30531	140	14/0	17/32"	13.5 MM	.531	
30750	258	-	-	-	3/4"	19 MM	.750	PER FOOT

V-BAR TWISTED LINK REGULAR AND PREMIUM



Regular V-Bar



Premium V-Bar

REGULAR V-BAR

PREMIUM V-BAR

STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
38218	51	A38218	58	4/0	7/32"	5.5 MM	.218	100'
38281	43	A38281	44	6/0	9/32"	7 MM	.281	50'
38312	54	A38312	56	7/0	5/16"	8 MM	.312	
38375	80	A38375	82	9/0	3/8"	10 MM	.375	

TWISTED LINK ALLOY AND PREMIUM STUDDED LINK ALLOY



Twisted Link Alloy



Premium Studded Link Alloy

TWISTED LINK ALLOY

PREMIUM STUDDED LINK ALLOY

STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
33218	49	-	-	4/0	7/32"	5.5 MM	.218	100'
33281	66	39281	94	6/0	9/32"	7 MM	.281	
33312	40	39312	62	7/0	5/16"	8 MM	.312	50'
33375	64	39375	90	9/0	3/8"	10 MM	.375	
33437	92	39437	98	11/0	7/16"	11 MM	.437	
33531	140	39531	150	14/0	17/32"	13.5 MM	.531	

SQUARE LINK ALLOY AND TWISTED SQUARE LINK ALLOY



Square Link Alloy



Twisted Square Link Alloy

SQUARE LINK ALLOY

PREMIUM SQUARE LINK ALLOY

TWISTED SQUARE LINK ALLOY

STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
31218	47	A31218	48	34218	47	4/0	7/32"	5.5 MM	.218	100'
31281	37	A31281	37	34281	38	6/0	9/32"	7 MM	.281	50'
31312	48	A31312	51	34312	54	7/0	5/16"	8 MM	.312	
31375	83	A31375	85	34375	89	9/0	3/8"	10 MM	.375	
31437	98	A31437	114	34437	115	11/0	7/16"	11 MM	.437	
31531	155	A31531	180	-	-	14/0	17/32"	13.5 MM	.531	PER FOOT
31750	303	-	-	-	-	-	3/4"	19 MM	.750	

CONTINUOUS SIDE CHAIN

REGULAR AND PREMIUM UNHARDENED SIDE CHAIN AND HARDENED SIDE CHAIN



Regular



Premium

REGULAR UNHARDENED		PREMIUM UNHARDENED		HARDENED		NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)					
40177	23	-	-	-	-	1/0	11/64"	4.5 MM	.177	100'
40192	25	-	-	-	-	2/0	3/16"	4.8 MM	.192	
40207	30	-	-	-	-	3/0	13/64"	5.2 MM	.207	
40218	35	A40218	35	AL40218H	35	4/0	7/32"	5.5 MM	.218	
40281	53	A40281	53	AL40281H	59	6/0	9/32"	7 MM	.281	
40312	69	A40312	69	AL40312H	70	7/0	5/16"	8 MM	.312	
40375	53	A40375	53	AL40375H	52	9/0	3/8"	10 MM	.375	50'
40437	75	A40437	75	AL40437H	75	11/0	7/16"	11 MM	.437	
40531	118	A40531	118	AL40531H	120	14/0	17/32"	13.5 MM	.531	
40750	258	-	-	-	-	-	3/4"	19 MM	.750	PER FOOT

CAM SIDE CHAIN

PRE-CUT WITH FOUR CAMS AND ONE END FASTENER PER RAIL

STOCK NUMBER	WEIGHT / PKG (LBS)	END FASTENER	LENGTH (INCHES)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
40218C	31	15003	86"	4/0	7/32"	5.5 MM	.218	10 PCS
40281C	61	15004	120"	6/0	9/32"	7 MM	.281	
40312C	86			7/0	5/16"	8 MM	.312	



REPLACEMENT CAMS FOR SIDE CHAIN

STOCK NUMBER	APPLICATION	WEIGHT / PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
CAM4	LIGHT TRUCK	1	4/0	7/32"	5.5 MM	.218	1 PC
CAM6	HEAVY TRUCK		6/0	9/32"	7 MM	.281	
CAM7			7/0	5/16"	8 MM	.312	



HARDENED CROSS CHAIN HOOKS

REGULAR		PREMIUM						
STOCK NUMBER	STOCK NUMBER	WEIGHT / PKG (LBS)	APPLICATION	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
20177	A20177	2	PASSENGER	1/0	11/64"	4.5 MM	.177	50 PCS
20230	A20230	4		3/0	15/64"	5.9 MM	.230	
20250	A20250	5	LIGHT TRUCK	5/0	1/4"	6.4 MM	.250	
20312	A20312	8	MEDIUM TRUCK	7/0	5/16"	8 MM	.312	
20375	A20375	12	HEAVY TRUCK	9/0	3/8"	10 MM	.375	
-	A20375L	13	LONG PITCH	9/0	3/8"	10 MM	.375	
20406	A20406	17	TRACTOR	10/0	13/32"	10.3 MM	.406	25 PCS
20437	A20437	22	GRADER	11/0	7/16"	11 MM	.437	
20437S	A20437S	23	SHORT PITCH	11/0	7/16"	11 MM	.437	
20531	A20531	14	LOADER	14/0	17/32"	13.5 MM	.531	



Regular



Premium

SWIVEL HOOKS

STOCK NUMBER	WEIGHT / PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	STANDARD PACKAGE
20451JH	13	9/0	3/8"	10 MM	.375	50 PCS
20450JH	20	11/0	7/16"	11 MM	.437	
20455JH	25	-	1/2"	12.5 MM	.500	
20375RJH	30	9/0	3/8"	10 MM	.375	





Swivel J Hook



Rugro Hook

SIDE CHAIN FASTENERS

STOCK NUMBER	APPLICATION	WEIGHT / PKG (LBS)	OVERALL LENGTH (INCHES)	STANDARD PACKAGE	PICTURE
5308	PASSENGER, LIGHT TRUCK	2	3"	25 PCS	1
5309	MEDIUM, HEAVY TRUCK	6.3	6"		
5310	TRACTOR	10	8.5"		
5311	MEDIUM, HEAVY TRUCK	8.8	7.5"		
5313	MEDIUM TRUCK	6.3	6"		
15003	LIGHT TRUCK	5	3"	25 PCS	2
15004	MEDIUM, HEAVY TRUCK	10	3.25"	1 EACH	3
15005	HEAVY GRADER	0.8	4.5"		2
15007	LIGHT GRADER	0.4	3.5"		
15008	HEAVY GRADER	0.9	4.5"		



PREMIUM SIDE CHAIN FASTENERS

STOCK NUMBER	APPLICATION	WEIGHT / PKG (LBS)	OVERALL LENGTH (INCHES)	STANDARD PACKAGE	PICTURE
A5308	PASSENGER, LIGHT TRUCK	1.3	1.5"	25 PCS	4
15NR4	LIGHT TRUCK BOOMER STYLE FITS 5.0 - 5.5 MM SIDE CHAIN	0.2	4.75"	1 EACH	5
15NR6	HEAVY TRUCK BOOMER STYLE FITS 6.0 - 8.0 MM SIDE CHAIN	0.5	6.5"		
15NR9	GRADER BOOMER STYLE FITS 9.5 - 11 MM SIDE CHAIN	0.9	8"		

CHAIN REPAIR PLIERS


STOCK NUMBER	APPLICATION	WEIGHT / PKG (LBS)	OVERALL LENGTH (INCHES)	STANDARD PACKAGE	PICTURE
7301	PASSENGER	0.3	6"	1 EACH	6
7300HD	PASSENGER, LIGHT TRUCK	2.8	14"		7
QV1893	VOLT TRUCK REPAIR PLIER	7	30.5"		8
75025	ALL TRUCK, TRACTOR SHORT HANDLE	8.1	24"		9
7302	ALL TRUCK, TRACTOR LONG HANDLE	10	36"		10

BOLT/CHAIN CUTTERS

STOCK NUMBER	APPLICATION	WEIGHT / PKG (LBS)	OVERALL LENGTH (INCHES)	STANDARD PACKAGE	PICTURE
BC18	PASSENGER	2.9	18"	1 EACH	11
BC24	LIGHT TRUCK	5.5	24"		
BC30	MEDIUM, HEAVY TRUCK	8.3	30"		
BC36	ALL TRUCK, TRACTOR	12.7	36"		


QUICK HOOKS

STOCK NUMBER	APPLICATION	WEIGHT/ PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	INSIDE PITCH (INCHES)	STANDARD PACKAGE	PICTURE
10218	PASSENGER	1	4/0	7/32"	5.5 MM	1.875"	25 PCS	1
10250	GARDEN TRACTOR		5/0	1/4"	6.4 MM			
10281	LIGHT TRUCK	2	6/0	9/32"	7 MM	2.125"		
10312	MEDIUM TRUCK		7/0	5/16"	8 MM	2.5"		
10375	HEAVY TRUCK	4	9/0	3/8"	10 MM	2.125"		
10406	TRACTOR	6	10/0	13/32"	10.3 MM	3"		



PREMIUM QUICK HOOKS

STOCK NUMBER	APPLICATION	WEIGHT/ PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	INSIDE PITCH (INCHES)	STANDARD PACKAGE	PICTURE
10N95-7	LIGHT TRUCK	0.18	6/0	9/32"	7 MM	1.7"	1 EACH	2
10N95	HEAVY TRUCK	0.2	7/0	5/16"	8 MM	2"		



CROSS CHAIN REPAIR LINKS

STOCK NUMBER	APPLICATION	WEIGHT/ PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	STANDARD PACKAGE	PICTURE
9233	PASSENGER	1	3/0	13/64"	5.2 MM	50 PCS	3
9253	LIGHT TRUCK	2	5/0	1/4"	6.4 MM		
9263	MEDIUM TRUCK	4	6/0	9/32"	7 MM		
9273	HEAVY TRUCK	5	7/0	5/16"	8 MM		



SQUARE LINK CROSS CHAIN REPAIR LINKS

STOCK NUMBER	APPLICATION	WEIGHT/ PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	STANDARD PACKAGE	PICTURE
9280	GRADER	8	9/0	3/8"	10 MM	10 PCS	4
9282	LOADER	13	11/0	7/16"	11 MM		
9284	GIANT OTR	22	14/0	17/32"	13.5 MM		



SIDE CHAIN REPAIR LINKS

STOCK NUMBER	APPLICATION	WEIGHT/ PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	INSIDE PITCH (INCHES)	STANDARD PACKAGE	PICTURE
9116A	PASSENGER	2	4/0	7/32"	5.5 MM	1.208"	50 PCS	5
9116B	LIGHT TRUCK	3	5/0	1/4"	6.4 MM	1.581"		
9116C	TRUCK	7	7/0	5/16"	8 MM	1.457"		
9116D	GRADER	11	9/0	3/8"	10 MM	1.639"		
9116E	LOADER	3	11/0	7/16"	11 MM	2.379"	10 PCS	
9116F	GIANT OTR	5	14/0	17/32"	13.5 MM	2.157"		



LINK REPAIR RINGS TO REPAIR NET, DIAMOND BACK

STOCK NUMBER	APPLICATION	WEIGHT/ PKG (LBS)	NOMINAL SIZE	WIRE SIZE (INCHES)	METRIC WIRE SIZE	STANDARD PACKAGE	PICTURE
RING-6	TRUCK / TRACTOR	1	5/0	1/4"	6.4 MM	1 EACH	6
RING-13	LOADER / GRADER		14/0	17/32"	13.5 MM		
RING-16	GIANT OTR		-	5/8"	16 MM		



COLD SHUTS

STOCK NUMBER	WIRE SIZE (INCHES)	LENGTH (INCHES)	INSIDE WIDTH (INCHES)	WEIGHT / PKG (LBS)	WORKING LOAD (LBS)	STANDARD PACKAGE	PICTURE
CS312	5/16"	1.22"	1.06"	1	1,250	10 PCS	7
CS375	3/8"	1.45"	1.33"	1.6	1,900		
CS437	7/16"	1.5"	1.55"	2.6	2,650		



SHACKLES CHAIN, ANCHOR AND PIN COUPLER STYLES




GALVANIZED SCREW PIN CHAIN SHACKLE



ALLOY SCREW PIN ANCHOR SHACKLE



GALVANIZED SCREW PIN ANCHOR SHACKLE



GALVANIZED PIN COUPLER SHACKLE

STOCK NUMBER	WORKING LOAD LIMIT (LBS)	STOCK NUMBER	WORKING LOAD LIMIT (LBS)	STOCK NUMBER	WORKING LOAD LIMIT (LBS)	STOCK NUMBER	DIMENSIONS (INCHES)		WIRE SIZE (INCHES)	METRIC WIRE SIZE
							A	B		
SGC218	700	-	-	-	-	-	-	-	7/32"	5.5 MM
SGC250	1,000	SAC250	2,000	-	-	PCS250	1.055	0.355	1/4"	6.4 MM
SGC312	1,500	-	-	SPC312	1,500	PCS312	1.425	0.425	5/16"	8 MM
SGC375	2,000	SAC375	4,000	SPC375	2,000	PCS375	1.529	0.503	3/8"	10 MM
SGC437	3,000	SAC437	5,200	-	-	-	-	-	7/16"	11 MM
SGC531	4,000	SAC531	6,600	SPC531	4,000	PCS531	2.078	0.681	17/32"	13.5 MM
SGC625	6,500	SAC625	10,000	SPC625	6,500	PCS625	2.429	0.777	5/8"	16 MM
-	-	SAC750	14,000	SPC750	9,500	PCS750	2.797	0.980	3/4"	19 MM

CAM TOOLS "T" AND "L" HANDLES

T-HANDLE

L-HANDLE

STOCK NUMBER	WEIGHT / PKG (LBS)	STOCK NUMBER	WEIGHT / PKG (LBS)	DESCRIPTION	STANDARD PACKAGE
T2801	5	L2801	2.5	LIGHT TRUCK	25 PCS
T2800	11.25	L2800	10	HEAVY TRUCK	

T-HANDLE




L-HANDLE




QUICK LINKS

STOCK NUMBER	WIRE SIZE (INCHES)	METRIC WIRE SIZE	DIMENSIONS (INCHES)					WT/ PKG (LBS)	WORKING LOAD LIMIT (LBS)	STANDARD PACKAGE
			A	B	C	D	E			
QL125	1/8"	3.2 MM	0.188"	1.125"	1.375"	0.375"	0.188"	0.2	220	10 PCS
QL192	3/16"	4.8 MM	0.281"	1.5"	1.875"	0.5"	0.25"	0.4	660	
QL281	9/32"	7 MM	0.375"	1.75"	2.25"	0.563"	0.281"	0.8	880	
QL312	5/16"	8 MM	0.5"	2.313"	2.875"	0.688"	0.375"	1.6	1,760	
QL375	3/8"	10 MM		2.438"	3.125"	0.75"	0.438"	2.4	2,200	
QL437	7/16"	11 MM	0.531"	2.688"	3.5"	0.813"	0.5"	3.8	2,600	
QL531	17/32"	13.5 MM	0.594"	3.188"	4.125"	0.938"	0.525"	5.6	3,300	



SNAP HOOKS

STOCK NUMBER	WIRE SIZE (INCHES)	METRIC WIRE SIZE	DIMENSIONS (MM)					WT/ PKG (LBS)	WORKING LOAD LIMIT (LBS)	STANDARD PACKAGE
			A1	A	B	D	L			
SH440	5/32"	4 MM	9	5	6.5	7	40	0.2	200	10 PCS
SH550	3/16"	4.8 MM	10	6	7.5	8	50	0.4	220	
SH660	1/4"	6.4 MM	13	8	9	9	60	0.6	260	
SH770	9/32"	7 MM			10		70	1	400	
SH880	5/16"	8 MM			11.5		80	1.4	500	
SH990	11/32"	9 MM	14		13		90	2	550	
SH1010	3/8"	10 MM	15	12	15	13	100	2.6	770	
SH1112	7/16"	11 MM	18	14	19	15	120	4	980	5 PCS
SH1214	15/32"	11.9 MM	20	13	18	19	140	2.8	1200	
SH1316	1/2"	12.7 MM	22	14	20	26	160	3.9	1600	
SH1418	17/32"	13.5 MM	25	21	25	32	180	4.9	1800	
SH1520	9/16"	14.3 MM				40	200	6	1800	



WHICH TIGHTENER IS RIGHT FOR YOU?

⚠ WARNING: ALWAYS WEAR EYE PROTECTION WHEN INSTALLING RUBBER BUNGEEES, TIGHTENERS OR STRAPS.

When deciding which tightener is correct for your application, begin with what vehicle type you have and reference the information below to help find the correct product.

THIS IS A GUIDE ONLY. ACTUAL TENSIONER MAY VARY BASED ON OVERALL TIRE DIAMETER. PLEASE CHECK PRIOR TO USE.

PASSENGER CAR

TIGHTENER	PART NUMBER	COLOR & MATERIAL	FITS RIM SIZE
SPIDER BUNGEE	0212	YELLOW RUBBER	13" - 22"
RUBBER TIGHTENER	0214	BLACK RUBBER	

VOLT SEE PAGES 12 - 13 FOR CORRECT VOLT BUNGEE BY PART NUMBER

LIGHT TRUCK / SUV

TIGHTENER	PART NUMBER	COLOR & MATERIAL	FITS RIM SIZE
SPIDER BUNGEE	0216	BLUE RUBBER	14" - 24"
RUBBER TIGHTENER	0225	BLACK RUBBER	
SPRING TIGHTENER	0272	SILVER ZINC	

VOLT SEE PAGES 26 - 27 FOR CORRECT VOLT BUNGEE BY PART NUMBER

COMMERCIAL TRUCK

TIGHTENER	PART NUMBER	COLOR & MATERIAL	FITS RIM SIZE
SPIDER BUNGEE	0218	ORANGE RUBBER	20" - 24.5"
RUBBER TIGHTENER	0229	BLACK RUBBER	
SPRING TIGHTENER	0273	SILVER ZINC	

VOLT SEE PAGE 41 FOR CORRECT VOLT BUNGEE BY PART NUMBER

LOADER / GRADER

TIGHTENER	PART NUMBER	COLOR & MATERIAL	FITS RIM SIZE
SPIDER BUNGEE	0220	BLACK RUBBER	20" - 24"
LINK SHACKLE TIGHTENER	0294	GOLD ZINC	
LINK SHACKLE TIGHTENER	0296	GOLD ZINC	25" - UP

TRACTOR / SNOW BLOWER

TIGHTENER	PART NUMBER	COLOR & MATERIAL	FITS RIM SIZE
SPIDER BUNGEE	0213	GREEN RUBBER	8" - 10"
SPIDER BUNGEE	0217	RED RUBBER	12" - 18"
SPIDER BUNGEE	0218	ORANGE RUBBER	18" - 20"
SPIDER BUNGEE	0220	BLACK RUBBER	24" - 28"
LINK SHACKLE TIGHTENER	0294	GOLD ZINC	20" - 28"
LINK SHACKLE TIGHTENER	0296	GOLD ZINC	28" - UP

FORKLIFT / SKID STEER

TIGHTENER	PART NUMBER	COLOR & MATERIAL	FITS RIM SIZE
SPIDER BUNGEE	0213	GREEN RUBBER	9" - 10"
SPIDER BUNGEE	0216	BLUE RUBBER	12" - 18"
SPIDER BUNGEE	0218	ORANGE RUBBER	18" - UP

ATV / UTV

TIGHTENER	PART NUMBER	COLOR & MATERIAL	TIRE DIAMETER
SPIDER BUNGEE	0213	GREEN RUBBER	20" - 24"
SPIDER BUNGEE	0217	RED RUBBER	24" - UP

0218 SPIDER BUNGEE PICTURED




0296 LINK SHACKLE PICTURED



SPIDER BUNGEEES

STOCK NUMBER	APPLICATION	NUMBER OF ARMS	WEIGHT / PR (LBS)	STANDARD PACKAGE	PICTURE
0212	PASSENGER	6	0.9	30 PR	1
0216	LIGHT TRUCK / SUV		0.9		2
0218	COMMERCIAL TRUCK		1.7		3
0220	TRACTOR / LIGHT LOADER	7	3	20 PR	4
	SMALL ATV / UTV		1	30 PR	5
0213	GARDEN TRACTOR				
	SNOW BLOWER				
0217	LARGE ATV / UTV				6
	FORKLIFT / SKID STEER				




RUBBER TIGHTENERS

STOCK NUMBER	APPLICATION	WEIGHT/ PR (LBS)	STANDARD PACKAGE	PICTURE
QV1172	VOLT PASSENGER	0.4	30 PR	7
QV1174	VOLT PASSENGER, LIGHT TRUCK	0.5		
QV1176	VOLT LIGHT TRUCK			
QV1870	VOLT TRUCK	0.6		8
QV1874				
QV1876				
QV1882				
0214	PASSENGER	0.5	30 PR	9
0225	LIGHT TRUCK / SUV	0.6		
0229	COMMERCIAL TRUCK	1		

WARNING: ALWAYS WEAR EYE PROTECTION WHEN INSTALLING RUBBER BUNGEEES, TIGHTENERS OR STRAPS.

SPRING TIGHTENERS

STOCK NUMBER	APPLICATION	WEIGHT/ PR (LBS)	STANDARD PACKAGE	PICTURE
0272	LIGHT TRUCK / SUV	1.25	1 PR	11
0273	COMMERCIAL TRUCK	4.8		



LINK SHACKLE TIGHTENERS

STOCK NUMBER	APPLICATION	FITS RIM SIZE	WEIGHT/ PR (LBS)	STANDARD PACKAGE	PICTURE
0294	TRACTOR & LIGHT LOADER	20" - 24"	10	1 PR	12
0296	TRACTOR & LOADER/GRADER	25" - UP	28.4		

NATURAL RUBBER BUNGEE STRAPS

STOCK NUMBER	DESCRIPTION	STANDARD PACKAGE	PICTURE
0209	9 INCH STRAP	50 PCS / BOX (5 BUNDLES OF 10 PCS)	13
0215	15 INCH STRAP		
0221	21 INCH STRAP		
0231	31 INCH STRAP		
0241	41 INCH STRAP		



TRYGG PARTS



STUDDED CROSS CHAINS WITH HOOKS INSTALLED

WIRE SIZE	NO. OF LINKS	WEIGHT / PC (LBS)	STOCK # W/ HOOKS
5 MM 3/16"	10 links	0.42	307023
	11 links	0.46	307024
	12 links	0.53	307025
5.5 MM 7/32"	10 links	0.55	307033
	11 links	0.59	307034
	12 links	0.62	307035
6 MM 1/4"	10 links	0.57	307043
	11 links	0.62	307044
	12 links	0.66	307045
	13 links	0.70	307046
	14 links	0.75	307047
SUPER 7 MM 9/32"	15 links	0.81	307048
	8 links	0.95	307581
	9 links	1.03	307582
	10 links	1.12	307583
	11 links	1.21	307584
	12 links	1.3	307585
	13 links	1.39	307586
	14 links	1.43	307587
	15 links	1.52	307588
	16 links	1.61	307589
8 MM 5/16"	17 links	1.69	307590
	18 links	1.78	307591
	10 links	1.23	307081
	11 links	1.61	307083
	12 links	2.02	307085
9.5 MM 3/8"	14 links	1.98	307087
	16 links	2.38	307088
	8 links	2.09	307121
	9 links	2.24	307122
	10 links	2.42	307123
	11 links	2.42	307124
	12 links	2.66	307125
	13 links	2.84	307126
	14 links	3.01	307127
	15 links	3.21	307128

BULK CONTINUOUS STUDDED CROSS CHAIN

WIRE SIZE	PITCH MM / INCH	WEIGHT / FT (LBS)	STOCK NUMBER
5 MM	20 / 0.79	0.50	301050
5.5 MM	21 / 0.82	0.60	301055
6 MM	22.5 / 0.89	0.73	301060
7 MM SUPER	29.5 / 1.16	0.94	301072
8 MM	29.5 / 1.16	1.30	301080
9.5 MM	36.5 / 1.44	1.71	301095
11 MM	42 / 1.65	2.47	301110
13 MM	56 / 2.2	3.22	301130
16 MM	60.5 / 2.38	4.76	301160
19. MM	70 / 2.76	5.67	301190



BULK CONTINUOUS HARDENED SIDE CHAIN

WIRE SIZE	WEIGHT / FT (LBS)	STOCK NUMBER
5 x 34 MM	0.28	311050
6 x 34 MM SUPER	0.45	311061
7 x 42 MM	0.56	311070
8 x 50 MM	0.75	311081
9.5 x 50 MM	1.12	311096
9.5 x 62.5 MM	1.04	311095
11 x 60 MM	1.45	311110
13 x 60 MM	2.15	311131
13 x 81 MM	1.88	311132



BULK CONTINUOUS SQUARE ICE CROSS CHAIN

D MM / INCHES	W MM / INCHES	L MM / INCHES	WEIGHT / FT (LBS)	FEET / BUNDLE	STOCK NO.
5 / .188	6.5 / 0.26	17 / 0.67	0.37	98.4	305049
7 / .281	10 / 0.39	25 / 0.98	0.69	98.4	305070
8 / .312	11.3 / 0.44	28 / 1.01	1	98.4	305080
10 / .375	13.5 / 0.53	36 / 1.42	1.42	49.2	305100
11.5 / .453	15.5 / 0.61	41.5 / 1.63	1.84	32.8	305110

TRYGG PARTS



TRYGG BOOMER WITH LINK			
FOR USE WITH	SIZE MM / INCH	WEIGHT / PC (LBS)	STOCK NO.
4 - 4.5 MM SIDE CHAIN	4 (1/8")	0.13	331010
5 - 5.5 MM SIDE CHAIN	4 (1/8")	0.15	331020
6 - 7 MM SIDE CHAIN	6 (1/4")	0.33	331030
8 MM SIDE CHAIN	8 (5/16")	0.55	331040
9.5 - 11 MM SIDE CHAIN	10 (3/8")	1.01	331050



TRYGG INNER LOCK / FLAT C-HOOK			
FOR USE WITH	SIZE MM	WEIGHT / PC (LBS)	STOCK NO.
3 - 3.5 MM SIDE CHAIN	6	0.02	333200
4 - 5.5 MM SIDE CHAIN	7	0.04	333210
6 - 7 MM SIDE CHAIN	8	0.11	333220
8 - 10 MM SIDE CHAIN	9	0.2	333230



TRYGG CROSS CHAIN HOOKS			
WIRE SIZE MM / INCH	PITCH MM / INCH	WEIGHT / PC (LBS)	STOCK NO.
			UNHARDENED
5 - 3/16"	42 / 1.65	.06	320050
5.5 - 7/32"	42 / 1.65	.07	320055
6 - 1/4"	35 / 1.38	.08	320060
6 - 1/4"	35 / 1.38	.08	479005
7 - 9/32"	44 / 1.73	.12	320070
8 - 5/16"	43 / 1.69	.17	320080
8 HYBRID	57 / 2.24	.20	320081
9 - 23/64"	57 / 2.24	.26	320090
9 - 23/64"	44 / 1.73	.22	320091
10 - 3/8"	57 / 2.24	.32	320100
11 - 7/16"	61 / 2.40	.45	320110
13 - 1/2"	70 / 2.76	.72	320130

SHOE CHAIN / SHOE SPIKES

FOR BOOTS, ORDER ONE SIZE LARGER

EXAMPLE: SIZE 9 BOOT = SIZE 10 SHOE (SCL)



Shoe Chain

STOCK NUMBER	DESCRIPTION	MEN'S SHOE SIZE	WOMEN'S SHOE SIZE
SCM	MEDIUM SHOE CHAIN	5-9	6-10
SCL	LARGE SHOE CHAIN	9.5-12.5	10.5-up
SCXL	EXTRA LARGE SHOE CHAIN	13-up	-
SC-SPIKES	UNIVERSAL SHOE SPIKES	One size fits all	



SC-Spikes

WIRE DIAMETER CROSS REFERENCE CHART

NOMINAL WEIGHTS AND DIMENSIONS ARE SUBJECT TO TOLERANCE OF PLUS OR MINUS 4%

NOMINAL SIZE	GAUGE	FRACTIONAL (INCHES)	METRIC
1/0	.177	11/64"	4.5 MM
2/0	.192	3/16"	4.8 MM
3/0	.207	13/64"	5.2 MM
4/0	.218	7/32"	5.5 MM
5/0	.250	1/4"	6.4 MM
6/0	.281	9/32"	7 MM
7/0	.312	5/16"	8 MM
8/0	.344	11/32"	9 MM
9/0	.375	3/8"	10 MM
10/0	.406	13/32"	10.3 MM
11/0	.437	7/16"	11 MM
14/0	.531	17/32"	13.5 MM


FINDING YOUR REPLACEMENT CROSS CHAIN

To find the correct replacement cross chain for your application, follow these simple steps and refer to the tables on pages 111 - 115.



STEP 1:

Determine what type of chain you have.




STEP 2:

Measure the length of your cross chain from inside of hook to inside of hook.
(As shown in photos)

STEP 3:

Count the number of links in your cross chain.
(Do not count the outside hooks as links)

USE THIS INFORMATION
TO FIND YOUR
REPLACEMENT
CROSS CHAIN ON THE
FOLLOWING PAGES.



REPLACEMENT CROSS CHAIN

NOTE: PREMIUM NUMBERS IN BLUE

SEE PAGE 110 FOR HOW TO MEASURE
(INSIDE OF HOOK TO INSIDE OF HOOK)

ROUND TWIST LINK



CROSS CHAIN SPECIFICATIONS

HOOK SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
6219	12.12"	9	7/32"	5.5 MM	.218	20250	1/4"	6.4 MM	.250	CARBON	25 PCS
6221	13.24"	10	7/32"	5.5 MM	.218	20250	1/4"	6.4 MM	.250	CARBON	25 PCS
6221LM	13.24"	10	7/32"	5.5 MM	.218	A20250	1/4"	6.4 MM	.250	ALLOY	25 PCS
6223	14.08"	11	7/32"	5.5 MM	.218	20312	5/16"	8 MM	.312	CARBON	25 PCS
6225	15.12"	12	7/32"	5.5 MM	.218	20250	1/4"	6.4 MM	.250	CARBON	25 PCS
6225LM	15.12"	12	7/32"	5.5 MM	.218	A20250	1/4"	6.4 MM	.250	ALLOY	25 PCS
6229	17.1"	14	7/32"	5.5 MM	.218	20312	5/16"	8 MM	.312	CARBON	25 PCS
6233	16.01"	9	5/16"	8 MM	.312	20312	5/16"	8 MM	.312	CARBON	25 PCS
6250	13.32"	8	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6251	14.37"	9	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6251CL	14"	11	15/64"	5.9 MM	.230	A20281	9/32"	7 MM	.281	ALLOY	25 PCS
6251LM	14.37"	9	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6253	15.62"	10	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6253CL	16.25"	13	15/64"	5.9 MM	.230	A20281	9/32"	7 MM	.281	ALLOY	25 PCS
6253LM	15.62"	10	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6254	16.84"	11	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6255	12.88"	7	5/16"	8 MM	.312	20312	5/16"	8 MM	.312	CARBON	25 PCS
6256	14.62"	8	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6256HH	14.62"	8	5/16"	8 MM	.312	20406	13/32"	10.3 MM	.406	CARBON	25 PCS
6258	17.25"	11	9/32"	7 MM	.281	20375	3/8"	10 MM	.375	CARBON	25 PCS
6259	18.12"	12	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6260	16.01"	9	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6260HH	16.01"	9	5/16"	8 MM	.312	20406	13/32"	10.3 MM	.406	CARBON	25 PCS
6260LM	16.01"	9	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
6263	17.4"	10	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6263LM	17.4"	10	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
6265	23.12"	16	9/32"	7 MM	.281	20375	3/8"	10 MM	.375	CARBON	25 PCS
6266	18.79"	11	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6267	24.37"	17	9/32"	7 MM	.281	20375	3/8"	10 MM	.375	CARBON	25 PCS
6268	20.36"	12	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6434	17.36"	11	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	25 PCS
A6434	17.36"	11	3/8"	10 MM	.375	A20406	13/32"	10.3 MM	.406	ALLOY	25 PCS
6434HH	17.36"	11	3/8"	10 MM	.375	204375	7/16"	11 MM	.437	CARBON	25 PCS
6438	20.5"	13	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	25 PCS
6438HH	20.5"	13	3/8"	10 MM	.375	204375	7/16"	11 MM	.437	CARBON	25 PCS
6445	21.14"	14	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	25 PCS
A6445	21.14"	14	3/8"	10 MM	.375	A20406	13/32"	10.3 MM	.406	ALLOY	25 PCS
6453HH	16.56"	10	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	25 PCS
6630	24.5"	17	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	10 PCS
A6630	25"	17	3/8"	10 MM	.375	A20406	13/32"	10.3 MM	.406	ALLOY	10 PCS
6640	28"	15	7/16"	11 MM	.437	20437	7/16"	11 MM	.437	CARBON	10 PCS
A6640	28"	15	7/16"	11 MM	.437	A20437	7/16"	11 MM	.437	ALLOY	10 PCS
6650	34.4"	19	7/16"	11 MM	.437	20437	7/16"	11 MM	.437	CARBON	10 PCS
A6650	34.4"	19	7/16"	11 MM	.437	A20437	7/16"	11 MM	.437	ALLOY	10 PCS
6660	37.75"	19	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6660	39.3"	19	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6670	44.5"	22	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6670	44.5"	22	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS

(ROUND TWIST LINK CROSS CHAIN CONTINUES ON PAGE 112)

REPLACEMENT CROSS CHAIN

NOTE: PREMIUM NUMBERS IN BLUE

ROUND TWIST LINK

(CONTINUED FROM PAGE 111)

SEE PAGE 110 FOR HOW TO MEASURE

(INSIDE OF HOOK TO INSIDE OF HOOK)



CROSS CHAIN SPECIFICATIONS

HOOK SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
6680	51.5"	26	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6680	51.5"	26	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6690	56.7"	29	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6690	56.7"	29	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6692	60.3"	31	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6692	60.3"	31	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6693	44.75"	22	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6693	44.75"	22	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6694	53.2"	27	17/32"	13.5 MM	.531	20531	17/32"	13.5 MM	.531	CARBON	5 PCS
A6694	53.2"	27	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
7213	21.57"	13	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
7213CL	21.75"	15	9/32"	7 MM	.281	A20281	9/32"	7 MM	.281	ALLOY	25 PCS
7213LM	21.5"	13	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
7214	22.96"	14	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
7214LM	23"	14	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
7215	24.35"	15	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
7215CL	24.5"	17	9/32"	7 MM	.281	A20281	9/32"	7 MM	.281	ALLOY	25 PCS
7215LM	24.35"	15	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
7216	31.3"	20	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
7420	23.66"	16	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	10 PCS
A7420	23.66"	16	3/8"	10 MM	.375	A20406	13/32"	10.3 MM	.406	ALLOY	10 PCS
7426	27.44"	19	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	10 PCS
A7426	27.44"	19	3/8"	10 MM	.375	A20406	13/32"	10.3 MM	.406	ALLOY	10 PCS
7465XD	17.4"	10	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
9562	31.29"	17	7/16"	11 MM	.437	20437	7/16"	11 MM	.437	CARBON	10 PCS
9567	39.1"	22	7/16"	11 MM	.437	20437	7/16"	11 MM	.437	CARBON	10 PCS

V-BAR LINK



CROSS CHAIN SPECIFICATIONS

HOOK SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
5814	10.18"	7	13/64"	5.2 MM	.207	20230	15/64"	5.9 MM	.230	CARBON	25 PCS
5820	12.02"	9	13/64"	5.2 MM	.207	20230	15/64"	5.9 MM	.230	CARBON	25 PCS
5822	12.94"	10	13/64"	5.2 MM	.207	20230	15/64"	5.9 MM	.230	CARBON	25 PCS
6819	12.12"	9	7/32"	5.5 MM	.218	20250	1/4"	6.4 MM	.250	CARBON	25 PCS
6821	13.12"	10	7/32"	5.5 MM	.218	20250	1/4"	6.4 MM	.250	CARBON	25 PCS
6822	14.37"	9	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6825	15.12"	12	7/32"	5.5 MM	.218	20250	1/4"	6.4 MM	.250	CARBON	25 PCS
6830	25"	17	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	10 PCS
6853	15.64"	10	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6858	17.25"	11	9/32"	7 MM	.281	20375	3/8"	10 MM	.375	CARBON	25 PCS
6859	18.12"	12	9/32"	7 MM	.281	20312	5/16"	8 MM	.312	CARBON	25 PCS
6860	16.01"	9	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6863	17.4"	10	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS
6866	18.79"	11	5/16"	8 MM	.312	20375	3/8"	10 MM	.375	CARBON	25 PCS

REPLACEMENT CROSS CHAIN

NOTE: PREMIUM NUMBERS IN BLUE

SEE PAGE 110 FOR HOW TO MEASURE
(INSIDE OF HOOK TO INSIDE OF HOOK)

SQUARE LINK



CROSS CHAIN SPECIFICATIONS

HOOK SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
6221SL	14.18"	11	7/32"	5.5 MM	.218	20312	5/16"	8 MM	.312	ALLOY	25 PCS
6225SL	15.4"	13	7/32"	5.5 MM	.218	20312	5/16"	8 MM	.312	ALLOY	25 PCS
6251SL	14.5"	9	9/32"	7 MM	.281	A20312AL	5/16"	8 MM	.312	ALLOY	25 PCS
6253SL	17"	11	9/32"	7 MM	.281	A20312AL	5/16"	8 MM	.312	ALLOY	25 PCS
6255SL	12"	7	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
6259SL	19"	13	9/32"	7 MM	.281	A20312AL	5/16"	8 MM	.312	ALLOY	25 PCS
6260SL	16.04"	9	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
6263SL	18.76"	11	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
6268SL	21.48"	13	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
E6520S	27"	17	5/16"	8 MM	.312	A20406	13/32"	10.3 MM	.406	ALLOY	25 PCS
E6520N	26"	17	5/16"	8 MM	.312	A20406	13/32"	10.3 MM	.406	ALLOY	25 PCS
E6530S	26.5"	17	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	10 PCS
E6530N	25.75"	15	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	5 PCS
E6540SH	32.25"	17	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	10 PCS
E6540N	32"	17	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6550SH	35.5"	19	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	10 PCS
E6550N	35.5"	19	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6560SH	38.69"	21	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6560N	39"	19	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6570SH	45.72"	25	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6570N	44.5"	25	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6580SH	51.83"	27	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6580N	52"	27	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6590SH	56.7"	29	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
E6590N	56.7"	29	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
7213SL	21.57"	13	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
7215SL	24.25"	15	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	25 PCS
7419SL	21.3"	13	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	10 PCS

TWISTED SQUARE LINK



CROSS CHAIN SPECIFICATIONS

HOOK SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
6221SLTWIST	13.25"	10	7/32"	5.5 MM	.218	A20281	9/32"	7 MM	.281	ALLOY	25 PCS
6225SLTWIST	15"	12	7/32"	5.5 MM	.218	A20281	9/32"	7 MM	.281	ALLOY	25 PCS
6251SLTWIST	14.5"	9	9/32"	7 MM	.281	A20312AL	5/16"	8 MM	.312	ALLOY	25 PCS
6253SLTWIST	15.5"	10	9/32"	7 MM	.281	A20312AL	5/16"	8 MM	.312	ALLOY	25 PCS
6260SLTWIST	16.01"	9	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
6263SLTWIST	17.25"	10	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS
7213SLTWIST	22"	13	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	25 PCS
7214SLTWIST	23.5"	14	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	25 PCS
7215SLTWIST	24.75"	15	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	25 PCS

REPLACEMENT CROSS CHAIN

NOTE: PREMIUM NUMBERS IN BLUE

STUDDED LINK

SEE PAGE 110 FOR HOW TO MEASURE
(INSIDE OF HOOK TO INSIDE OF HOOK)



CROSS CHAIN SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOO K STOCK NUMBER	HOO K WIRE SIZE (INCHES)	HOO K METRIC WIRE SIZE	HOO K GAUGE	STEEL TYPE	STD PKG
6912	15.13"	10	9/32"	7 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	25 PCS
6913	16.13"	11	9/32"	7 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	25 PCS
6915	18.63"	13	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6915L	18.25"	13	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6916L	19.75"	14	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6918L	22.2"	16	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6920L	23.75"	18	9/32"	7 MM	.281	A20312	5/16"	8 MM	.312	ALLOY	25 PCS
6923	17.13"	11	5/16"	8 MM	.312	A20393	3/8"	10 MM	.393	ALLOY	25 PCS
6925	19.38"	13	5/16"	8 MM	.312	A20393	3/8"	10 MM	.393	ALLOY	25 PCS
6926	20.63"	14	5/16"	8 MM	.312	A20393	3/8"	10 MM	.393	ALLOY	25 PCS
6930N	26"	14	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	10 PCS
6931	23"	16	5/16"	8 MM	.312	A20393	3/8"	10 MM	.393	ALLOY	10 PCS
6932	25.13"	18	5/16"	8 MM	.312	A20393	3/8"	10 MM	.393	ALLOY	10 PCS
6935N	17.4"	11	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	10 PCS
6940N	29.75"	15	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	10 PCS
6950N	36.4"	19	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	10 PCS
6960N	39.11"	17	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6970N	44.5"	23	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
6980N	51.5"	27	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
7915	24.5"	18	5/16"	8 MM	.312	A20375	3/8"	10 MM	.375	ALLOY	25 PCS

HOO K SPECIFICATIONS

ROUND TWIST H-PATTERN



CROSS CHAIN SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOO K STOCK NUMBER	HOO K WIRE SIZE (INCHES)	HOO K METRIC WIRE SIZE	HOO K GAUGE	STEEL TYPE	STD PKG
DUO292	18.25"	9	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO293	20"	10	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO294	22"	11	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO295	23.3"	12	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO296	25.25"	13	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO297	26.75"	14	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO298	31.5"	17	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO299	35.25"	19	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO301	38"	21	3/8"	10 MM	.375	20406	13/32"	10.3 MM	.406	CARBON	5 PCS
DUO292LW	18.5"	9	5/16"	7.8 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	5 PCS
DUO293LW	20"	10	5/16"	7.8 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	5 PCS
DUO295LW	23.5"	12	5/16"	7.8 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	5 PCS
DUO294LW	21.75"	11	5/16"	7.8 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	5 PCS
DUO297LW	26.75"	14	5/16"	7.8 MM	.281	A20344	11/32"	9 MM	.344	ALLOY	5 PCS

HOO K SPECIFICATIONS

REPLACEMENT CROSS CHAIN

NOTE: PREMIUM NUMBERS IN BLUE

SEE PAGE 110 FOR HOW TO MEASURE
(INSIDE OF HOOK TO INSIDE OF HOOK)

SQUARE LINK H-PATTERN

NOTE: 8914 - 8922 PATTERNS ARE A SQUARE LINK H-PATTERN DESIGN.
LINK-OVER-LINK ONLY AVAILABLE ON 8901 - 8911 PATTERNS.



LINK-OVER-LINK PATTERN PICTURED

CROSS CHAIN SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
8901	26"	13	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	1 EACH
8902	29.08"	15	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	1 EACH
8903	28.75"	15	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8904	32"	17	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8905	35.5"	19	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8906	37.5"	21	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8907	36.5"	15	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8908	38.75"	17	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8909	42"	19	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8911	47.71"	21	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8914	18"	11	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	1 EACH
8918	23.25"	15	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	1 EACH
8922	28.25"	19	5/16"	8 MM	.312	A20375AL	3/8"	10 MM	.375	ALLOY	1 EACH

HOOK SPECIFICATIONS

STUDDED H-PATTERN




CROSS CHAIN SPECIFICATIONS

CROSS CHAIN STOCK NUMBER	INSIDE LENGTH HOOK TO HOOK (INCHES)	NO. OF LINKS	WIRE SIZE (INCHES)	METRIC WIRE SIZE	GAUGE	HOOK STOCK NUMBER	HOOK WIRE SIZE (INCHES)	HOOK METRIC WIRE SIZE	HOOK GAUGE	STEEL TYPE	STD PKG
8501	26"	14	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	5 PCS
8502	29.1"	16	3/8"	10 MM	.375	A20437	7/16"	11 MM	.437	ALLOY	5 PCS
8503	29.5"	15	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
8504	32.9"	17	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
8505	36.1"	19	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	5 PCS
8506	39.3"	21	7/16"	11 MM	.437	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8507	35.6"	15	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8508	39.6"	17	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8509	43.6"	19	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8510	45.6"	20	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH
8511	47.6"	21	17/32"	13.5 MM	.531	A20531	17/32"	13.5 MM	.531	ALLOY	1 EACH

HOOK SPECIFICATIONS

VISIT OUR NEW WEBSITE!

YOUR ULTIMATE TOOL FOR TIRE CHAIN INFORMATION!




EASY!

Browse our large selection of products and search by our part number!

HELPFUL!

View installation videos and instructions. Find specifications on all our products. Look up by part number for all tire fitments.


Industry information, warranties, warnings, terms and conditions of sale and other important information available at the click of your finger. Don't forget to sign up for our newsletter for new products, updates and specials!



FAST!

Create a shortcut on your desktop and bookmark our page for instant access!

ALSO DESIGNED FOR USE
WITH YOUR MOBILE DEVICE!



SCAN QR CODE TO GO
DIRECTLY TO OUR WEBSITE


For more information, up-to-date tire fitments, installation videos or to download this catalog to your computer; just visit our website at:

WWW.QUALITYCHAINCORP.COM

STATE CHAIN REQUIREMENTS FOR TRUCKS


Note: This is a guide only. Actual chain requirements vary from state to state.

DUAL AXLE CHAINING DIAGRAM:



Chains on trailers may be staggered front and back.

All drive wheels may be required to use chains if conditions warrant.



Two outside wheels must be chained.

All drive wheels may be required to use chains if conditions warrant.


SINGLE AXLE CHAINING DIAGRAM:

LINK CHAIN REQUIRED ON ALL DRIVE TIRES



Chains on trailers may be staggered front and back.

Drive axle must be chained.



Two outside wheels must be chained.

Drive axle must be chained.



COMMON CHAIN LAW STATES:

PLEASE VISIT EACH STATE'S INDIVIDUAL DEPARTMENT OF TRANSPORTATION WEBSITE FOR SPECIFIC CHAIN REGULATIONS

OREGON: WWW.TRIPCHECK.COM/PAGES/MINIMUM-CHAIN-REQUIREMENTS.ASP

WASHINGTON: WSDOT.WA.GOV/TRAVEL/COMMERCIAL-VEHICLE-ROUTE-RESTRICTIONS/COMMERCIAL-VEHICLE-CHAIN-REQUIREMENTS

CALIFORNIA: DOT.CA.GOV/TRAVEL/WINTER-DRIVING-TIPS/CHAIN-REQUIREMENTS

NEVADA: WWW.NEVADADOT.COM/HOME/SHOWDOCUMENT?ID=96

WYOMING: DOT.STATE.WY.US/home/travel/winter/chain_law.html

COLORADO: CSP.COLORADO.GOV/CHAIN-LAW-INFORMATION

FINDING YOUR TIRE SIZE

THE TIRE SIZE CAN ALWAYS BE FOUND ON THE SIDEWALL OF A TIRE.
IT USUALLY LOOKS LIKE THE EXAMPLE SHOWN: P235/70R15



TIRE TYPE: For example "P" for passenger or "LT" for Light Truck.


TIRE WIDTH: The width of the tire in millimeters (mm).

ASPECT RATIO: The sidewall height (from rim to tread), shown as a percentage of the tire width. In this example, the sidewall height is 70% of the tire width.

TIRE CONSTRUCTION: "R" stands for Radial. This is not as important when choosing a winter traction device.

RIM DIAMETER: The diameter of the rim in inches (in).

MINIMUM CLEARANCE REQUIREMENTS



PASSENGER AND LIGHT TRUCK

SAE CLASS	MINIMUM TREAD FACE CLEARANCE (A)	MINIMUM SIDEWALL CLEARANCE (C)
CLASS "S"	1.46" / 37 MM	0.59" / 15 MM
CLASS "U"	1.97" / 50 MM	0.91" / 23 MM
CLASS "W"	2.5" / 63.5 MM	1.5" / 38.1 MM

The minimum clearance specified must be maintained around spring clips, spring bolts, fenders, braces, splash pans, fuel lines, brake lines, brake controls and other mechanical components.

The tire size must be known in order to select a tire chain of correct fit. It is important to check your vehicle owner's manual. The restricted wheel clearances in most of today's vehicles may require the use of SAE Class "S" tire chains. Please refer to your owner's manual for specific tire chain recommendations for your vehicle.

DEFINITIONS OF SAE CLASSIFICATIONS

S.A.E Classifications refers to the area around the drive tires that is allowed for tire chains and cables. This classification is created by the Society of Automotive Engineers and almost every vehicle since the mid 90's has been placed in a category. It is always recommended the vehicle owner look in their owner's manual before purchasing a traction product.



Regular (non-reinforced) passenger tire chains and cables for vehicles with restricted wheel well clearances.



Regular (non-reinforced) and lug reinforced passenger tire chains for vehicles with regular (non-restricted) wheel well clearances.



Those passenger tire chains that use light truck components, as well as some light truck chains.

STANDARD CHAIN SPECIFICATIONS

STOCK NUMBER	X-CHAIN PER 1/2 PAIR	X-CHAIN DIAMETER	LINKS PER X-CHAIN	X-CHAIN WIDTH	SIDE CHAIN LENGTH	STOCK NUMBER	X-CHAIN PER 1/2 PAIR	X-CHAIN DIAMETER	LINKS PER X-CHAIN	X-CHAIN WIDTH	SIDE CHAIN LENGTH
LIGHT TRUCK / SUV						LOADER / GRADER					
1661	12	0.385	N/A	13.5"	75"	2612 (V)	14	0.375	17	25"	114.6"
1663	14	0.385	N/A	14.5"	85"	2615(V)	16	0.375	17	25"	126.1"
1665	12	0.385	N/A	14.5"	74.5"	2624 (V)	13	0.437	15	28"	121.5"
1669	13	0.385	N/A	14.5"	80"	2627 (V)	15	0.437	15	28"	138.9"
1673	12	0.385	N/A	15.5"	75"	2627	14	0.437	19	34.4"	128"
1675	14	0.385	N/A	15.5"	85"	2633	15	0.437	19	34.4"	138.9"
1678	15	0.385	N/A	15.5"	90.5"	2636	18	0.437	19	34.4"	164.9"
1679	14	0.385	N/A	16.25"	85"	2642	15	0.531	19	39.3"	143.7"
1680	14	0.385	N/A	17.5"	85"	2645	17	0.531	22	44.5"	161.7"
1681	15	0.385	N/A	17"	90"	2657	17	0.531	26	51.5"	161.7"
2214(QC), 2814(QC)	15	0.218	10	13.12"	86.2"	2672	18	0.531	26	51.5"	170.7"
2216(QC), 2816(QC)	12	0.218	10	13.12"	71.3"	TRACTOR					
2219(QC), 2819(QC)	13	0.218	10	13.12"	77.5"	DUO210	7	0.375	10	20"	102"
2221(QC), 2821(QC)	14	0.218	10	13.12"	80.9"	DUO214	7	0.375	9	18.25"	108.5"
2228(QC), 2828(QC)	14	0.218	12	15.12"	82.7"	DUO218	9	0.375	10	20"	131.9"
2229(QC), 2829(QC)	12	0.218	12	15.12"	72.3"	DUO226	8	0.375	9	18.25"	119.1"
2435HH	9	0.312	8	14.62"	72.8"	DUO229	8	0.375	10	20"	119.1"
2437HH	10	0.312	8	14.62"	79.3"	DUO239	7	0.375	12	23.3"	108.5
2439HH	10	0.312	9	16.01"	77.2"	DUO240	8	0.375	12	23.3"	119.1"
2440HH	11	0.312	9	16.01"	84"	DUO241	6	0.375	11	22"	90"
3210(QC), 3810(QC)	13	0.218	12	15.12"	76.4"	DUO242	9	0.375	11	22"	131.9"
3227(QC), 3827(QC)	10	0.281	10	15.62"	76.6"	DUO246	11	0.375	11	22"	161.6"
3228(QC), 3828(QC)	11	0.281	10	15.62"	82"	DUO250	9	0.375	12	23.3"	131.9"
3229(QC), 3829(QC)	10	0.281	12	18.12"	77.4"	DUO252	10	0.375	12	23.3"	144.6"
3231(QC), 3831(QC)	11	0.281	12	18.12"	84"	DUO256	13	0.375	14	26.75"	206.6"
3235(QC), 3835(QC)	12	0.281	12	18.12"	91.2"	DUO262	9	0.375	14	26.75"	131.9"
TRUCK						DUO266	10	0.375	14	26.75"	144.6"
2141SLC	14	0.281	9	14.60"	106.5"	DUO268	8	0.375	17	31.5"	123.4"
2145SLC	15	0.281	9	14.60"	113.3"	DUO269	9	0.375	17	31.5"	131.9"
2147SLC	13	0.281	11	16.75"	106"	DUO270	11	0.375	14	26.75"	161.6"
2149SLC	15	0.281	11	16.75"	115.6"	DUO271	9	0.375	17	31.5"	140.4"
2239(QC), 2839(QC)	13	0.281	9	14.37"	98.8"	DUO272	11	0.375	17	31.5"	165.9"
2241(QC), 2841(QC)	14	0.281	9	14.37"	106.5"	DUO273	10	0.375	17	31.5"	148.9"
2245(QC), 2845(QC)	15	0.281	9	14.37"	113.3"	DUO276	12	0.375	19	35.25"	172.3"
2247(QC), 2847(QC)	14	0.281	10	15.62"	106.5"	DUO277	13	0.375	17	31.5"	198"
2249(QC), 2849(QC)	15	0.281	10	15.62"	115.6"	DUO278	9	0.375	21	39.5"	180"
2251(QC), 2851(QC)	14	0.312	9	16.01"	114"	DUO280	9	0.375	19	35.25"	130.2"
2255(QC), 2855(QC)	14	0.312	10	17.40"	115.9"	DUO281	10	0.375	19	35.25"	145.4"
2441HH	11	0.375	11	17.36"	88.9"	SKID STEER					
2445HH	12	0.375	11	17.36"	97.1"	1501-2	18	0.312	9	16.01"	77.87"
2448HH	13	0.375	11	17.36"	103.9"	1502-2	18	0.312	12	20.36"	77.87"
2452HH	14	0.375	11	17.36"	110.2"	1503-2	22	0.312	12	20.36"	92.36"
3255(QC), 3255LMC	14	0.312	13	21.57"	106.2"	ATV / UTV					
3261(QC), 3261LMC	16	0.312	14	22.96"	119.8"	ATV-A	9	.207	12	14"	52"
3269(QC), 3269LMC	13	0.312	15	24.35"	101.8"	ATV-B	10	.207	12	14"	54"
3271(QC), 3271LMC	14	0.312	15	24.35"	106.9"	ATV-C	10	.207	12	14"	56"
						ATV-D	12	.250	12	15.12"	67.5"



CORPORATE HEADQUARTERS - HILLSBORO, OR




ADDITIONAL WAREHOUSES

- ROCKLIN, CA
- CEDAR RAPIDS, IA

**FOR MORE INFORMATION, UPDATED TIRE FITMENTS, INSTALLATION VIDEOS OR TO DOWNLOAD THIS CATALOG;
VISIT OUR WEBSITE AT: WWW.QUALITYCHAINCORP.COM**

PROUDLY OFFERING

YOUR ONE-STOP SHOP FOR ALL CARGO CONTROL PRODUCTS



**Go online and visit our
cargo control website!
QualityCargoControl.com**



**SPECIALIZING IN:
FLATBED, INDUSTRIAL,
INTERIOR VAN,
AUTO HAULING,
HARDWARE
& CUSTOM STRAPS**



**TIRE CHAINS FOR ALL YOUR NEEDS
PRODUCT AND SERVICE SECOND TO NONE!**